

College Station Independent School District

Success...each life...each day...each hour

PURCHASING OFFICE

INTER-DEPARTMENTAL MEMO

DATE:

December 1, 2023

TO:

Amy Drozd, CFO

FROM:

Carmella Shafer, Director of Purchasing

SUBJECT:

Purchase School Buses (9) 77 passenger and (7) 54 passengers for a total of sixteen

(16) buses

The 2023 Bond program provides for the purchase of school buses to replace existing buses and add districtwide transportation capacity. The Transportation Department requested quotes from Longhorn Bus Sales based on our fleet standards as well as state required standards for nine (9) 77 passenger and seven (7) 54 passenger buses. The buses will be 2025 models and have an estimated 1-year build and delivery time. Standardizing the fleet provides additional financial and time savings because the Transportation department can stock parts to reduce downtime as well as the mechanics have already received training and are experienced working on them.

No. Passengers	Price Per Bus	Quantity	Totals
77 Passenger	\$152,520.00	9	\$ 1,372,680.00
54 Passenger	\$146,580.00	7	\$ 1,026,060.00
BuyBoard Fee \$800			
	Total	for 16 Buses	\$ 2,399,540.00

The quote does not include the following additional components that will be added upon delivery: routing hardware and software, child accountability components, and fuel management system components.

The quotes are based on BuyBoard purchasing cooperative contract 630-20. All items on this contract have been competitively bid and awarded based on state statutes and meets the competitive bid requirements stipulated in Texas Government Code, Section 791.025.

It is the recommendation of Carmella Shafer, Director of Purchasing, and Hector Silva, Director of Transportation that we purchase the buses in the amount of \$2,399,540.00 from Longhorn Bus Sales using 2023 bond funds.

Carmella Shafer, Director of Purchasing

Hector Silva, Director of Transportation



CE SCHOOL BUS

Sales Proposal For:

College Station

Presented By:

LONGHORN BUS SALES

Prepared For: College Station Transportation Dept 1812 Welsh College Station, TX 77840-

(979)764 - 5408

Reference ID: 54P DSL 4WC

Presented By: LONGHORN BUS SALES LINDA BLUME 9100 N LOOP E **HOUSTON TX 77029 -**(713)631-9306

Thank you for the opportunity to provide you with the following quotation on a new IC Corporation vehicle. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile 2025 CE SCHOOL BUS (PB110)

AXLE CONFIG:

4X2

APPLICATION:

School Transportation, Special Needs

MISSION:

Requested GVWR: 29800. Calc. GVWR: 29800

Calc. Start / Grade Ability: 24.84% / 1.93% @ 55 MPH

Calc. Geared Speed: 88.2 MPH

Omit Item (Clutch & Control)

DIMENSION:

Wheelbase: 217.00, CA: N/A, Axle to Frame: 126.00

ENGINE, DIESEL:

{Cummins B6.7 250} EPA 2024, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM

Governed Speed, 250 Peak HP (Max), School Bus Only

TRANSMISSION, AUTOMATIC:

{Allison 2500 PTS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less

PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max. School Bus

CLUTCH:

AXLE, FRONT NON-DRIVING:

(Meritor MFS-10-122A) I-Beam Type, 10,000-lb Capacity

AXLE, REAR, SINGLE:

{Dana Spicer S140} Single Reduction, 19,800-lb Capacity, 190 Wheel Ends Gear Ratio: 4.88

TIRE, FRONT:

(2) 255/70R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 566 rev/mile, 81 MPH, All-

Position

TIRE, REAR:

(4) 255/70R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 566 rev/mile, 81 MPH, All-

Position

SUSPENSION, REAR, AIR, SINGLE: {International IROS} 21,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers Mounted

Outside the Rails

PAINT:

Cab schematic 100NB

Location 1: 4421, School Bus Yellow (Std)

Chassis schematic N/A

<u>Code</u> PB11000	<u>Description</u> Base Chassis, Model CE SCHOOL BUS with 217.00 Wheelbase, N/A CA, and 126.00 Axle to Frame.	
BODY PLANS		
47AEU	BODY, BUS Conventional; 78" Headroom, 26'8" Body Length, +9 Section Front and Rear, 59 Passenger, 217/218 WB	
OBD001	BODY PLAN, SPECIAL NEEDS TBD - BODY PLAN REQUESTED	
49001	BODY PLAN, APPROVED VARIATION Number 001	
AXLE CONFIGURATION	I	
1ANA	AXLE CONFIGURATION {Navistar} 4x2	
ENGINE		
12EYH	ENGINE, DIESEL (Cummins B6.7 250) EPA 2024, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 250 Peak HP (Max), School Bus Only	
12VJR	EMISSION, CALENDAR YEAR {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2024	
12XCS	CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty	
12WZE	CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations	
12WVG	EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood	
12XCC	RADIATOR Aluminum, 2-Row, Down Flow, Front to Back System, 640 Sqln Louvered, with 383 Sqln Charge Air Cooler, Includes In-Tank Oil Cooler	
	Includes : RADIATOR HOSES Premium, Rubber	
12TSY	FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On	
	Includes : FAN Nylon	
12VCE	AIR CLEANER Single Element, Fire Retardant Media	
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	
12VVN	CRUISE CONTROL Electronic	
12VYV	IDLE MANAGEMENT SYSTEM Ramp Engine Speed with Air Condition On, in Neutral and Parking Brake Set, Accommodation Package	
12WPV	OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines	
12UGN	THROTTLE, HAND CONTROL Electronic	
TRANSMISSION		
13BBP	TRANSMISSION, AUTOMATIC {Allison 2500 PTS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus	
13WVW	NEUTRAL AT STOP OMIT	
13WYY	SHIFT CONTROL PARAMETERS (Allison) 1000 or 2000 Series Transmissions, Performance Programming	
13WLN	TRANSMISSION OIL Synthetic; 20 thru 28 Pints	

3

Code

Description

13WEX

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, for Allison 1000 & 2000 Series

Transmission

CLUTCH

11001

CLUTCH Omit Item (Clutch & Control)

REAR AXLES, SUSPENSIONS

14AJJ AXLE, REAR, SINGLE {Dana Spicer S140} Single Reduction, 19,800-lb Capacity, 190 Wheel Ends . Gear

Ratio: 4.88

14TDV SUSPENSION, REAR, AIR, SINGLE (International IROS) 21,000-lb Capacity, 9.25" Ride Height, with Shock

Absorbers Mounted Outside the Rails

14WAW FLAT FLOOR EFFECTS for Air Suspension; with Conventional Bus Models

FRONT AXLES

2ASH AXLE, FRONT NON-DRIVING (Meritor MFS-10-122A) I-Beam Type, 10,000-lb Capacity

FRONT SUSPENSIONS

3ADB SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 10,000-lb Capacity, with Shock

Absorbers

<u>Includes</u>

: SPRING PINS Rubber Bushings, Maintenance-Free

CABS, COWLS, BODIES

16010 COWL Flat Back

16VKB CAB INTERIOR TRIM Classic, for Day Cab

16GEG GAUGE CLUSTER Premium Level; English with English Electronic Speedometer

<u>Includes</u>

: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip

Hours, MPG, Distance to Empty/Refill for

: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure

Gauge, Primary and Secondary Air Pressure or Auxiliary Air Pressure (if Air Equipped)

: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage

(Visual and Audible), Low Air Pressure, Primary and Secondary (if Air Equipped)

16HLJ GAUGE, DEF FLUID LEVEL

16HGH GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission

16BAL HEATER

16563 HEATER SHUT-OFF VALVES (2) Ball Valve Type

16XJP INSTRUMENT PANEL Wing Panel

16HKT IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

16VUY MONITOR, TIRE PRESSURE System Gives Warning that Tire Pressure is Below Set Pressure, Monitors Tire

4

Pressure of Each Tire with Temperature Compensation, Data Displayed in the LCD of the Cluster, for 4x2 Axle

Configuration, Does Not Include Lift Axles or Spare Wheels

16VVJ WINDSHIELD Three Piece, Bonded, with Shaded Band

Code FRAMES	Description	
1CAC	FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm); 489.2" (12425mm) Maximum OAL	
1LSG	BUMPER, FRONT Contoured, Steel, Painted Gloss Black, Severe Duty	
	Notes : Bumper Thickness is .25"	
1LNT	CROSSING GATE, FRONT Omit Item	
1SAL	CROSSMEMBER, REAR, AF (1)	
1570	TOW HOOK, FRONT (2) Frame Mounted	
1WRP	TOW HOOK, REAR (2) Mounted on Lower Rail Flange	
1WHT	WHEELBASE RANGE 193" (490cm) Through and Including 217" (550cm)	
BRAKES		
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications	
	Includes : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6	
4AZS	AIR BRAKE ABS (Bendix AntiLock Brake System) 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control	
4GBL	BRAKE, PARKING (Bendix Intellipark) Electronic Park Brake, for Truck or Bus Applications	
4XDD	BRAKES, FRONT {Meritor 15X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 15" X 5", 13,200-lb Capacity	
4EXP	BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 Sqln	
4LAG	SLACK ADJUSTERS, FRONT {Gunite} Automatic	
4XDR	BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle	
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Sqln Spring Brake	
4LGG	SLACK ADJUSTERS, REAR {Gunite} Automatic	
4SPA	AIR COMPRESSOR (Cummins) 18.7 CFM	
4EDN	AIR DRYER {Bendix AD-9SI} with Heater, Includes Safety Valve	
4VLE	AIR DRYER LOCATION Mounted Inside Engine Compartment, Right Side	
4VLY	AIR TANK LOCATION (1) Mounted Inside & Below Left Rail, Back of Cab	
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank	
4WZT	GVWR LIMITATION FOR BUS with Air Brakes, Limited to 33,000-lbs Maximum to meet FMVSS 121 Requirements, for Conventional Bus	
4WJP	PARKING BRAKE INTERLOCK with Electronic Park Brake, Parking Brake Cannot be Released Until Ignition Switch is in "On" Position and Service Brake Pedal is Applied, Use with Air Brake Chassis Only	

5

Code STEERING	<u>Description</u>	
5PSA	STEERING GEAR {Sheppard M100} Power	
5708	STEERING COLUMN Tilting	
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black	
DRIVELINES		
6DGA	DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2	
6901	PROPSHAFT GUARD	
EXHAUST SYSTEMS		
7ВМК	EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Under Right Rail, for Single Long Horizontal Tail Pipe	
7WCX	HEAT SHIELD Between Exhaust & Fuel Tank, Mounted to AF Crossmember	
7WBL	TAIL PIPE (1) Horizontal, Long, Exits Left Side Through Bumper	
ELECTRICAL SYSTEMS		
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment	
	Includes : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : MISCELLANEOUS FEATURES Modular, Loom Protected, Grommets in all Applicable Body Openings, Assembled in Computer Assisted Fixture which Verifies Continuity and Correct Assembly Prior to Installation : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : STARTER SWITCH Electric, Key Operated : TURN SIGNAL SWITCH Self-Cancelling with Lane Change Feature : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WIRING, CHASSIS Color Coded and Continuously Numbered	
8GXN	ALTERNATOR {Leece-Neville BLP4024N} Brushless, 12 Volt, 325 Amp Capacity, Pad Mount, with Remote Sense	
8TTK	BATTERY BOX Steel, with Sliding Tray, 25.25" Wide, for Standard Batteries, 1-3 Battery Capacity, Mounted Left Side Behind Front Axle Perpendicular to Frame Rail	
8MJU	BATTERY SYSTEM (Fleetrite) Maintenance-Free, (3) 12-Volt 2850CCA Total, Top Threaded Stud	
8XDX	BK WARN IND,PARK BK NOT SET Visual and Audible Alarm, Active Upon Ignition Off and Parking Brake Not Set, Reminder to Set Parking Brake	
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	
8TUT	COLLISION MITIGATION SYSTEM Omit	
8WXB	HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position	
8XKC	HEADLIGHTS Halogen, with Daytime Running Lights, Automatic Twilight Controlled	
8WRB	HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On	
8540	HORN, ELECTRIC (2) Trumpet Style	

6

Code Description 8WWJ INDICATOR, LOW COOLANT LEVEL with Audible Alarm RADIO AM/FM/USB Input/Auxiliary Input, Includes Wiring and Antenna, with Public Address System 8RRC 8XKL STARTING MOTOR (Mitsubishi Electric Automotive America 90P47) 12-Volt, with Soft-Start **FRONT END** 9WBW FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes 9HCW GRILLE Molded in Black 9WAB HOOD TILT ASSIST {EASY TILT} Mechanical 9AAB LOGOS EXTERIOR Model Badges 9AAE LOGOS EXTERIOR, ENGINE Badges SPEEDOMETER, TOOLS, MISC 10020 **CHASSIS PAINT Full Chassis** 10AGB COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360 **10WUE** MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension 10060 PAINT SCHEMATIC, PT-1 Single Color, Design 100 Includes : PAINT SCHEMATIC ID LETTERS "NB" 10788 PAINT TYPE Urethane, One or Two Colors, Other than Imron or International. PROMOTIONAL PACKAGE 7 Year Unlimited Miles/km Warranty, Limited Time Program for Allison 2500 10XAK Series Transmission on School and Commercial Buses (Supplied directly through Allison) **FUEL TANKS** 15SLK FUEL TANK Top Draw, Steel, Rectangular, 65 US Gal (246L), Includes Protective Cage, Mounted Between Frame Rails and Behind Rear Axle DEF TANK 16.5 US Gal (62.5L) Capacity, Frame Mounted Outside Right Rail, Behind 0 Bow 15WEP 15LMR FUEL/WATER SEPARATOR (Racor 400 Series,) with Primer Pump, Includes Water-in-Fuel Sensor

WHEELS, TIRES - FRONT

15LRE

27DUW WHEELS, FRONT {Accuride 51408} DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud,

285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

7752528132 (2) TIRE, FRONT 255/70R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 566 rev/mile, 81 MPH, All-

LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle

Position

WHEELS, TIRES - REAR

28DUW WHEELS, REAR (Accuride 51408) DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud,

285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

7752528132 (4) TIRE, REAR 255/70R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 566 rev/mile, 81 MPH, All-

7

Position

Code BODY FEATURES	<u>Description</u>	
47BAK	BUMPER, REAR Painted, 12" High, 3/16" Thick	
47BAR	SUPPORTS, REAR BUMPER Bolted to Frame	
47AYB	BODY, REAR Includes Emergency Door	
47ARH	BOWS, ROOF 14 ga., One Piece Construction	
	<u>Includes</u> : BOWS, ROOF Positioned Floor Line to Floor Line, Threaded Through Roof Strainers and Drip Rail	
47BLU	FASTENERS, EXTERIOR MOUNTED Stainless Steel Screws; for All Exterior Body Lights, Body Exterior Rear View Mirrors, Bumper Mounted Crossing Gate and Body Mounted Stop Arms	
47APX	FASTENERS, HEADLINER Screws	
47AZK	FLOOR, BODY Flat	
47PBZ	HANDLE, ASSIST Windshield Side Mounted, Left and Right, Body Color	
47APR	HEADLINER, BODY Conventional; 25'11"-35'08" Body Length, Perforated Full Length with Sound Insulation Full Length	
47ARP	LIGHT BARS Plastic	
47BBH	LINING, SIDE INTERIOR, LOWER Embossed Steel, Clear Coated	
47AXR	RUB RAILS, BODY (4) Conventional; Steel, 25'2", 25'11", 26'8", 27'5" Body Length, Includes Snow Rail	
	Includes : RUB RAILS Full Length, Primer Coated (Both Sides), Attached to Body without Cuts or Splices	
47BBZ	SEALER Extra; Sidewall to Floor, In Wheel Pocket Area, and Rear Wall to Floor	
47AZC	SIDE SHEET, BODY, EXTERIOR Conventional, 16ga., Smooth, 25'2", 25'11", 26'8", 27'5", Body Length	
47ASZ	SKIRT, BODY Conventional, 20", 16ga., 25'2", 25'11", 26'8", 27'5" Body Length	
	Includes : SKIRT, BODY Extra Smooth Steel Supported by Floor Gussets	
47BLE	STEP, FRONT ENTRANCE DOOR 25 3/4" Depth; 14ga Steel, Formed Treads, Naviflex Finish	
47AUR	TIE DOWNS, BODY Grade 8 Bolts, Every Body Section	
	<u>Includes</u> : TIE DOWNS, BODY with Formed Tab that Fits into Floor Structure to Prevent Turning	
47DAJ	COVER, REAR DOOR INSIDE HANDLE Partial Coverage	
47DYL	DOOR, ENTRANCE, FRONT Air, Outward Opening, with Single Pane Glass	
47DWP	DOOR, LIFT Single, 43" x 69.79", Mounted Aft of Rear Wheel Pocket, with 78" Headroom	
47DAK	FASTENERS, REAR DOOR Bolts and Nutserts, Rear Door To Body	
47DDE	HANDLE, ASSIST, ENTRANCE DOOR Outside Entrance	
47DCW	HANDLE, EXTERIOR, LIFT DOOR Single Door, Yellow	
47DEY	HANDLE, EXTERIOR, REAR Emergency Door; Yellow	
47DDH	HOLD BACK, REAR DOOR Stationary, No Cables, with Plastic Cover	
47DDR	LATCH, LIFT DOOR Single, Three Point Slide Bar	
47DDU	LATCH, REAR DOOR One Point Slide Bar, Cam Operated, with One Inch Stroke	

Code Description LOCK, ENTRANCE DOOR in External Release, with Key 47EYL 47DEK LOCK, REAR DOOR with Ignition Starter Interlock LOCK, SINGLE LIFT DOOR with Ignition Starter Interlock 47DEV 47BDJ COMPARTMENT, DRIVER STORAGE Bin, Sized to Hold Three Ring Binder, Includes (1) USB-A Port and (1) **USB-C Port 47EBM** HOLD DOWN, BATTERY For Up To 3 Batteries 47LAU INSULATION, ROOF/SIDES/BULKHEAD 1.5" NOISE REDUCTION, ROOF BOW Conventional; Insulation, 25'2", 25'11", 26'8", 27'5" Body Lengths 47LAR 47MBA UNDERCOAT, BODY Fire Resistant, Water Based, TT-C-730 Spec : UNDERCOATING Performed Before and After Mounting on Chassis 47SPB ALPHA/NUMERIC DECAL GUIDE Quantity 021-30 ARROW, RR DOOR, INSIDE Decal; Red, .75" Stroke, Indicating Handle Direction 47MNT 47AJA **BODY CERTIFICATION TAG Metal** 47APJ BODY RATING TAG Metal; for State of Texas, Includes Design Capacity and Seat Capacity 47AJC BODY TAG, METAL Capacity to Include the Total Number of Passengers DECAL, HANDICAP (4) 6" x 6", 1 Mounted on Electrical Access Door, 1 Mounted on Lift Door Below Window 47AKZ Line, 1 on Left Bumper, 1 on Rear Door Between Top and Bottom Glass 47PLX LETTERS, DEF, I.D. Decal; "DEF ONLY", 1" Black, on DEF Filler Door 47MJR LETTERS, DOOR, REAR Decals: "EMERGENCY DOOR", 2" Black Letters Inside and Outside 47NGP LETTERS, FUEL I.D. Paint; "DIESEL FUEL", 2" Black, Adjacent to Fuel Filler Door 47MVA LETTERS, HEADER Decal; "WATCH YOUR STEP", 1" Black, Above Windshield 47MRU LETTERS, E/E WINDOW, LEFT (2) Decal Sets, "EMERGENCY EXIT", Black Inside and Outside 47NHL LETTERS, E/E WINDOW, RIGHT (2) Decal Sets, "EMERGENCY EXIT", Black, Inside and Outside 47MAV LETTERS, SCHOOL BUS SIDE Decal; "SCHOOL BUS"; in 8" Reflective Black Letters, Each Side 47MZB LETTERS, SCHOOL BUS FRONT/REAR Decal; OMIT "SCHOOL BUS"; with 8" Black Letters; on Front and Rear Cap 47MVC LETTERS, STEPWELL Decal, "WATCH YOUR STEP", 2.5" Black, Behind Door on Step Riser 47NTE LOGO, ROOF LINE Decal; Wing and Shield, First Body Section, Above Driver Window and Entrance Door Over Driver Window and Entrance Door 47NMG OPERATING INSTRUCTIONS, REAR Decal, Inside Rear Emergency Door 47NJA PAINT COLOR, BODY EXTERIOR 4421 School Bus Yellow 47NKM PAINT COLOR, BODY INTERIOR 9384 Spring White 47NJS PAINT COLOR, BUMPER Rear, 0001 Canyon Black 47NKD PAINT COLOR, ROOF 9219 Winter White, Beginning 5" Above Drip 47NAB PAINT COLOR, RUB RAILS 0001 Canyon Black

PAINT FLASHER BACKGRD 0001 Canyon Black

9

47NJM

<u>Code</u> 47NTY	Description PAINT HOOD AND FENDER To Match Body Exterior
47NKL	PAINT, RUB RAIL Flange to Flange
47NGW	SEAL, RUB RAILS Top Edge, All Rails
47NXH	STRIPING, E/E WINDOW, LEFT {3M} (02) Perimeter, 1" Yellow Fluorescent Diamond Grade
47NWU	STRIPING, E/E WINDOW, RIGHT {3M} (02) Perimeter, 1" Yellow Fluorescent Diamond Grade
47NXN	STRIPING, PERIMETER, REAR (3M) Emergency Door, 1" Yellow Fluorescent Diamond Grade
47NWR	STRIPING, REAR END (3M) 2" Yellow Fluorescent Diamond Grade
47NWT	STRIPING, ROOF HATCH, FRONT (3M) Decal, Perimeter, 1" Yellow Fluorescent Diamond Grade
47NWH	STRIPING, ROOF HATCH, REAR {3M} Decal, Perimeter, 1" Yellow Fluorescent Diamond Grade
47NWJ	STRIPING, SEATLINE (3M) 2" Yellow Fluorescent Diamond Grade
47MTY	WIRING DIAGRAM Schematic, Electrical
	Includes : ACCESS PANEL for Wiring Diagram Schematic Located on Inside of Electrical Panel Door, Below Driver Window
47SAZ	SUB FLOOR, PLYWOOD Conventional; B-B Marine Grade, Less Sealed Edges, 5/8", 5 Ply, for 25'2",25'11", 26'8" or 27'5" Body Lengths
47KEJ	DISARM, POST TRIP INSPECTION Button Located on Light Bar at Rear of Bus
47KEB	MONITOR, POST TRIP INSPECTION (Leave No Student Behind) Accessory Controlled, with Push Button Alarm Disable at Rear of Bus Prompts Driver to Walk to Back of Bus to Disable Alarm
47DNK	SWITCH, LOCATION Steering Wheel; Includes Master Flasher, Flasher On/Off, Red Override, and Door Control
	Includes : SWITCH, STEERING WHEEL, LIGHT Includes Illuminated Switches

BODY FEATURES

48ANT	WINDOW, DRIVER Laminated, Clear
48BJA	COLOR, WINDOW FRAME, PASS Passenger Window, Natural Aluminum Finish
48BAH	WINDOW, E/E, LEFT (2) Vertical Hinge
48BKP	WINDOW, E/E, RIGHT (2) Vertical Hinge
48AUL	WINDOW, PASSENGER, TINT Conventional; 28% Light, Laminated Glass, 78" Headroom, with 25'2", 25'11", 26'8", 27'5" Body Lengths
48ARD	WINDOW, SASH (9) 27" Sections, 9"x 23" Opening
48ASR	WINDOW, SASH +9 SECTIONS (3) 9" x 32 1/4" Opening
48APL	WINDOW, STOPS 12" Opening, Only with 78" Headroom
48PAY	AISLE POSITION Center, for balanced seating
48PBD	FLOOR COVERING, COLOR Brown
48PJR	FLOOR COVERING, TRIM Aluminum
48PJZ	FLOOR COVERING, TYPE (Koroseal) All Body Lengths

Code Description STEP TREADS (Koroseal) Pebble White Nosing Only, with Non-Metal Backing, used with Formed Treaded 48VVR Steps 48GZW AIR CONDITIONER, BODY IC Air, 120,000 BTU, Evaporators FM55 Front & Rear Flush Mounted, Condensers SMC3L Skirt Mounted, Compressors TM21, #16 Suction Hose, with EC4.0 Control System 48PKC HOSE CLAMPS, HEATER HOSE Constant Torque for Heater System 48UZK FAN, DEFOG LEFT OF DRIVER 6.50" Diameter, Black, Mounted on Driver Overhead Compartment, 2 Speed Switch in Panel 48PPP HEATER CUT OFF, VALVE INSIDE Brass Ball, Inside Driver Area 48UYC HEATER, REAR WALL, RT SIDE 80,000 BTU 48PNW HEATER, WATER PUMP (2 MPU 12) Self Priming, with Plastic Housing ROOF HATCH, FRONT (Specialty Hybrid Adv H1975-025-191-0F) Emergency Exit with Outside Release, 48UZN Alarm, English Decals 48UZT ROOF HATCH, REAR (Specialty Hybrid Adv H1975-025-191-0F) Emergency Exit with Outside Release, Alarm, English Decals 48PPS ROOF VENT, FRONT Static SEAT, DRIVER (National 2000) Air Suspension, High Back with Integral Headrest, Isolated, with 2 Position 48RYW Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Mechanical Lumbar Support, Includes Additional Back Padding Includes : SEAT BELT, DRIVER Adjustable D-Loop Seat Belt, Single Locking Retractor 48PXP UPHOLSTERY, BARRIER, TYPE (1-2) Prevaill, 42 oz. 48UXN UPHOLSTERY, DRIVER SEAT, COLOR Drivers Seat, Graphite 48PVA UPHOLSTERY, DRIVER SEAT, STYLE Plain, with Cloth Insert 48PWR UPHOLSTERY, DRIVER SEAT, TYPE Prevaill, 42 oz. **48BDS** BARRIER, CRASH, AFT ENTRY DOOR 39", 2 Leg 48RAL BARRIER, CRASH, AFT DRIVER 39", 1 Leg 48DPL HAND RAIL, ENTRANCE DOOR, AFT 1" Dia, Stainless Steel 48DPR HAND RAIL, ENTRANCE DOOR, FWD 1" Dia, Stainless Steel 48REP PANEL, MODESTY, AFT OF DRIVER Mounted Under Barrier 48BDG POUCH, CRASH BARRIER Full Width, Sewn Into Front Side of Barrier AFT of Driver Seat 48ACN SEAT BELT, DRIVER, COLOR with Blaze Orange Seat Belt Webbing 48USV SEAT BACK, PASSENGER High Back 48YRL SEAT,36",TRK,3PT,CHLD,LT {IMMI Seats SBR-U} (03) with 3 Point Seat Belts, Child Restraint 48XAG SEAT,36",WALL,3PT,CHLD,RT {BTI Seating System} (03) High Back, with 3 Point Seat Belts and Child Restraint 48YYC SEAT,39",TRK,3PT,LT {IMMI Seats SBR-U} (02) with 3 Point Seat Belts 48YAK SEAT,39",WALL,3PT,RT {BTI Seating System} (2) High Back, with 3 Point Seat Belts 48PWE UPHOLSTERY, PASS SEATS, COLOR Black, for Seats, Barriers and Head Bumpers

UPHOLSTERY, PASS SEATS, TYPE Prevaill, 42 oz.; for (09-10) Seats

48PHE

<u>Code</u>

48RLX

<u>Description</u> CUSHION, SEAT 15" Depth

48RRA

UPHOLSTERY, SEAT, STITCHING Single

B	סכ	Y	FE	A.	TU	R	E	S
---	----	---	----	----	----	---	---	---

48HAC	WINDOW, ENTRANCE DOOR Laminated, Clear, with Single Piece Glass	
49HGC	TRACK, FLOOR LENGTHS 251"-300", with Full Shoulder Track	
49JBG	TRACK, TYPE (BRAND) {OMNI L Track}	
49AMJ	ALARM, BACKING {Ecco #575} 107 dB	
49AMT	CIRCUIT, PROTECTION Breakers, Manual Reset in Lieu of Fuses	
49BCN	FLASHER SYSTEM (8) Warning Lights, 8-Lamp System, Electronic Relay Flasher, Non-Sequential Operation, Red Lights Activate with Door Open	
49DBR	HOOD, WARNING LAMP (4) Black, 8-Lamp System, One Hood Above Two Lights	
49JBU	LIGHT, ENTRY DOOR {Sound Off/OptiLuxx} LED; 4" Oval; Light Mounted in Skirt Behind Entrance Door, Wired To Step Light	
49BCR	LIGHT, EXTERIOR, CHECK Automatically Activates Lights for Pre Trip Inspection	
49ATJ	LIGHT, INDIC, LIFT DOOR Amber; Flashing, Located in Driver Area	
49ATV	LIGHT, INDIC, WARNING LIGHTS Red and Amber	
	Includes : LIGHTS, WARNING Indicator Located in Instrument Cluster	
49JBV	LIGHT, LICENSE PLATE (Sound Off/OptiLuxx) LED, with Mounting Gasket	
49BZC	LIGHT, LIFT DOOR, INTERIOR Above Lift Door, Rectangular LED, with Door Operated Switch (Functionality May Be Included in Existing Dome Light)	
49JBW	LIGHT, STEP {Sound Off/OptiLuxx} 4" Round LED, White, Wired to Clearance Lights, Operated by Entrance Door	
49EYH	LIGHT, STROBE LED, Specialty Man. Co. 845-4020-100, Low Profile, Double Flash, 4.50" High	
49ZNC	LIGHTS, BACK UP (2) {Sound Off/OptiLuxx} 4" Round, White, LED, with Flange	
49JBS	LIGHTS, CLUSTER (Sound Off/OptiLuxx) Oval, 4 Internal LEDs per Light; Amber Front and Red Rear	
49BYZ	LIGHTS, DIRECTIONAL, REAR (2) (Sound Off/OptiLuxx) LED, 7" Round Amber	
49PTB	LIGHTS, DIRECTIONAL, SIDE {Sound Off/OptiLuxx} Rectangular LED Armor Type, Amber, 1 Each Side, Second Bow Section Aft of Entrance Door Between 2nd & 3rd Rub Rail	
49JEN	LIGHTS, DOME LED, Rectangular Recessed Type, Stagger Mounted, for 25'02", 25'11", 26'08", 27'05", 28'02", 28'11" Body Lengths	
49ESC	LIGHTS, DOME, DRIVER (1) LED, Rectangular, Mounted in Light Bar in Ceiling, with Separate Switch	
49JED	LIGHTS, MARKER, FRONT & REAR LED, Flush Mount, Amber Front and Red Rear	
49ZNN	LIGHTS, MARKER, SIDE, INTERMED LED, Amber, Flush Mount, Intermediate, Centered, Required for Units 30 Foot or Longer	
49BYT	LIGHTS, STOP (2) (Sound Off/OptiLuxx) and Tail; 7" Round LED, Red	
49ZNG	LIGHTS, STOP & TAIL ADDITIONAL (2) (Sound Off/OptiLuxx) 4" Round LED, Red, with Flange	

12

<u>Code</u> 49NGJ	<u>Description</u> LIGHTS, WARNING (8) {Sound Off/OptiLuxx} (4) 7" Round Red Strobing LED and (4) 7" Round Amber Strobing LED, 2 Front, 2 Rear Each Color
49AWT	SPEAKERS AND WIRING (4) Flush Mounted in Light Bar
49BMA	STOP ARM, FRONT {Specialty 2980} Air, 18" Octagon, Double Sided, 1/2" White Border, Hi Intensity Grade, Strobing LED Lights
49BWG	STOP ARM, LEFT REAR (Specialty 2981) Air, Hi Intensity, Strobing LED Lights, with Letters on Back
49SAA	SWITCH, INSTRUMENT PANEL LIGHTS; Rheostat
49EVL	SWITCH, NOISE SUPPRESSION Actuator Legend States, "NOISE SUPP ", for Separate Solenoid, with Red Switch in Panel
49AMY	SWITCH, REAR DOOR BUZZER for Emergency Door
49BXN	SWITCH, RED, OVERRIDE WARNING Wired Hot, with ESC, Mounted Left of Driver
49BUS	WIRING, WARNING LIGHTS (8) for 7" Red Warning Lights, Alternately Flashing, 2 Front, 2 Rear, Red Warning Lights to Operate When Lift Door is Open and Master Flasher Switch is "ON"
49NBM	MIRROR, CROSS VIEW, EXTERIOR (2) {Rosco High Definition} Black, Heated, with LED Downlit Front Lighting
49EGC	MIRROR, INSIDE 6" x 30", Clear Safety Glass, Metal Back, Round Corners
49DNB	MIRROR, REAR VIEW, EXTERIOR (Rosco AccuStyle) Black, Motorized Head, Heated, Breakaway Bracket
49ENK	VISOR, INTERIOR, LEFT FRONT 6" x 30", Transparent, For Left Windshield
49GDS	COMPARTMENT ABOVE DRIVER Left of the Driver
	Includes : COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type
49GGU	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10"
49GGU 49JGJ	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type
	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft.
49JGJ	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle
49JGJ 49JGN	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat
49JGJ 49JGN 49GAY	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat KIT, BODY FLUID Texas
49JGJ 49JGN 49GAY 49EBA	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat KIT, BODY FLUID Texas KIT, FIRST AID Plastic; 24 Unit, Spec State
49JGJ 49JGN 49GAY 49EBA 49MZV	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat KIT, BODY FLUID Texas KIT, FIRST AID Plastic; 24 Unit, Spec State LATCH, COMPARTMENT Locking, for Overhead Storage Compartment
49JGJ 49JGN 49GAY 49EBA 49MZV 49JEY	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat KIT, BODY FLUID Texas KIT, FIRST AID Plastic; 24 Unit, Spec State LATCH, COMPARTMENT Locking, for Overhead Storage Compartment LOCATION, BODY FLUID KIT on Bulkhead
49JGJ 49JGN 49GAY 49EBA 49MZV 49JEY 49GCH	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat KIT, BODY FLUID Texas KIT, FIRST AID Plastic; 24 Unit, Spec State LATCH, COMPARTMENT Locking, for Overhead Storage Compartment LOCATION, BODY FLUID KIT on Bulkhead LOCATION, FIRST AID KIT Right Side Front Bulkhead with Screws
49JGJ 49JGN 49GAY 49EBA 49MZV 49JEY 49GCH 49GDG	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat KIT, BODY FLUID Texas KIT, FIRST AID Plastic; 24 Unit, Spec State LATCH, COMPARTMENT Locking, for Overhead Storage Compartment LOCATION, BODY FLUID KIT on Bulkhead LOCATION, FIRST AID KIT Right Side Front Bulkhead with Screws PADDING COMPART ABOVE DRIVER Window; Safety Equipment Compartment, with Cutout for Dome Light
49JGJ 49JGN 49GAY 49EBA 49MZV 49JEY 49GCH 49GDG 49GLP	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat KIT, BODY FLUID Texas KIT, FIRST AID Plastic; 24 Unit, Spec State LATCH, COMPARTMENT Locking, for Overhead Storage Compartment LOCATION, BODY FLUID KIT on Bulkhead LOCATION, FIRST AID KIT Right Side Front Bulkhead with Screws PADDING COMPART ABOVE DRIVER Window; Safety Equipment Compartment, with Cutout for Dome Light REFLECTORS, REAR (2) 3", Red, Mounted with Screws REFLECTORS, SIDE, FRONT (2) 3", Amber; 1 Aft Drivers Window Left, 1 Aft Entrance Door Right, Mounted
49JGJ 49JGN 49GAY 49EBA 49MZV 49JEY 49GCH 49GDG 49GLP 49GLM	: COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type FIRE BLANKET 36 Sq. Ft. FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat KIT, BODY FLUID Texas KIT, FIRST AID Plastic; 24 Unit, Spec State LATCH, COMPARTMENT Locking, for Overhead Storage Compartment LOCATION, BODY FLUID KIT on Bulkhead LOCATION, FIRST AID KIT Right Side Front Bulkhead with Screws PADDING COMPART ABOVE DRIVER Window; Safety Equipment Compartment, with Cutout for Dome Light REFLECTORS, REAR (2) 3", Red, Mounted with Screws REFLECTORS, SIDE, FRONT (2) 3", Amber; 1 Aft Drivers Window Left, 1 Aft Entrance Door Right, Mounted with Screws REFLECTORS, SIDE, INTERMEDIATE (2) 3" Amber, 1 Each Side, Mounted with Screws, Below The Third

Code 49GED	<u>Description</u> SAFETY TRIANGLES Warning Reflectors, Mounted on Floor Between Driver Seat and Drivers Crash Barrier/ Stanchion/Partition	
49HAY	STORAGE COMPARTMENT, BELTS (4) for Sure Lok Wheelchair Belts, Mounted to Wall	
49GMM	INTERLOCK, LIFT for FMVSS Wheel Chair Interlock Requirements; Key Off, Lift Door Must be Open before Lift can be Activated, w/ Key in "On or Accessory" Position, Park Brake Must be Applied, Transmission in Neutral, Lift Door Must be Open Before Lift Can be Activated, w/ Automatic or Procision Transmissions	
49NAB	LIFT, WHEELCHAIR (Braun Model NCL1000FIB3451 Gen 2) Power Pack Mounted Forward of Lift	
49JCE	TIE DOWN, WHEELCHAIR (Sure-Lok AL812S-4C-7) Titan System, (04) Forward Facing, 50" Floor Space Front To Rear Required, Tie Down Only	
49EPY	CUTTER, SEAT BELT (2) {TIE TECH Safecut} for Cutting Seat Belts	
49JGE	CUTTER, SEAT BELT, LOCATION Mounted on Panel Left of Driver	
49JAC	DEF FILLER DOOR with Non-Locking Latch	
49MZS	FUEL FILLER DOOR Non-Locking, Lever Latch, Spring Loaded to Hold in Open Position	
49CKT	FUEL FILLER PIPE Low Profile Neck Cap and Vent Hosing, for Use with Right Side Fill for Between the Rail Fuel Tanks, for Above the Floor Fuel Fill, for 25 GPM Fill Rate Only	
49GUM	INSPECTION PLATE Fuel Sending Unit 8" x 8" Steel	
49GVC	MUD FLAPS, REAR WHEELS (2) Rubber	
49ESH	SIGN, DESTINATION, FRONT LED Illuminated, Exterior Bulkhead Mounted, with 8" Letters "SCHOOL BUS"	
49ESG	SIGN, DESTINATION, REAR LED Illuminated, Exterior Bulkhead Mounted, with 8" Letters "SCHOOL BUS"	
49UBZ	STATE OF OPERATION Texas	
	Services Section:	
WARRANTY		
40126	WARRANTY Standard for CE, RE, BE School Bus Models, Effective with Vehicles Built March 1, 2017 or Later, CTS-3304H	
40YET	SERVICES, TOWING {Navistar} Service Call to 24-Month/Unlimited Mileage to the Nearest IC Bus Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$1100 (USA) Maximum Benefit per Incident	
40YGC	SRV CONTRACT, EXT VEH COVERAGE {Navistar} To 24-Month/50,000 Miles (80,000 km), Covers 100% Parts and Labor; Includes Body; Excludes Extending Warranty for Engine, Transmission, Perforation or Corrosion of Cab/Cowl Structure and Paint	
BODY FEATURES		
49GVN	WARRANTY 5-Year, Limited	
	DOT INSPECTION	
	SET GOVERN SPEED @ 60 MPH	
	WEIGHT SLIP	
	DVR CAMERA SYSTEM - SEON 5 CAMERA *** LHB INSTALL	
	TWO WAY RADIO - MOTOROLA XPR5550E	

December 01, 2023

Code

<u>Description</u>
BACKUP CAMERA IN MIRROR 10X30 - CBC INSTALL

Proposal: 11061-01

15

<u>Price</u>

<u>Financial Summary</u> 2025 CE SCHOOL BUS (PB110)

(US DOLLAR)

Description

Authorized Signature

Net Sales Price:	\$146,580.00
Please feel free to contact me regarding these specification pleased with the quality and service of an IC Corporation v	ns should your interests or needs change. I am confident you will be rehicle.
Prices are good for 30 days from the date of this proposal.	
PRICE PER BUS: \$146,580.00	
***OPTIONAL ITEMS TO CONSIDER (Not included in abo	ove pricing) ***
\$160 per bus - Window frames black (does not include bla	ck painted posts in between windows)
\$70 per bus - Digital clock located on dash (right side)	
\$65 per bus - Waste container located right side forward o	f entry door
\$75 per bus - Black front grille with chrome surround	
\$185 per bus - Dual height handrails on each side of entry	stepwell
of code references. Estimated delivery: 300-365 Days fron responsible for material shortages or delays due to the glo that of the represented OEM (IC Corp) or third-party vendo be subject to any and all applicable surcharges at the time applicable surcharges will be the responsibility of the buye (i.e., A/C, GPS, two-way radios, camera surveillance equipavailability. These shortages/delays will not hold up invoice.	arded. Feature codes are subject to update upon IC Bus completion in receipt of a purchase order. Longhorn Bus Sales will not be held bal COVID-19 pandemic or any other reasons outside of our control, with the same of the
Price does not include Buy Board fee of \$800 per purchase	e order, please add if applicable. Buy Board contract 630-20.
	nty for 24-months/unlimited mileage. (Navistar will cover the first 50King of the 24-month period, as per current Texas School Bus
CODE "49GVN WARRANTY 5-YEAR, LIMITED" IS A NAV AFTERMARKET PARTS	/ISTAR WARRANTY ONLY, IT DOES NOT APPLY TO ANY
	istomer acknowledges that all equipment listed within this document any miss-built units. Any changes to what is listed herein, may result
Approved by Seller:	Accepted by Purchaser
Official Title and Date	Firm or Business Name

Authorized Signature and Date

Financial Summary 2025 CE SCHOOL BUS (PB110)

December 01, 2023

This proposal is not binding upon the seller without Seller's Authorized Signature

Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

17



CE SCHOOL BUS

Sales Proposal For:

College Station

Presented By:

LONGHORN BUS SALES

Prepared For: College Station Transportation Dept 1812 Welsh College Station, TX 77840-(979)764 - 5408

Reference ID: 77P DSL 3PT

Presented By: LONGHORN BUS SALES LINDA BLUME 9100 N LOOP E HOUSTON TX 77029 -(713)631-9306

Thank you for the opportunity to provide you with the following quotation on a new IC Corporation vehicle. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile 2025 CE SCHOOL BUS (PB110)

AXLE CONFIG:

4X2

APPLICATION:

School Transportation

MISSION:

Requested GVWR: 31000. Calc. GVWR: 31000

Calc. Start / Grade Ability: 22.51% / 1.65% @ 55 MPH

Calc. Geared Speed: 92.9 MPH

DIMENSION:

Wheelbase: 276.00, CA: N/A, Axle to Frame: 166.00

ENGINE, DIESEL:

{Cummins B6.7 250} EPA 2024, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM

Governed Speed, 250 Peak HP (Max), School Bus Only

TRANSMISSION, AUTOMATIC:

{Allison 2500 PTS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less

PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus

CLUTCH:

Omit Item (Clutch & Control)

AXLE, FRONT NON-DRIVING:

{Meritor MFS-10-122A} I-Beam Type, 10,000-lb Capacity

AXLE, REAR, SINGLE:

(Dana Spicer S140) Single Reduction, 21,000-lb Capacity, 190 Wheel Ends Gear Ratio; 5,29

TIRE, FRONT: TIRE, REAR:

(2) 11R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position (4) 11R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position

SUSPENSION, REAR, AIR, SINGLE:

{International IROS} 21,000-lb Capacity, 9.25" Ride Height, with Shock Absorbers Mounted

Outside the Rails

PAINT:

Cab schematic 100NB

Location 1: 4421, School Bus Yellow (Std)

Chassis schematic N/A

<u>Code</u> PB11000	<u>Description</u> Base Chassis, Model CE SCHOOL BUS with 276.00 Wheelbase, N/A CA, and 166.00 Axle to Frame.
BODY PLANS	
47AMG	BODY, BUS Conventional; 78" Headroom, 34'11" Body Length, +9 Section Rear, 81 Passenger, 276 WB
	Includes : NOTE: Body Mandates Overall Vehicle Length of Greater than 40 Feet
OBD001	BODY PLAN, NON-SPECIAL NEEDS USE BODY PLAN 50ZDV 49001
49001	BODY PLAN, APPROVED VARIATION Number 001
AXLE CONFIGURATION	N
1ANA	AXLE CONFIGURATION (Navistar) 4x2
ENGINE	
12EYH	ENGINE, DIESEL {Cummins B6.7 250} EPA 2024, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 250 Peak HP (Max), School Bus Only
12VJR	EMISSION, CALENDAR YEAR (Cummins B6.7) EPA, OBD and GHG Certified for Calendar Year 2024
12XCS	CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty
12WZE	CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations
12WVG	EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood
12XCC	RADIATOR Aluminum, 2-Row, Down Flow, Front to Back System, 640 Sqln Louvered, with 383 Sqln Charge Air Cooler, Includes In-Tank Oil Cooler
	<u>Includes</u> : RADIATOR HOSES Premium, Rubber
12TSY	FAN DRIVE {Borg-Warner SA85} Viscous Type, Screw On
	Includes : FAN Nylon
12VCE	AIR CLEANER Single Element, Fire Retardant Media
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
12VVN	CRUISE CONTROL Electronic
12VYV	IDLE MANAGEMENT SYSTEM Ramp Engine Speed with Air Condition On, in Neutral and Parking Brake Set, Accommodation Package
12WPV	OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines
12UGN	THROTTLE, HAND CONTROL Electronic
TRANSMISSION	
13BBP	TRANSMISSION, AUTOMATIC (Allison 2500 PTS) 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, Less PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max, School Bus
13WVW	NEUTRAL AT STOP OMIT
13WYY	SHIFT CONTROL PARAMETERS (Allison) 1000 or 2000 Series Transmissions, Performance Programming
13WLN	TRANSMISSION OIL Synthetic; 20 thru 28 Pints

Code

Description

13WEX

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, for Allison 1000 & 2000 Series

Transmission

CLUTCH

11001

CLUTCH Omit Item (Clutch & Control)

REAR AXLES, SUSPENSIONS

14AKC AXLE, REAR, SINGLE {Dana Spicer S140} Single Reduction, 21,000-lb Capacity, 190 Wheel Ends . Gear

Ratio: 5.29

14TDV SUSPENSION, REAR, AIR, SINGLE {International IROS} 21,000-lb Capacity, 9.25" Ride Height, with Shock

Absorbers Mounted Outside the Rails

FRONT AXLES

2ASH AXLE, FRONT NON-DRIVING (Meritor MFS-10-122A) I-Beam Type, 10,000-lb Capacity

FRONT SUSPENSIONS

3ADB SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 10,000-lb Capacity, with Shock

Absorbers

Includes

: SPRING PINS Rubber Bushings, Maintenance-Free

CABS, COWLS, BODIES

16010 COWL Flat Back

16VKB CAB INTERIOR TRIM Classic, for Day Cab

16GEG GAUGE CLUSTER Premium Level; English with English Electronic Speedometer

Includes

: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip

Hours, MPG, Distance to Empty/Refill for

: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure

Gauge, Primary and Secondary Air Pressure or Auxiliary Air Pressure (if Air Equipped)

: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage

(Visual and Audible), Low Air Pressure, Primary and Secondary (if Air Equipped)

16HLJ GAUGE, DEF FLUID LEVEL

16HGH GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission

16BAL HEATER

16563 HEATER SHUT-OFF VALVES (2) Ball Valve Type

16XJP INSTRUMENT PANEL Wing Panel

16HKT IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

16VUY MONITOR, TIRE PRESSURE System Gives Warning that Tire Pressure is Below Set Pressure, Monitors Tire

Pressure of Each Tire with Temperature Compensation, Data Displayed in the LCD of the Cluster, for 4x2 Axle

Configuration, Does Not Include Lift Axles or Spare Wheels

16VVJ WINDSHIELD Three Piece, Bonded, with Shaded Band

Code FRAMES	Description
1CAC	FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm); 489.2" (12425mm) Maximum OAL
1LSG	BUMPER, FRONT Contoured, Steel, Painted Gloss Black, Severe Duty
	Notes : Bumper Thickness is .25"
1LNT	CROSSING GATE, FRONT Omit Item
1SAL	CROSSMEMBER, REAR, AF (1)
1570	TOW HOOK, FRONT (2) Frame Mounted
1WRP	TOW HOOK, REAR (2) Mounted on Lower Rail Flange
1WJE	WHEELBASE RANGE 276" (700cm) Only
BRAKES	
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications
	Includes : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6
4AZS	AIR BRAKE ABS (Bendix AntiLock Brake System) 4-Channel (4 Sensor/4 Modulator) Electronic Stability Program, with Automatic Traction Control
4GBL	BRAKE, PARKING {Bendix Intellipark} Electronic Park Brake, for Truck or Bus Applications
4XDD	BRAKES, FRONT {Meritor 15X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 15" X 5", 13,200-lb Capacity
4EXP	BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 Sqln
4LAG	SLACK ADJUSTERS, FRONT {Gunite} Automatic
4XDR	BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Sqln Spring Brake
4LGG	SLACK ADJUSTERS, REAR {Gunite} Automatic
4SPA	AIR COMPRESSOR (Cummins) 18.7 CFM
4EDN	AIR DRYER {Bendix AD-9SI} with Heater, Includes Safety Valve
4VLE	AIR DRYER LOCATION Mounted Inside Engine Compartment, Right Side
4VLY	AIR TANK LOCATION (1) Mounted Inside & Below Left Rail, Back of Cab
4722	DRAIN VALVE {Bendix DV-2} Automatic, with Heater, for Air Tank
4WZT	GVWR LIMITATION FOR BUS with Air Brakes, Limited to 33,000-lbs Maximum to meet FMVSS 121 Requirements, for Conventional Bus
4WJP	PARKING BRAKE INTERLOCK with Electronic Park Brake, Parking Brake Cannot be Released Until Ignition Switch is in "On" Position and Service Brake Pedal is Applied, Use with Air Brake Chassis Only

5

Code STEERING	<u>Description</u>	
5PSA	STEERING GEAR (Sheppard M100) Power	
5708	STEERING COLUMN Tilting	
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black	
DRIVELINES		
6DGA	DRIVELINE SYSTEM {Dana Spicer} SPL100, for 4x2/6x2	
6901	PROPSHAFT GUARD	
EXHAUST SYSTEMS		
7BMK	EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Under Right Rail, for Single Long Horizontal Tail Pipe	
7WCX	HEAT SHIELD Between Exhaust & Fuel Tank, Mounted to AF Crossmember	
7WBL TAIL PIPE (1) Horizontal, Long, Exits Left Side Through Bumper		
ELECTRICAL SYSTEMS		
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment	
	Includes : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : MISCELLANEOUS FEATURES Modular, Loom Protected, Grommets in all Applicable Body Openings, Assembled in Computer Assisted Fixture which Verifies Continuity and Correct Assembly Prior to Installation : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : STARTER SWITCH Electric, Key Operated : TURN SIGNAL SWITCH Self-Cancelling with Lane Change Feature : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WIRING, CHASSIS Color Coded and Continuously Numbered	
8GXN	ALTERNATOR {Leece-Neville BLP4024N} Brushless, 12 Volt, 325 Amp Capacity, Pad Mount, with Remote Sense	
8ТТК	BATTERY BOX Steel, with Sliding Tray, 25.25" Wide, for Standard Batteries, 1-3 Battery Capacity, Mounted Left Side Behind Front Axle Perpendicular to Frame Rail	
8MJU	BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 2850CCA Total, Top Threaded Stud	
8XDX	BK WARN IND,PARK BK NOT SET Visual and Audible Alarm, Active Upon Ignition Off and Parking Brake Not Set, Reminder to Set Parking Brake	
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	
8TUT	COLLISION MITIGATION SYSTEM Omit	
8WXB	HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position	
8XKC	HEADLIGHTS Halogen, with Daytime Running Lights, Automatic Twilight Controlled	
8WRB	HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On	
8540	HORN, ELECTRIC (2) Trumpet Style	

<u>Code</u> <u>Description</u>

8WWJ INDICATOR, LOW COOLANT LEVEL with Audible Alarm

8RRC RADIO AM/FM/USB Input/Auxiliary Input, Includes Wiring and Antenna, with Public Address System

8XKL STARTING MOTOR (Mitsubishi Electric Automotive America 90P47) 12-Volt, with Soft-Start

FRONT END

9WBW FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes

9HCW GRILLE Molded in Black

9WAB HOOD TILT ASSIST (EASY TILT) Mechanical

9AAB LOGOS EXTERIOR Model Badges

9AAE LOGOS EXTERIOR, ENGINE Badges

SPEEDOMETER, TOOLS, MISC

10020 CHASSIS PAINT Full Chassis

10AGB COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data

Plan and International 360

10WUE MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension

10060 PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

: PAINT SCHEMATIC ID LETTERS "NB"

10788 PAINT TYPE Urethane, One or Two Colors, Other than Imron or International.

10XAK PROMOTIONAL PACKAGE 7 Year Unlimited Miles/km Warranty, Limited Time Program for Allison 2500

Series Transmission on School and Commercial Buses (Supplied directly through Allison)

FUEL TANKS

15SLL FUEL TANK Top Draw, Steel, Rectangular, 100 US Gal (379L), Includes Protective Cage, Mounted Between

Frame Rails and Behind Rear Axle

15WEP DEF TANK 16.5 US Gal (62.5L) Capacity, Frame Mounted Outside Right Rail, Behind 0 Bow

15LMR FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor

15LRE LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle

WHEELS, TIRES - FRONT

27DUW WHEELS, FRONT (Accuride 51408) DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud,

285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

7382138132 (2) TIRE, FRONT 11R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-

Position

WHEELS, TIRES - REAR

28DUW WHEELS, REAR (Accuride 51408) DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud,

285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

7382138132 (4) TIRE, REAR 11R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position

Code BODY FEATURES	<u>Description</u>
47BAK	BUMPER, REAR Painted, 12" High, 3/16" Thick
47BAR	SUPPORTS, REAR BUMPER Bolted to Frame
47AYB	BODY, REAR Includes Emergency Door
47ARH	BOWS, ROOF 14 ga., One Piece Construction
	<u>Includes</u> : BOWS, ROOF Positioned Floor Line to Floor Line, Threaded Through Roof Strainers and Drip Rail
47BLU	FASTENERS, EXTERIOR MOUNTED Stainless Steel Screws; for All Exterior Body Lights, Body Exterior Rear View Mirrors, Bumper Mounted Crossing Gate and Body Mounted Stop Arms
47APX	FASTENERS, HEADLINER Screws
47AZL	FLOOR, BODY with Wheel Wells
47PBZ	HANDLE, ASSIST Windshield Side Mounted, Left and Right, Body Color
47APR	HEADLINER, BODY Conventional; 25'11"-35'08" Body Length, Perforated Full Length with Sound Insulation Full Length
47ARP	LIGHT BARS Plastic
47BBH	LINING, SIDE INTERIOR, LOWER Embossed Steel, Clear Coated
47AXT	RUB RAILS, BODY (4) Conventional; Steel, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths, Includes Snow Rail
	Includes : RUB RAILS Full Length, Primer Coated (Both Sides), Attached to Body without Cuts or Splices
47BBZ	SEALER Extra; Sidewall to Floor, In Wheel Pocket Area, and Rear Wall to Floor
47AZE	SIDE SHEET, BODY, EXTERIOR Conventional, 16ga., Smooth, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
47ATB	SKIRT, BODY Conventional, 20", 16ga., 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
	Includes : SKIRT, BODY Extra Smooth Steel Supported by Floor Gussets
47BLD	STEP, FRONT ENTRANCE DOOR 27 1/4" Depth; 14ga Steel, Formed Treads, Naviflex Finish
47AUR	TIE DOWNS, BODY Grade 8 Bolts, Every Body Section
	Includes : TIE DOWNS, BODY with Formed Tab that Fits into Floor Structure to Prevent Turning
47DAJ	COVER, REAR DOOR INSIDE HANDLE Partial Coverage
47DYL	DOOR, ENTRANCE, FRONT Air, Outward Opening, with Single Pane Glass
47DAK	FASTENERS, REAR DOOR Bolts and Nutserts, Rear Door To Body
47DDE	HANDLE, ASSIST, ENTRANCE DOOR Outside Entrance
47DEY	HANDLE, EXTERIOR, REAR Emergency Door; Yellow
47DDH	HOLD BACK, REAR DOOR Stationary, No Cables, with Plastic Cover
47DDU	LATCH, REAR DOOR One Point Slide Bar, Cam Operated, with One Inch Stroke
47EYL	LOCK, ENTRANCE DOOR in External Release, with Key

8

Code Description

LOCK, REAR DOOR with Ignition Starter Interlock 47DEK

COMPARTMENT, DRIVER STORAGE Bin, Sized to Hold Three Ring Binder, Includes (1) USB-A Port and (1) 47BDJ

USB-C Port

47EVY COMPARTMENT, LUGGAGE, LT MID 114" x 24" x 22"

: HINGES Rubber

: LATCH, T-HANDLE, LOCKING Stainless Steel

47EWA COMPARTMENT, LUGGAGE, RT MID 114" X 24" X 22"

HOLD DOWN, BATTERY For Up To 3 Batteries 47EBM

47EMV LUGGAGE RACK, INTERIOR Tubular, Below Light Bar, 22 Bow

INSULATION, ROOF/SIDES/BULKHEAD 1.5" 47LAU

47LAT NOISE REDUCTION, ROOF BOW Conventional; Insulation, 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8"

Body Lengths

47MBA UNDERCOAT, BODY Fire Resistant, Water Based, TT-C-730 Spec

: UNDERCOATING Performed Before and After Mounting on Chassis

47SPB ALPHA/NUMERIC DECAL GUIDE Quantity 021-30

ARROW, RR DOOR, INSIDE Decal; Red, .75" Stroke, Indicating Handle Direction 47MNT

47AJA **BODY CERTIFICATION TAG Metal**

47APJ BODY RATING TAG Metal; for State of Texas, Includes Design Capacity and Seat Capacity

47AJC BODY TAG, METAL Capacity to Include the Total Number of Passengers LETTERS, DEF, I.D. Decal; "DEF ONLY", 1" Black, on DEF Filler Door 47PLX

47MJR LETTERS, DOOR, REAR Decals; "EMERGENCY DOOR", 2" Black Letters Inside and Outside

47NGP LETTERS, FUEL I.D. Paint; "DIESEL FUEL", 2" Black, Adjacent to Fuel Filler Door 47MVA LETTERS, HEADER Decal; "WATCH YOUR STEP", 1" Black, Above Windshield

LETTERS, E/E WINDOW, LEFT (2) Decal Sets, "EMERGENCY EXIT", Black Inside and Outside 47MRU 47NHL LETTERS, E/E WINDOW, RIGHT (2) Decal Sets, "EMERGENCY EXIT", Black, Inside and Outside LETTERS, SCHOOL BUS SIDE Decal; "SCHOOL BUS"; in 8" Reflective Black Letters, Each Side 47MAV

47MZB LETTERS, SCHOOL BUS FRONT/REAR Decal; OMIT "SCHOOL BUS"; with 8" Black Letters; on Front and

Rear Cap

47MVC LETTERS, STEPWELL Decal, "WATCH YOUR STEP", 2.5" Black, Behind Door on Step Riser

47NTE LOGO, ROOF LINE Decal; Wing and Shield, First Body Section, Above Driver Window and Entrance Door

9

Over Driver Window and Entrance Door

47NMG OPERATING INSTRUCTIONS, REAR Decal, Inside Rear Emergency Door

47NJA PAINT COLOR, BODY EXTERIOR 4421 School Bus Yellow

47NKM PAINT COLOR, BODY INTERIOR 9384 Spring White 47NJS PAINT COLOR, BUMPER Rear, 0001 Canyon Black

47NKD PAINT COLOR, ROOF 9219 Winter White, Beginning 5" Above Drip

<u>Code</u> 47NAB	<u>Description</u> PAINT COLOR, RUB RAILS 0001 Canyon Black
47NJM	PAINT FLASHER BACKGRD 0001 Canyon Black
47NTY	PAINT HOOD AND FENDER To Match Body Exterior
47NKL	PAINT, RUB RAIL Flange to Flange
47NGW	SEAL, RUB RAILS Top Edge, All Rails
47NXH	STRIPING, E/E WINDOW, LEFT {3M} (02) Perimeter, 1" Yellow Fluorescent Diamond Grade
47NWU	STRIPING, E/E WINDOW, RIGHT (3M) (02) Perimeter, 1" Yellow Fluorescent Diamond Grade
47NXN	STRIPING, PERIMETER, REAR (3M) Emergency Door, 1" Yellow Fluorescent Diamond Grade
47NWR	STRIPING, REAR END {3M} 2" Yellow Fluorescent Diamond Grade
47NWT	STRIPING, ROOF HATCH, FRONT (3M) Decal, Perimeter, 1" Yellow Fluorescent Diamond Grade
47NWH	STRIPING, ROOF HATCH, REAR {3M} Decal, Perimeter, 1" Yellow Fluorescent Diamond Grade
47NWJ	STRIPING, SEATLINE (3M) 2" Yellow Fluorescent Diamond Grade
47MTY	WIRING DIAGRAM Schematic, Electrical
	<u>Includes</u> : ACCESS PANEL for Wiring Diagram Schematic Located on Inside of Electrical Panel Door, Below Driver Window
47SBB	SUB FLOOR, PLYWOOD Conventional; B-B Marine Grade, Less Sealed Edges, 5/8", 5 Ply, for 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
47KEJ	DISARM, POST TRIP INSPECTION Button Located on Light Bar at Rear of Bus
47KEB	MONITOR, POST TRIP INSPECTION (Leave No Student Behind) Accessory Controlled, with Push Button Alarm Disable at Rear of Bus Prompts Driver to Walk to Back of Bus to Disable Alarm
47DNK	SWITCH, LOCATION Steering Wheel; Includes Master Flasher, Flasher On/Off, Red Override, and Door Control
	<u>Includes</u> : SWITCH, STEERING WHEEL, LIGHT Includes Illuminated Switches

BODY FEATURES

48ANT	WINDOW, DRIVER Laminated, Clear
48BJA	COLOR, WINDOW FRAME, PASS Passenger Window, Natural Aluminum Finish
48BAH	WINDOW, E/E, LEFT (2) Vertical Hinge
48BKP	WINDOW, E/E, RIGHT (2) Vertical Hinge
48AUN	WINDOW, PASSENGER, TINT Conventional; 28% Llght, Laminated Glass, 78" Headroom, with 31'2", 31'11", 32'8", 33'5", 34'2", 34'11", 35'8" Body Lengths
48ARU	WINDOW, SASH (20) 27" Sections, 9"x 23" Opening
48ASP	WINDOW, SASH +9 SECTIONS (2) 9" x 32 1/4" Opening
48APL	WINDOW, STOPS 12" Opening, Only with 78" Headroom
48PAY	AISLE POSITION Center, for balanced seating
48PBD	FLOOR COVERING, COLOR Brown
48PJR	FLOOR COVERING, TRIM Aluminum

Code Description FLOOR COVERING, TYPE (Koroseal) All Body Lengths 48PJZ STEP TREADS (Koroseal) Pebble White Nosing Only, with Non-Metal Backing, used with Formed Treaded 48VVR Steps WHEEL POCKET COVER Plastic, ABS 48PAV AIR CONDITIONER, BODY IC Air, 120,000 BTU, Evaporators FM55 Front & Rear Flush Mounted & TA93 Side 48HDJ Mounted, Condensers SMC3L Skirt Mounted, Compressors TM21, #16 Suction Hose, EC4.0 Control System HOSE CLAMPS, HEATER HOSE Constant Torque for Heater System 48PKC FAN, DEFOG LEFT OF DRIVER 6.50" Diameter, Black, Mounted on Driver Overhead Compartment, 2 Speed 48UZK Switch in Panel 48PPP HEATER CUT OFF, VALVE INSIDE Brass Ball, Inside Driver Area HEATER, PASS, LT REAR 84,500 BTU 48PMJ Includes : AIR FILTER HEATER, WATER PUMP {2 MPU 12} Self Priming, with Plastic Housing 48PNW 48UZN ROOF HATCH, FRONT (Specialty Hybrid Adv H1975-025-191-0F) Emergency Exit with Outside Release, Alarm, English Decals ROOF HATCH, REAR (Specialty Hybrid Adv H1975-025-191-0F) Emergency Exit with Outside Release, 48UZT Alarm, English Decals 48PPS ROOF VENT. FRONT Static 48PPC SWITCH, HTR FAN, REAR, LT with 84,500 BTU Rear Heater Only 48RYW SEAT, DRIVER (National 2000) Air Suspension, High Back with Integral Headrest, Isolated, with 2 Position Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Mechanical Lumbar Support, Includes Additional Back Padding : SEAT BELT, DRIVER Adjustable D-Loop Seat Belt, Single Locking Retractor 48PXP UPHOLSTERY, BARRIER, TYPE (1-2) Prevaill, 42 oz. 48UXN UPHOLSTERY, DRIVER SEAT, COLOR Drivers Seat, Graphite 48PVA UPHOLSTERY, DRIVER SEAT, STYLE Plain, with Cloth Insert 48PWR UPHOLSTERY, DRIVER SEAT, TYPE Prevaill, 42 oz. 48BDS BARRIER, CRASH, AFT ENTRY DOOR 39", 2 Leg 48RAL BARRIER, CRASH, AFT DRIVER 39", 1 Leg 48DPL HAND RAIL, ENTRANCE DOOR, AFT 1" Dia, Stainless Steel 48DPR HAND RAIL, ENTRANCE DOOR, FWD 1" Dia, Stainless Steel 48RFP PANEL, MODESTY, AFT OF DRIVER Mounted Under Barrier 48BDG POUCH, CRASH BARRIER Full Width, Sewn Into Front Side of Barrier AFT of Driver Seat 48ACN SEAT BELT, DRIVER, COLOR with Blaze Orange Seat Belt Webbing

SEAT,26",WALL,3PT,LT {BTI Seating System} (01) High Back, with 3 Point Seat Belts

SEAT BACK, PASSENGER High Back

48USV

48XGC

Code 48WZV	<u>Description</u> SEAT,36",WALL,3PT,CHLD,LT {BTI Seating System} (02) High Back, with 3 Point Seat Belts, with Child Restraints
48XAE	SEAT,36",WALL,3PT,CHLD,RT {BTI Seating System} (02) High Back, with 3 Point Seat Belts and Child Restraint
48YAE	SEAT,39",WALL,3PT,LT {BTI Seating System} (10) High Back, with 3 Point Seat Belts
48YAV	SEAT,39",WALL,3PT,RT (BTI Seating System) (11) High Back, with 3 Point Seat Belts
48PWE	UPHOLSTERY, PASS SEATS, COLOR Black, for Seats, Barriers and Head Bumpers
48PHR	UPHOLSTERY, PASS SEATS, TYPE Prevaill, 42 oz.; for (25-26) Seats
48RLX	CUSHION, SEAT 15" Depth
48RRA	UPHOLSTERY, SEAT, STITCHING Single
BODY FEATURES	
48HAC	WINDOW, ENTRANCE DOOR Laminated, Clear, with Single Piece Glass
49AMJ	ALARM, BACKING {Ecco #575} 107 dB
49AMT	CIRCUIT, PROTECTION Breakers, Manual Reset in Lieu of Fuses
49BÇN	FLASHER SYSTEM (8) Warning Lights, 8-Lamp System, Electronic Relay Flasher, Non-Sequential Operation, Red Lights Activate with Door Open
49DBR	HOOD, WARNING LAMP (4) Black, 8-Lamp System, One Hood Above Two Lights
49JBU	LIGHT, ENTRY DOOR {Sound Off/OptiLuxx} LED; 4" Oval; Light Mounted in Skirt Behind Entrance Door, Wired To Step Light
49BCR	LIGHT, EXTERIOR, CHECK Automatically Activates Lights for Pre Trip Inspection
49ATV	LIGHT, INDIC, WARNING LIGHTS Red and Amber
	Includes : LIGHTS, WARNING Indicator Located in Instrument Cluster
49JBV	LIGHT, LICENSE PLATE (Sound Off/OptiLuxx) LED, with Mounting Gasket
49JBW	LIGHT, STEP (Sound Off/OptiLuxx) 4" Round LED, White, Wired to Clearance Lights, Operated by Entrance Door
49EYH	LIGHT, STROBE LED, Specialty Man. Co. 845-4020-100, Low Profile, Double Flash, 4.50" High
49ZNC	LIGHTS, BACK UP (2) {Sound Off/OptiLuxx} 4" Round, White, LED, with Flange
49JBS	LIGHTS, CLUSTER (Sound Off/OptiLuxx) Oval, 4 Internal LEDs per Light; Amber Front and Red Rear
49BYZ	LIGHTS, DIRECTIONAL, REAR (2) {Sound Off/OptiLuxx} LED, 7" Round Amber
49PTB	LIGHTS, DIRECTIONAL, SIDE {Sound Off/OptiLuxx} Rectangular LED Armor Type, Amber, 1 Each Side, Second Bow Section Aft of Entrance Door Between 2nd & 3rd Rub Rail
49JEK	LIGHTS, DOME LED, Rectangular Recessed Type, Two Full Rows, for 34'02", 34'11", 35'08" Body Lengths
49ESC	LIGHTS, DOME, DRIVER (1) LED, Rectangular, Mounted in Light Bar in Ceiling, with Separate Switch
49JED	LIGHTS, MARKER, FRONT & REAR LED, Flush Mount, Amber Front and Red Rear
49ZNN	LIGHTS, MARKER, SIDE, INTERMED LED, Amber, Flush Mount, Intermediate, Centered, Required for Units 30 Foot or Longer
49BYT	LIGHTS, STOP (2) {Sound Off/OptiLuxx} and Tail; 7" Round LED, Red

<u>Code</u> 49ZNG	<u>Description</u> LIGHTS, STOP & TAIL ADDITIONAL (2) {Sound Off/OptiLuxx} 4" Round LED, Red, with Flange	
49NGJ	LIGHTS, WARNING (8) {Sound Off/OptiLuxx} (4) 7" Round Red Strobing LED and (4) 7" Round Amber Strobing LED, 2 Front, 2 Rear Each Color	
49AWV	SPEAKERS AND WIRING (8) Flush Mounted In Light Bar	
49BMA	STOP ARM, FRONT (Specialty 2980) Air, 18" Octagon, Double Sided, 1/2" White Border, Hi Intensity Grade, Strobing LED Lights	
49BWG	STOP ARM, LEFT REAR (Specialty 2981) Air, Hi Intensity, Strobing LED Lights, with Letters on Back	
49SAA	SWITCH, INSTRUMENT PANEL LIGHTS; Rheostat	
49EVL	SWITCH, NOISE SUPPRESSION Actuator Legend States, "NOISE SUPP ", for Separate Solenoid, with Red Switch in Panel	
49AMY	SWITCH, REAR DOOR BUZZER for Emergency Door	
49BXN	SWITCH, RED, OVERRIDE WARNING Wired Hot, with ESC, Mounted Left of Driver	
49BTR	WIRING MOD, DOME LIGHTS Mounted in Ceiling	
49NBM	MIRROR, CROSS VIEW, EXTERIOR (2) {Rosco High Definition} Black, Heated, with LED Downlit Front Lighting	
49EGC	MIRROR, INSIDE 6" x 30", Clear Safety Glass, Metal Back, Round Corners	
49DNB	MIRROR, REAR VIEW, EXTERIOR (Rosco AccuStyle) Black, Motorized Head, Heated, Breakaway Bracket	
49ENK	VISOR, INTERIOR, LEFT FRONT 6" x 30", Transparent, For Left Windshield	
49GDS COMPARTMENT ABOVE DRIVER Left of the Driver		
	Includes : COMPARTMENT ABOVE DRIVER Compartment Size: 39" x 10" x 10" : HINGES Piano Type	
49GGU	FIRE BLANKET 36 Sq. Ft.	
49JGJ	FIRE EXTINGUISHER 5 lb 3A-40BC Minimum, with Flexible Hose and Metal Nozzle	
49JGN	FIRE EXTINGUISHER, FRONT LOC Located Behind Driver Seat	
49GAY	KIT, BODY FLUID Texas	
49EBA	KIT, FIRST AID Plastic; 24 Unit, Spec State	
49MZV	LATCH, COMPARTMENT Locking, for Overhead Storage Compartment	
49JEY	LOCATION, BODY FLUID KIT on Bulkhead	
49GCH	LOCATION, FIRST AID KIT Right Side Front Bulkhead with Screws	
49GDG	PADDING COMPART ABOVE DRIVER Window; Safety Equipment Compartment, with Cutout for Dome Light	
49GLP	REFLECTORS, REAR (2) 3", Red, Mounted with Screws	
49GLM	REFLECTORS, SIDE, FRONT (2) 3", Amber; 1 Aft Drivers Window Left, 1 Aft Entrance Door Right, Mounted with Screws	
49GLA	REFLECTORS, SIDE, INTERMEDIATE (2) 3" Amber, 1 Each Side, Mounted with Screws, Below The Third Rub Rail From the Top	
49GLG	REFLECTORS, SIDE, REAR (2) 3", Red, Mounted with Screws	
49GED	SAFETY TRIANGLES Warning Reflectors, Mounted on Floor Between Driver Seat and Drivers Crash Barrier/ Stanchion/Partition	

December 01, 2023

<u>Vehicle Specifications</u> 2025 CE SCHOOL BUS (PB110)

<u>Code</u> 49GUB	<u>Description</u> CUTTER, SEAT BELT {TIE TECH Safecut} for Cutting Seat Belts	
49JGE	CUTTER, SEAT BELT, LOCATION Mounted on Panel Left of Driver	
49JAC	DEF FILLER DOOR with Non-Locking Latch	
49MZS	FUEL FILLER DOOR Non-Locking, Lever Latch, Spring Loaded to Hold in Open Position	
49CKT	FUEL FILLER PIPE Low Profile Neck Cap and Vent Hosing, for Use with Right Side Fill for Between the Rail Fuel Tanks, for Above the Floor Fuel Fill, for 25 GPM Fill Rate Only	
49GUM	INSPECTION PLATE Fuel Sending Unit 8" x 8" Steel	
49GVC	MUD FLAPS, REAR WHEELS (2) Rubber	
49ESH	SIGN, DESTINATION, FRONT LED Illuminated, Exterior Bulkhead Mounted, with 8" Letters "SCHOOL BUS"	
49ESG	SIGN, DESTINATION, REAR LED Illuminated, Exterior Bulkhead Mounted, with 8" Letters "SCHOOL BUS"	
49UBZ	STATE OF OPERATION Texas	
Services Section:		
WARRANTY		
40126	WARRANTY Standard for CE, RE, BE School Bus Models, Effective with Vehicles Built March 1, 2017 or Later, CTS-3304H	
40YET	SERVICES, TOWING {Navistar} Service Call to 24-Month/Unlimited Mileage to the Nearest IC Bus Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$1100 (USA) Maximum Benefit per Incident	
40YGC	SRV CONTRACT, EXT VEH COVERAGE {Navistar} To 24-Month/50,000 Miles (80,000 km), Covers 100% Parts and Labor; Includes Body; Excludes Extending Warranty for Engine, Transmission, Perforation or Corrosion of Cab/Cowl Structure and Paint	
BODY FEATURES		
49GVN	WARRANTY 5-Year, Limited	
	SET GOVERN SPEED @ 60 MPH	
	DOT INSPECTION	
	WEIGHT SLIP	
	DVR CAMERA SYSTEM - SEON 5 CAMERA *** LHB INSTALL	
	TWO WAY RADIO - MOTOROLA XPR5550E	
	PRE DELIVERY INSPECTION CE MODEL	
	BACKUP CAMERA IN MIRROR 10X30 - CBC INSTALL	

<u>Financial Summary</u> 2025 CE SCHOOL BUS (PB110)

(US DOLLAR)

<u>Description</u>	<u>Price</u>
Net Sales Price:	\$152,520.00
Please feel free to contact me regarding these specifications sh pleased with the quality and service of an IC Corporation vehicl	
Prices are good for 30 days from the date of this proposal.	
PRICE PER BUS: \$152,520.00	
***OPTIONAL ITEMS TO CONSIDER (Not included in above pr	ricing) ***
\$260 per bus - Window frames black (does not include black pa	ninted posts in between windows)
\$70 per bus - Digital clock located on dash (right side)	
\$65 per bus - Waste container located right side forward of entr	y door
\$75 per bus - Black front grille with chrome surround	
\$185 per bus - Dual height hand rails on each side of entry step	well
This quote would be produced as a 2025MY product if awarded of code references. Estimated delivery: 300-365 Days from rece responsible for material shortages or delays due to the global C that of the represented OEM (IC Corp) or third-party vendors us be subject to any and all applicable surcharges at the time of but applicable surcharges will be the responsibility of the buyer. A but (i.e., A/C, GPS, two-way radios, camera surveillance equipment availability. These shortages/delays will not hold up invoicing a fluctuate. Instructions for payment of invoices will be provided upon email wiring or ACH instructions for payment.	eipt of a purchase order. Longhorn Bus Sales will not be held OVID-19 pandemic or any other reasons outside of our control, ed to complete a customers' bus order. Any buses ordered, will wild, due to the volatility of the producers' material costs. Any bus order may be delivered without OEM or third-party products t, etc.), and any such items will be installed immediately upon and or payment. Due to industry constraints, quote pricing may
Price does not include Buy Board fee of \$800 per purchase order	er, please add if applicable. Buy Board contract 630-20.
40PKZ Warranty: Longhorn Bus Sales will cover the warranty for miles. Longhorn Bus will cover 50K+ miles, up to the ending of the Specifications.	
CODE "49GVN WARRANTY 5-YEAR, LIMITED" IS A NAVISTA AFTERMARKET PARTS	AR WARRANTY ONLY, IT DOES NOT APPLY TO ANY
By signing this document in acceptance of an order, the custom is correct. Longhorn Bus Sales will not be responsible for any n in additional charges to the order. Thank you.	
Approved by Seller:	Accepted by Purchaser
Official Title and Date	Firm or Business Nam

15

Authorized Signature

Authorized Signature and Date

Financial Summary 2025 CE SCHOOL BUS (PB110)

December 01, 2023

This proposal is not binding upon the seller without Seller's Authorized Signature

Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

16