

STILL CREEK WASTEWATER TREATMENT IMPROVEMENTS CONTRACT FOR

Teal Services LLC

, 2024, is between the City of Bryan, a Texas home-rule (Contractor). City and Contractor, in consideration of the mutual covenants set forth herein, agree municipal corporation (City) and Teal Services, LLC, a Texas limited liability company This Contract, dated as follows:

1. Scope of Work

The work is generally described as Still Creek Wastewater Treatment Plant improvements in response to RFB #24-041, incorporated herein by reference. Contractor shall complete all work as indicated in the provisions and specifications in attached Exhibit A.

2. Payment

The City shall pay the Contractor according to the terms set forth in Exhibit A and the unit pricing sheet in Exhibit B. Except in the event of a duly authorized change order, approved by the City in writing, the total cost of all services provided under this Contract may not exceed \$6,061,300.

3. Time of Performance

- the work order of the City Engineer and fully complete all work hereunder within 656 days The Contractor shall commence work under this Contract on the date specified in thereafter. The Contractor further agrees to pay as administrative costs the sum of \$\sum{\$1000}\$ for each consecutive calendar day used over and above the specified work time.
- shall be prepared to complete the work in an expedient and efficient manner in order to complete Time is an important and material consideration of this Contract. The Contractor the work by the time specified in Section 3.A.

Performance Standards, Indemnification, and Release 4

As an experienced and qualified Contractor, the Contractor agrees that the services provided by the Contractor reflect the professional and industry standards, procedures, and performance of services under this Contract, will be pursuant to the standard of performance in the profession. The Contractor agrees that the Contractor will exercise diligence and due care and The Contractor agrees the selection and supervision of personnel, and performances.

of the City shall not constitute, or be deemed, a release of the responsibility and liability of the Contractor, its employees, agents, or associates for the exercise of skill and diligence to promote deemed to be the assumption of responsibility by the City for any defect or error in the aforesaid perform in a good and workmanlike manner all of the services pursuant to this Contract. Approval the accuracy, competency and quality of the services provided, nor shall the City's approval be services provided by the Contractor, its employees, associates, agents, or subcontractors.

- any part of the services hereunder itself shall in no way alter the Contractor's obligations or the The Contractor shall promptly correct any defective work furnished by the Contractor at no cost to the City. The City's approval, acceptance, use of, or payment for, all or City's rights hereunder.
- agents, servants, or employees of the City. As an independent contractor, the Contractor shall be responsible for the services and the final work product contemplated under this Contract. Except for materials furnished by the City, the Contractor shall supply all materials, equipment, and labor required for the services to be provided under this Contract. The Contractor shall have ultimate subcontractors, and the City shall have no control of or supervision over the employees of the In all activities or services performed hereunder, the Contractor is an independent contractor and not an agent or employee of the City. The Contractor and its employees are not the control, supervise, manage, discharge, and compensate all of its employees or control over the execution of the services. The Contractor shall have the sole obligation to employ, Contractor or any of the Contractor's subcontractors.
- and other persons, as well as their personal property, while in the vicinity of the project or any of The Contractor must at all times exercise reasonable precautions on behalf of, and the work being done on or for the project. It is expressly understood and agreed that the City shall not be liable or responsible for the negligence of the Contractor, its officers, employees, agents, be solely responsible for, the safety of its officers, employees, agents, subcontractors, licensees, subcontractors, invitees, licensees, and other persons.
- suits, actions, or claims of any character, name and description brought for or on account of from the Contractor's negligent performance of the work, or by or on account of any claims save harmless the City, its officers, agents and employees in accordance with this indemnification clause only for that portion of the damage caused by Contractor's Responsibility for damage claims (indemnification): Contractor shall defend, any injuries or damages received or sustained by any person or persons or property resulting or amounts recovered under the Workmen's Compensation Law or any other law, ordinance, order or decree, and his sureties shall be held until such suit or suits, action or actions, claim or claims for injury or damages as aforesaid shall have been settled and satisfactory evidence to the effect furnished the City. Contractor shall defend, indemnify and indemnify and save harmless the City and all its officers, agents, and employees from all negligence.
- and character, including the cost of defense thereof, for any injury to, sickness or death of Release. The Contractor releases, relinquishes, and discharges the City, its officers, agents, and employees from all claims, demands, and causes of action of every kind

or its employees that is caused by or alleged to be caused by, arises out of, or is in connection with the Contractor's negligent performance of the work. Both the City and the Contractor expressly intend that this release shall apply regardless of whether said claims, demands, and the Contractor or its employees and any loss of or damage to any property of the Contractor causes of action are covered, in whole or in part, by insurance.

5. Termination

- written notice. Upon the Contractor's receipt of such notice, the Contractor shall cease work immediately. The Contractor shall be compensated for the services satisfactorily performed prior The City may terminate this Contract at any time upon thirty (30)-calendar days' to the termination date.
- Contract, or if the Contractor violates any of the agreements of this Contract, the City has the right to terminate this Contract by giving the Contractor five (5) calendar days' written notice. The If, through any cause, the Contractor fails to fulfill its obligations under this Contractor will be compensated for the services satisfactorily performed before the termination
- of liability to the City for damages sustained by the City because of any breach of contract by the Contractor. The City may withhold payments to the Contractor for the purpose of setoff until the No term or provision of this Contract shall be construed to relieve the Contractor exact amount of damages due the City from the Contractor is determined and paid.

6. Insurance Requirements

as Exhibit C. All policies, endorsements, certificates, and/or binders shall be subject to approval by the City as to form and content. These requirements are subject to amendment or waiver only if so approved in writing by the City. A lapse in any required coverage shall be a breach of this Contractor agrees to have and maintain the policies set forth in the insurance requirements attached

7. Governmental Contract Requirements

- Contractor must submit a disclosure of interested parties to the City, as applicable under Section 2252.908 of the Texas Government Code, for any contract that requires approval by City Council, has a value of at least \$1 million, or is for services that would require a person to register as a lobbyist. The disclosure must be submitted at the time the Contractor submits the signed contract to the City and on a form prescribed by the Texas Ethics Commission.
- Contractor verifies that it is not engaged in business with Iran, Sudan, or a foreign terrorist organization, as prohibited by Section 2252.152 of the Texas Government Code.
- Contractor verifies, to the extent authorized by law and as applicable under Section 2271.002 of the Texas Government Code, that for any contract that has a value of \$100,000 or more, it does not, and will not for the duration of this Contract, boycott Israel.

8. Bond Requirement

less than 100% of the Contract price, conditioned upon faithful performance of the Contract and For contracts over \$100,000.00, a Performance Bond and a Payment Bond in an amount of not payment of all persons supplying labor and furnishing materials, shall be executed by the successful bidder and accompany this signed Contract.

9. Miscellaneous Terms

- This Contract has been made under and shall be governed by the laws of the State Venue for any matter arising from this Contract shall be in the court of competent The parties agree that performance and all matters related thereto shall be in Brazos jurisdiction in Brazos County, Texas. County, Texas. of Texas.
- Notices shall be mailed to the addresses designated herein or as may be designated in writing by the parties from time to time and shall be deemed received when sent postage prepaid U.S. Mail to the following addresses:

The City of Bryan Teal Services LLC
Attn: Mark Jurica Attn: Chad Smith
P.O. Box 1000 4144 FM 244

Email: chad@tealtexas.com Anderson, Texas 77830 Bryan, Texas 77805

deemed or construed to be a waiver of any other term or condition or subsequent waiver of the No waiver by either party hereto of any term or condition of this Contract shall be same term or condition.

- This Contract represents the entire and integrated agreement between the City and the Contractor and supersedes all prior negotiations, representations, or agreements, either written or oral. This Contract may only be amended by written instrument approved and executed by the
- This Contract and all rights and obligations contained herein may not be assigned by the Contractor without the prior written approval of the City.
- The Contractor, its agents, employees, and subcontractors must comply with all applicable federal and state laws, the charter and ordinances of the City of Bryan, and with all applicable rules and regulations promulgated by local, state, and national boards, bureaus, and agencies. The Contractor must obtain all necessary permits and licenses required in completing the work and providing the services required by this Contract.
- or regulation shall be deemed stricken, and all remaining provisions shall continue to be valid and binding upon City and Contractor, who agree that the Contract shall be reformed to replace such Any provision or part of this Contract held to be void or unenforceable under law

stricken provision or part thereof with a valid and enforceable provision that comes as close as possible to expressing the intention of the stricken provision.

- The exhibits attached to this Contract are incorporated herein and shall be considered a part of this Contract. In the event of a conflict between this Contract and any exhibits or attachments to this Contract, the provision of this Contract shall prevail.
- transmit any information, not intended for public release, which is provided by or generated for the City. This requirement does not include information provided by the City to the public or and procedures shall include, at a minimum, the security control requirements "reflective of actions 52.204-21(b) (2016). Contractor shall include the substance of this clause in subcontracts under protect the Contractor's information systems whenever the information systems store, process or simple transactional information, such as that necessary to process payments. These requirements a prudent business person would employ" which are outlined in the Federal Acquisition this contract in which the subcontractor may have City contract information residing in or The Contractor shall apply basic safeguarding requirements and procedures to Regulations FAR 52.204-21(b) and codified in the Code of Federal Regulations at 48 C.F.R. § transiting through its information system.
- The parties acknowledge that they have read, understood, and intend to be bound by the terms and conditions of this Contract.

[Remainder of Page Intentionally Left Blank - Signature Page Follows]

CITY OF BRYAN:

APPROVED AS TO FORM

Thomas A. Leeper, City Attorney

Bobby Gutierrez, Mayor

APPROVED

PREPARED AND RECOMMENDED

ATTEST

Mark Jurica, Treatment and Compliance Manager

Mary Lynne Stratta, City Secretary

Date:

Jayson Barfknecht, P.E., Ph.D., Director of Public Works

PREPARED FOR PROCESSING

APPROVED FOR COUNCIL

Kean Register, City Manager

CONTRACTOR

Name: Printed Title:

Date:

(Contractor - Corporate Seal)

COUNTY OF LIM

STATE OF

day of JM This instrument was acknowledged before me on the

on behalf of had Shit



or The State of Texas

Thomas A. Leeper, City Attorney	Bobby Gutierrez, Mayor
PREPARED AND RECOMMENDED	ATTEST
Mark Jurica, Treatment and Compliance Manager	Mary Lynne Stratta, City Secretary
PREPARED FOR PROCESSING	Date:
Jayson Barfknecht, P.E., Ph.D., Director of Public Works	
APPROVED FOR COUNCIL	
Kean Register, City Manager	
CONT	CONTRACTOR:
By:	By: Printed Name:
Date: _	
STATE OF \$ ACKNOWLEDGEMENT	E Zu
,	
This instrument was acknowledged before me on the by on	the day of, 20, on behalf of

APPROVED

APPROVED AS TO FORM

CITY OF BRYAN:

Notary Public in and for The State of Texas



CITY OF BRYAN, TEXAS

STILL CREEK WASTEWATER TREATMENT PLANT IMPROVEMENTS

PROJECT NO. 411-D4-2414 **BID SET**

BRYAN CITY COUNCIL

BOBBY GUTTUERREZ - MAYOR

PAUL TORRES - SINGLE MEMBER DISTRICT 1

RAY ARRINGTON - SINGLE MEMBER DISTRICT 2

JARED SALVATO - SINGLE MEMBER DISTRICT 3

JAMES EDGE SINGLE MEMBER DISTRICT 4

MARCA EWERS - SHURTLEFF - SINGLE MEMBER DISTRICT 5

KEVIN BORISKIE - AT LARGE, PLACE 6


CITY MANAGER

KEAN REGISTER

PUBLIC WORKS DIRECTOR JAYSON BARFKNECHT, PH.D, P.E.

CITY OF BRYAN DATE

APRIL 2024



LOCATION PLAN



AUSTIN, TEXAS Transportation



PROJECT LOCATION: 2028 QUALITY PARK LANE, BRYAN, TEXAS

Water

Environment

Energy

Facilities

DATE

\forall	· · · · · · · · · · · · · · · · · · ·	<u> </u>		1	₹.	V		<u>©</u>	₩/
SHEET INDEX									
GENERAL		ELECTRICAL CONIT	NUED						
G-0 G-1	COVER SHEET SHEET INDEX	EZ-1 EZ-2	ELECTRICAL STANDARD DETAILS—I ELECTRICAL STANDARD DETAILS—II						
5-1 5-2	GENERAL NOTES	EZ-2 EZ-3	ELECTRICAL STANDARD DETAILS-III						
3-3	GENERAL LEGEND AND ABBREVIATIONS	EZ-4 EZ-5	ELECTRICAL STANDARD DETAILS—IV ELECTRICAL STANDARD DETAILS—V						
-4 -5	DESIGN CRITERIA								
5	PROCESS FLOW DIAGRAM — GREASE FACILITY PROCESS FLOW DIAGRAM — SOLID PHASE DIGESTER MODIFICATIONS	INSTRUMENTATION							
	AREA CLASSIFICATION AND MATERIALS SCHEDULE	I-1 I-2	INSTRUMENTATION LEGEND AND SYMBOLS I INSTRUMENTATION LEGEND AND SYMBOLS I						
		ID-1	INSTRUMENTATION WAS HOLDING TANK PIPI	NG AND INSTRUMENTATION DIAGRAM					
<u>IVIL</u> -1	EXISTING SITE PLAN AND OVERALL DEMOLITION AREAS	IG-1	GREASE FACILITY PIPING AND INSTRUMENTA	TION DIAGRAM					
-2	OVERALL SITE PLAN	IG-2 IH-1	VOLUTE PRESS SYSTEM PIPING AND INSTR HEADWORKS PIPING AND INSTRUMENTATION	UMENTATION DIAGRAM					
C-3 CZ-1	MODIFIED YARD PIPING AND GRADING PLAN CIVIL DETAILS I	IZ-1	EXISTING PLC AND RIO LOCATION PLAN	DIAGRAM					
	CIVIL DETAILS I	IZ-2	INSTRUMENT INSTALLATION DETAILS						
EMOLITION D-1	DIGESTER ROOF DEMOLITION PLAN								
D-2	DIGESTER GROUND LEVEL DEMOLITION PLAN								
D-3	DIGESTER LOWER LEVEL DEMOLITION PLAN								
D-4 D-5	DIGESTER DEMOLITION SECTION I FLARE DEMOLITION PLAN								
G-1	GREASE FACILITY DEMOLITION PLAN								
H-1	HEADWORKS BAR SCREEN DEMOLITION PLAN AND SECTIONS								
TRUCTURAL									
D-1	BLOWER FACILITY FOUNDATION PLAN AND SECTION								
D-2 G-1	DIGESTER NO.3 SECTION GREASE FACILITY FOUNDATION AND CANOPY FRAMING PLAN								
-2	GREASE FACILITY SECTION								
Z-1	GENERAL NOTES I								
Z-2 Z-3	GENERAL NOTES II TYPICAL STRUCTURAL DETAILS I								
<u>'-4</u>	TYPICAL STRUCTURAL DETAILS II								
-5	TYPICAL STRUCTURAL DETAILS III								
PROCESS MECHANI	CAL								
A−1 AD−1	MECHANICAL LEGEND DIGESTER NO. 3 PLAN								
D-2	DIGESTER NO. 3 SECTION								
)-3	DIGESTER BUILDING ROOF PLAN MODIFICATION								
-4	DIGESTER BUILDING GROUND AND LOWER LEVEL PLANS MODIFICATIONS								
)−5)−6	DIGESTER BUILDING MODIFICATIONS - SECTIONS I								
-7	BLOWER FACILITY PLAN								
-8	BLOWER FACILITY SECTION								
(G−1 (G−2	GREASE FACILITY PLAN GREASE FACILITY SECTIONS I								
-3	GREASE FACILITY SECTIONS II								
/G−4 /H−1	GREASE FACILITY SECTIONS III								
H-1 Z-1	HEADWORKS MODIFICATIONS PLAN AND SECTIONS MECHANICAL DETAILS I								
Z-2	MECHANICAL DETAILS II								
4Z-3	MECHANICAL DETAILS III								
ECTRICAL									
-1	ELECTRICAL LEGEND AND SYMBOLS I								
-2 -3	ELECTRICAL LEGEND AND SYMBOLS II ELECTRICAL GENERAL NOTES								
-4	ELECTRICAL SITE PLAN - OVERALL DEMOLITION								
E-5	ELECTRICAL ROOM DEMOLITION								
:-6 :-7	ELECTRICAL ONE LINE DIAGRAM DEMOLITION I ELECTRICAL ONE LINE DIAGRAM DEMOLITION II AND RISER DIAGRAM								
-/ -8	ELECTRICAL ONE LINE DIAGRAM DEMOLITION II AND RISER DIAGRAM ELECTRICAL MCC—A ELEVATION DEMOLITION								
-9	ELECTRICAL SITE PLAN- OVERALL MODIFIED								
-10 -11	ELECTRICAL ONE LINE DIAGRAM MODIFICATION I ELECTRICAL ONE LINE DIAGRAM MODIFICATION II								
-12	ELECTRICAL ONE LINE DIAGRAM MODIFICATION II								
-13	ELECTRICAL GREASE SCHEMATIC I								
:–14 :D−1	ELECTRICAL GREASE SCHEMATIC II ELECTRICAL BLOWER MODIFICATION PLAN								
D-2	ELECTRICAL BLOWER ENLARGED PLAN AND RISER DIAGRAM								
D-3	ELECTRICAL DIGESTER ENLARGED PLAN								
D-4 D-5	ELECTRICAL BUILDING POWER AND CONTROL PLANS								
D-6	ELECTRICAL MCC-C1 ONE LINE MODIFICATION AND PANEL SCHEDULE ELECTRICAL MCC-C1 ELEVATION AND INTERFACE DIAGRAM								
D-7	FLECTRICAL DIGESTER DETAILS								
	ELECTRICAL BLOWER SCHEMATIC ELECTRICAL GREASE FACILITY DEMOLITION								
D-8 G-1	ELECTRICAL GREASE FACILITY DEMOLITION ELECTRICAL GREASE AREA PHOTOS AND DEMOLITION RISER								,///
G-1 G-2									AND OF THE
G-1 G-2	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL ONE LINE DIAGRAM DEMOLITION II AND RISER DIAGRAM								
EG-1 EG-2 EG-3 EG-4 EG-5	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL ONE LINE DIAGRAM DEMOLITION II AND RISER DIAGRAM ELECTRICAL GREASE FACILITY DETAILS								
EG-1 EG-2 EG-3 EG-4 EG-5 EH-1 EH-2	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL ONE LINE DIAGRAM DEMOLITION II AND RISER DIAGRAM ELECTRICAL GREASE FACILITY DETAILS ELECTRICAL SCREENING FACILITY DEMOLITION PLAN ELECTRICAL SCREENING FACILITY DEMOLITION PHOTOS								CHRISTOPHER V
EG-1 EG-2 EG-3 EG-4 EG-5 EH-1 EH-2 EH-3	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL ONE LINE DIAGRAM DEMOLITION II AND RISER DIAGRAM ELECTRICAL GREASE FACILITY DETAILS ELECTRICAL SCREENING FACILITY DEMOLITION PLAN ELECTRICAL SCREENING FACILITY DEMOLITION PHOTOS ELECTRICAL SCREENING FACILITY MODIFICATION ELECTRICAL SCREENING FACILITY MODIFICATION								y
ED-8 EG-1 EG-2 EG-3 EG-4 EG-5 EH-1 EH-2 EH-3 EH-3 EH-4 EH-5	ELECTRICAL SITE PLAN — DETAIL MODIFIED I AND RISER DIAGRAM ELECTRICAL OR LINE DIAGRAM DEMOLITION II AND RISER DIAGRAM ELECTRICAL SCREENING FALUITY DETAILS DESCRIPTION OF A DESC								97453
G-1 G-2 G-3 G-4 G-5 H-1 H-2 H-3 H-4	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL ONE LINE DIAGRAM DEMOLITION II AND RISER DIAGRAM ELECTRICAL GREASE FACILITY DETAILS ELECTRICAL SCREENING FACILITY DEMOLITION PLAN ELECTRICAL SCREENING FACILITY DEMOLITION PHOTOS ELECTRICAL SCREENING FACILITY MODIFICATION ELECTRICAL SCREENING FACILITY MODIFICATION								97453 Vicense Vional III
G-1 G-2 G-3 G-4 G-5 H-1 H-2 H-3 H-4 H-5	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL OR LINE DAGRAM DEMOUTION II AND RISER DIAGRAM ELECTRICAL GREASE FACULTY DETAILS ELECTRICAL SCREENING FACULTY DEMOUTION PLAN ELECTRICAL SCREENING FACULTY DEMOUTION PHOTOS ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY RACK DETAILS								97453 Constant ONAL 978
EG-1 EG-2 EG-3 EG-4 EG-5 EH-1 EH-2 EH-3	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL OR LINE DAGRAM DEMOUTION II AND RISER DIAGRAM ELECTRICAL GREASE FACULTY DETAILS ELECTRICAL SCREENING FACULTY DEMOUTION PLAN ELECTRICAL SCREENING FACULTY DEMOUTION PHOTOS ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY RACK DETAILS	DESIONED BY: D. HERNANDEZ	CDM	_	CITY OF BRYAN TEYAS	<u> </u>			PROJECT NO. 2381-2
G-1 G-2 G-3 G-4 G-5 H-1 H-2 H-2 H-3 H-3 H-4	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL OR LINE DAGRAM DEMOUTION II AND RISER DIAGRAM ELECTRICAL GREASE FACULTY DETAILS ELECTRICAL SCREENING FACULTY DEMOUTION PLAN ELECTRICAL SCREENING FACULTY DEMOUTION PHOTOS ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY RACK DETAILS	DESIGNED BY: D. HERNANDEZ DRAWN BY: D. GURAY	ÇDM.		CITY OF BRYAN, TEXAS				PROJECT NO. 2381–2 FILE NAME: G001NFI
EG—1 EG—2 EG—3 EG—4 EG—5 EH—1 EH—2 EH—3 EH—3 EH—4	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL OR LINE DAGRAM DEMOUTION II AND RISER DIAGRAM ELECTRICAL GREASE FACULTY DETAILS ELECTRICAL SCREENING FACULTY DEMOUTION PLAN ELECTRICAL SCREENING FACULTY DEMOUTION PHOTOS ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY RACK DETAILS	SHEET CHK'D BY: C. VARNON	Smitn	STILL CREE		FATMENT	SHI	EET INDEX	PROJECT NO. 2381- FILE NAME: GOOTNF SHEET NO.
EG-1 EG-3 EG-3 EG-4 EG-5 EH-1 EH-2 EH-3 EH-3 EH-4	ELECTRICAL SITE PLAN — DETAIL MODIFIED ELECTRICAL OR LINE DAGRAM DEMOUTION II AND RISER DIAGRAM ELECTRICAL GREASE FACULTY DETAILS ELECTRICAL SCREENING FACULTY DEMOUTION PLAN ELECTRICAL SCREENING FACULTY DEMOUTION PHOTOS ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY DETAILS HEADWORKS RISER DIAGRAM ELECTRICAL SCREENING FACULTY RACK DETAILS	DESIGNED BY. D. HERNANGEZ DOWN BY. D. UNIAV SHEET ON'D BY. C. WHENDA GROSS GIN'D BY. A. WELKE MERPOYLD BY. C. WHENDA			CITY OF BRYAN, TEXAS K WASTEWATER TRI ANT IMPROVEMENTS		SHI	EET INDEX	PROJECT NO. 2381- FILE NAME: GOOTNF

G-1 100% SUBMITTAL ∇

- THE CONTRACTOR SHALL GIVE THE CITY A MINIMUM OF 72 HOURS NOTICE BEFORE BEGINNING CONSTRUCTION.
- UPON THE COMPLETION OF THE PROPOSED IMPROVEMENTS AND PRIOR TO ACCEPTANCE BY THE OWNER, THE ENGINEER SHALL CERTIFY IN WRITING THAT THE PROPOSED IMPROVEMENTS WERE CONSTRUCTED IN CONFORMANCE WITH THE

⟨В/

- PROPOR TO BEGINNING MY CONSTRUCTION, THE CONTRACTOR SHALL YERRY MORIZONTAL AND VERTICAL LOCATIONS OF ALL KNOWN ENSTRUCTURES WHICH WILL EITHER BE CONNECTED TO, ADMICKED, OR CROSSED, IF HERE ARE ANY CONFLICTS BETWEEN PROPOSED AND EXISTING UITLIES, OR IF THE EXISTING UITLIES ARE IN ANY WAY DIFFERENT FROM WHAT IS SHOWN ON THE DRAWINGS, IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE CITY'S BEFORE PROCEEDING WITH ANY CONSTRUCTION. THE CONTRACTOR SHALL PROVIDE TO THE CITY, FOR THE CITY'S APPROVAL, A SOLUTION FOR RESOLUNGS SUCH CONFLICTS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ALL FITTINGS, ADAPTERS, ETC, AND RESOLVING ALL CONFLICTS AT HIS EXPENSE
- NO MORY SMALL BE PREFORMED ON SALIDEDVS, SUNDAYS, OR CITY HOLDAYS WITHOUT WRITTEN PERMISSION BY OWNER THE SECRIFIED CONTRACT TIMES WERE ESTREINEND ASSUMMENT ON WEEKEND ON HOLDAYS WERE COUNTED IN DETERMINING THE NUMBER OF CONSECUTIVE WORKING DAYS USED TO COMPLETE PROJECT. WORKING HOURS ARE UNITED TO 7:00 AM TO 600 PM WIDDOWN THROUGH FRIEND.
- CONTRACTOR SHALL PROVIDE "AS-BUILT" PLANS TO THE ENGINEER SO THAT THE REPRODUCIBLES OF THE ENGINEERING PLANS MAY BE CORRECTED TO REFLECT "RECORD DRAWINGS" CONDITIONS.
- 6 IN CASE OF CONFLICT BETWEEN PLANS AND/OR SPECIFICATIONS AND CITY OF BRYAN OR TCEQ REGULATIONS, THE REGULATIONS SHALL PREVAIL, UNLESS A VARIANCE HAS BEEN APPROVED.
- CONTRACTOR SHALL MAINTAIN ACCESS TO EXISTING DRIVEWAYS AT ALL TIMES.

PROJECT INFORMATION:	
OWNER:CITY_OF_BRYAN	PHONE: (979) 209-5900
ADDRESS: 2028 QUALITY PARK LANE, BRYAN, TX, 77803	
OWNER'S REPRESENTATIVE RESPONSIBLE FOR PLAN ALTERATIONS:	
CDM SMITH INC	PHONE: (512) 346-1100
PERSON OR FIRM RESPONSIBLE FOR EROSION/SEDIMENTATION CONTROL MAINTENANCE:	
CONTRACTOR	PHONE:
PERSON OR FIRM RESPONSIBLE FOR TREE/NATURAL AREA PROTECTION MAINTENANCE:	
CONTRACTOR	PHONE:

- THE CONTRACTOR SHALL OBTAIN ALL REQUIRED CONSTRUCTION PERMITS PRIOR TO COMMENCING WORK. NO SEPARATE PAYMENT.
- CONTRACTOR AREAS FOR PARKING, LAYDOWN, AND TEMPORARY SPOIL STORAGE SHALL BE AS SHOWN IN THE DRAWINGS. CONTRACTOR TO RESTRICT HIS OPERATIONS TO THESE AREAS.
- WATER FOR USE IN CONSTRUCTION SHALL BE FURNISHED BY THE CONTRACTOR.
- 14. THE CONTRACTOR SHALL COORDINATE ALL MATERIALS TESTS TO BE CONDUCTED BY AN INDEPENDENT LARGRATORY AT THE FREQUENCY AND LOCATIONS SPECIFIED. A COPY OF ALL TEST RESULTS SHALL BE FURNISHED TO THE OWNER'S REPRESENTATIVE, CITY OF AUSTIN, ENGINEER, AND THE CONTRACTOR, CONTACT THE OWNER 48 HOURS PRIOR TO DENSITY TESTING. FAILED TESTS SHALL BE REPEATED AT THE CONTRACTOR'S SOLE EXPENSE.
- 15. PRIOR TO REGINNING CONSTRUCTION, THE OWNER OR HIS AUTHORIZED REPRESENTATIVE WILL CONVENE A PRE-CONSTRUCTION CONFERENCE BETWEEN THE OWNER, ENGINEER, CONTRACTOR(S), AND ANY OTHER AFFECTED PARTIES.

ENVIRONMENTAL

REVW_CHRIS] images: []

VDR Time: 4/8/2024 6:42:33 P

—pw.bentley.com;pw_ext\2381\28

— pw.dror RESERVED.

— RIGHTS RESERVED.

S: THESE DOCUMENTS AND DESI AND D

MS_2234, R by: GURAVD mith—az02—p SMITH ALL I DOCUMENTS:

- ALL SITE WORK MUST COMPLY WITH ENVIRONMENTAL REQUIREMENTS AS SHOWN AND SPECIFIED IN THE EROSION AND SEDIMENTATION CONTROL DRAWINGS AND DETAILS, TREE PROTECTION NOTES AND DETAILS, AND SPECIFICATIONS.
- ALL DISTURBED AREAS SHALL BE RESTORED AND CONTRACTOR SHALL REPECTATE ALL PROSECUTE OF FILL APRAS UPON COMPETION OF CONSTRUCTION. THE SEEDING SHALL BE APPLIED AT THE SPECIFIED RATE OVER ALL AREAS DISTURBED BY THE CONTRACTOR. SOL STABILIZATION OF DISTURBED BY THE CONTRACTOR. SOL STABILIZATION OF DISTURBED AREAS SHALL PROVIDE PERMANENT SURFACE COVERAGE THAT MINIMIZES EROSION AND SEDIMENT TRANSPORT AWAY FROM THE SITE AND THAT MEETS THE APPROVAL OF THE ENGREEN SHALL PROVIDE PERMANENT SURFACE.
- 3 NO TREES SHALL BE REMOVED WITHOUT THE ENGINEER'S APPROVAL. AS APPROPRIATE, THE ENGINEER MAY ELECT TO ALTER SITE IMPROVEMENTS SLIGHTLY TO AVOID DAMAGING EXISTING TREES.

CONTROL OF WORK

 ∇

\c/

1 THE CONTRACTOR SHALL FIELD VERIFY ALL EXISTING FACILITIES (SIGNS, UTILITIES, STRUCTURES, ETC). CARE SHALL BE TAKEN TO PROTECT EXISTING FACILITIES, ITEMS TO BE DISTURBED BY NEW WORK SHALL BE PROTECTED OR REPLACED.

\E/

- 3 NO BURNING OF TREES, BRUSH, RUBBISH, VEGETATION, OR OTHER OBJECTIONABLE MATTER WILL BE ALLOWED.
- 4 THE CONTRACTOR SHALL MANTAIN ALL WORK AREAS FREE FROM DUST WHICH WOULD CAUSE A HAZARO DRIVINGNET TO OTHERS. SPRINKLING OR SHALLAR METHODS WILL BE FERMITED TO CONTROL JUST, LUSE OF PETROLICULA PRODUCTS OR CHLORIDES IS PROHIBITED. SPRINKLING MUST BE REPEATED AS NEEDED TO KEEP THE DISTURBED AREA DAMP, DUST CONTROL SHALL BE PERFORDED AS THE WOOR PROCEEDS WHENEVER A POTENTIAL FOR DUST HUISANCE OR HAZARO
- 5 ANY DAMAGE TO EXISTING STRUCTURES (IE, FENCES, WALLS, R.O.W. MONUMENTS, SIGNS, CULVERTS, AND CONCRETE APRONS, ETC) DURING CONSTRUCTION SHALL BE REPAIRED OR REPLACED AT CONTRACTOR'S EXPENSE. REPLACEMENT MATERIALS SHALL MATCH EXISTING. ALL REPAIRS MUST BE APPROVED BY OWNER OR OWNER REPRESENTATIVE.
- 6 TRACK EQUIPMENT WILL NOT BE ALLOWED ON PAVED ROADWAYS WITHOUT SUITABLE PROTECTION UNDER TRACKS.
- 8 ALL FLEX BASE PLACED FOR REPAIR OF GRAVEL ROADS, DRIVEWAYS, ETC, SHALL BE COMPACTED TO 4" THICKNESS PER LIFT AT 95% MODIFIED PROCTOR DENSITY. FINISHED SURFACE SHALL MATCH EXISTING SURFACE.
- 9 THE CONTRACTOR SHALL LOCATE, PROTECT, AND MAINTAIN BENCHMARKS, MONUMENTS, AND CONTROL POINTS. REESTABLISH ANY DISTURBED ITEMS BY A TEXAS REGISTERED PUBLIC LAND SURVEYOR, AT NO ADDED COST TO OWNER.

SAFETY

- 1 ALL CONSTRUCTION OPERATIONS SHALL BE ACCOMPLISHED IN ACCORDANCE WITH APPLICABLE REGULATIONS OF THE U.S. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA).
- CELECTRICAL LINES ARE LOCATED CLOSE TO THE PROJECT. THE ATTENTION OF THE CONTRACTOR IS DIRECTED TO THE STATE LAW (VERNON'S ANNOTATED TEXAS STATUTES, ARTICLE 1436(c)) CONCERNING OPERATIONS IN THE VICINITY OF ELECTRICAL LINES & THE NEED FOR TETEOTHE PREVAILED THE TOTAL TOTAL CONTRACTOR OF COLVENTIONAL SAFETY AND HEALTH ANNINSTRATION FOR THE PROPERTY OF THE PROPERTY

GENERAL CONSTRUCTION NOTES

IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY THE EXACT LOCATION OF ALL EXISTING UNDERGROUND UTILES. FURTHERMORE, THE CONTRACTOR SHALL CONTACT ALL UTILITY COMPANY REPRESENTATIVES A MINIMUM OF 48 HOURS IN ADVANCE OF ANY EXCLANATION.

W

\F/

\G/

- ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE SPECIFICATION ESSED IN THIS BID PACKAGE ALL PRIBLIC UTILITIES AS DEFINED BY THE LOCATIONS OF PHIBAC UTILITY RESIDENTS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE 2012 BYCS UNIFIED TECHNICAL SPECIFICATIONS. THE STANDARD SPECIFICATIONS AND DEFINIS ARE AWAILABLE AT HITP://WWW.BCSUNITED.NET/ THE CONTRACTOR SHALL KEEP A SET OF THE CURRENT SPECIFICATIONS AND DEFINIS AND EATHER AT ALL THE SEA. ALL WORK SHALL BE INSPECIED BY THE STAFF OF THE CITY ENGINEER OF BRYAN. ALL WORK SHALL BE INSPECIED BY THE STAFF DENINEER.
- 3 IN LIEU OF USING THE CONSTRUCTION MATERIALS INDICATED IN THESE PLANS, THE CONTRACTOR SHALL OBTAIN WRITTEN APPROVAL FROM THE ENGINEER FOR ANY SUBSTITUTION PRIOR TO CONSTRUCTION, REQUESTS FOR CHANCES SHOULD INCLUDE PRODUCT INFORMATION AND AN ENGINEER'S SEA, WHERE APPLICABLE, THE CONTRACTOR SHALL BE FINANCIALLY RESPONSIBLE FOR THE ENGINEER'S TIME SPENT REVIEWING CHANGES AND REDESIGNING BASED ON CONTRACTORS CONCUESTS.
- 4 IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO COMPLY WITH ALL STATE AND FEDERAL REQUIATIONS RECARDING CONSTRUCTION ACTIVITIES NARE REPROZED OVERHEAD FOWER LINES, ADDITIONALLY CONTRACTOR SHALL COORDINATE ALL PROPOSED WORK AND PROCEDURES WITH THE BTU AND WHERE APPLICABLE, BRYAN RURAL ELECTRICAL DEPARTMENT AT THE CONTRACTORS EXPENS.
- 5 ALL MATERIALS & LABOR NOT IDENTIFIED AS A SEPARATE BID ITEM SHALL BE CONSIDERED SUBSIDIARY TO THE ITEM IN WHICH IT IS USED. ALL MATERIALS AND EQUIPMENT SHALL BE BOTH FURNISHED AND INSTALLED UNLESS OTHERWISE NOTED.
- 6 THE CONTRACTOR MUST PROVIDE CONSTRUCTION STAKING FROM THE INFORMATION PROVIDE ON THESE PLANS. THE CONTRACTOR SHALL PROVIDE CUT-SHEETS FROM A REGISTERED SURVEYOR TO THE OWNERS'S REPRESENTATIVE PRIOR TO THE CONSTRUCTION OF ANY FACILITY.
- 7 ALL SOIL EXPOSED BY CONSTRUCTION SHALL RECEIVE HYDROMULCH SEEDING EXCEPT WHERE THE LANDSCAPE PLAN SPECIFIES OTHERWISE.



D. HERNANDEZ D. GURAV C. VARNON SHEET CHK'D BY:__ A. WOELKE ROSS CHK'D BY:___ C. VARNON PROVED BY: REV. DATE DRWN CHKD APRIL 2024




CITY OF BRYAN, TEXAS

STILL CREEK WASTEWATER TREATMENT PLANT IMPROVEMENTS

GENERAL NOTES

ROJECT NO. 2381-2846 SHEET NO. G-2



W

GREASE F.	ACILITY IMPI	ROVEMENTS
PARAMETER	UNIT	DESIGN
STORAGE TANKS		
TANK TYPE	TYPE	CONE BOTTOM, DOME TOP
NUMBER OF TANKS	NO.	2
TANK DIAMETER	FT-IN	14'-0"
TANK HEIGHT(1)	FT	20'-4"
CONE ANGLE OF INCLINATION	DEGREES	22
VOLUME OF EACH TANK	GAL	21,237
USABLE VOLUME OF EACH TANK	GAL	20,085
TANK MATERIAL	TYPE	FRP
VOLUTE DEWATERING PRESS		
NUMBER OF DEWATERING DRUMS	NO.	3
MAX SOLIDS LOADING PER DRUM	LB/HR	350
	GPM	10
MAX HYDRAULIC LOADING PER DRUM	GPM	16
WASHWATER	GAL	112
FLASH MIXING TANK VOLUME	GAL	98
FLASH MIXING TANK USBALE VOLUME	GAL	191
FLOCULATION TANK VOLUME	GAL	167
FLOCULATION TANK USBALE VOLUME TOTAL POWER USE	HP	4
POLYMER SYSTEM	nr	+
		5
NEAT POLYMER FEED CAPACITY	GPH	•
NEAT POLYMER METERING PUMP TYPE	TYPE	PROGRESSIVE CAVITY
WATER USE	GPH	60-600
POWER	HP	1
FOG FEED TRANSFER PUMP		
NUMBER OF PUMPS	NO.	1
PUMP TYPE	TYPE	DOUBLE DISC
TDH	FT	39
DESIGN FLOW	GPM	60
SUCTION SIZE	INCH	4
DISCHARGE SIZE	INCH	4
POWER	HP	5
FOG RECIRCULATION PUMP		
NUMBER OF PUMPS	NO.	2
PUMP TYPE	TYPE	HORIZONTAL RECESSED IMPELLER
SUCTION SIZE	INCH	6
DISCHARGE SIZE	INCH	6
TH AT PRIMARY OPERATING POINT	FT	11
FLOW AT PRIMARY OPERATING POINT	GPM	600
TH AT SECONDARY OPERATING POINT	FT	14.5
FLOW AT SECONDARY OPERATING POINT	GPM	250
POWER	HP	10
SCREW CONVEYOR		
NUMBER	NO.	1
TYPE	TYPE	SHAFTLESS REVERSING SCREW CONVEYOR
CAPACITY	CFH	110
LENGTH	FT	16
DISCHARGE PORTS	-	3 POINT DISCHARGE WITH CHUTE EXTENSIONS AND 1 SLIDE GATE
POWER	HP	2
(1) TANK HEIGHT NOT INCLUSIVE OF DOME	HEIGHT. D	OME HEIGHT MAY VARY.

	DIGES*	TER MODIFICATIONS		
PARAMETER	UNIT	DESIGN		
TANKS				
NUMBER OF TANKS	NO.	1		
TANK DIAMETER	FT-IN	50'-0"		
TANK HEIGHT	FT-IN	25'-0"		
TANK VOLUME	GAL	49,090		
USABLE TANK VOLUME	GAL	46,410		
TANK MATERIAL	TYPE	CONCRETE		
BLOWERS				
MIXING CRITERIA	CFM/1000 CU FT	30		
NUMBER OF BLOWERS	NO.	2		
DUTY BLOWERS	NO.	1		
STAND BY BLOWERS	NO.	1		
TYPE	TYPE	TRI- LOBE POSITIVE DISPLACEMENT		
DESIGN CAPACITY	CFM	1,385		
DISCHARGE PRESSURE	PSI	11		
POWER	HP	125		
DIFFUSERS				
TYPE OF DIFFUSERS	TYPE	HYDRODYNAMIC MIXING NOZZLES (DUCK -BILL NOZZLES)		
FLOW RATE/DIFFUSER	CFM	10		

BAR SCREEN	REPLACEMENT	
PARAMETER	UNIT	DESIGN
MULTIRAKE BAR SCREEN		
DEPTH OF CHANNEL	FT-IN	13'-10"
INSIDE WIDTH OF CHANNEL	FT-IN	2'-9"
ANNUAL AVG PLANT FLOW	MGD	4
2 HR PEAK FLOW	GPM	8,333
MAX FLOW	MGD	12
BAR SPACING	ММ	6
POWER	HP	2
SCREEN INCLINE DEGREE	DEGREES	80



					DESIGNED BY:	D. HERNANDEZ
					DRAWN BY:	D. GURAV
_					SHEET CHK'D BY:	C. VARNON
\vdash					CROSS CHK'D BY:	A. WOELKE
⊢					APPROVED BY:	C. VARNON
REV. NO.	DATE	DRWN	CHKD	REMARKS	DATE:	APRIL 2024





CITY OF BRYAN, TEXAS


STILL CREEK WASTEWATER TREATMENT PLANT IMPROVEMENTS

DESIGN CRITERIA

PROJECT NO. 2381-284648
FILE NAME: GOO4DCFN.DWG
SHEET NO.
G-4







PAINTED STEEL

PAINTED STEEL

RIGID ALUMINUM

RIGID ALUMINUM

CAST ALUMINUM

CAST ALLIMINIUM

CITY OF BRYAN, TEXAS

STILL CREEK WASTEWATER TREATMENT

PLANT IMPROVEMENTS

NEMA 1/NEMA12

NEMA 1/NEMA12

HOT DIPPED GALVANIZED STEEL

HOT DIPPED GALVANIZED STEEL

GALVANIZED STEEL

CALVANIZED STEEL

GALVANIZE

GALVANIZED STEEL

AREA CLASSIFICATION AND

MATERIALS SCHEDULE

316 SST

316 SST

316 SST

316 SST

GALVANIZED STEEL

GALVANIZED STEEL

NEETE (COME, 2214, CEPOIST, CEPOIST, MINFOLISE, MINFOLISE, MINFOLISE) mages: []
Less med by Colonion Time 3/3/2021 331144 PM united to the colonion PM colonion PM

HEADWORKS AREA

POWER SURPLY

10

RAW WATER LIFT STATION DRY SIDE

E-BUILDING

NDOOR/DRY

INDOOR /DRY

SHEET CHK'D BY:

PPROVED BY:

CROSS CHK'D BY:___

UNCLASSIFIED

LINCLASSIFIED

CDM

Smith

9430 Research Blvd., Suite 1-200 Austin, TX 78759 Tol: (512) 346-1100

D. HERNANDEZ

D. GURAV

A. WOELKE

C. VARNON


APRIL 2024


C. VARNON


G-7 100% SUBMITTAL


ROJECT NO. 2381-2846


SHEET NO.












































E **GENERAL NOTES** GENERAL THESE GENERAL NOTES SHALL APPLY UNLESS OTHERWISE SPECIFICALLY NOTED ON PLANS AND DETAILS. CONCRETE NOTES SHOP DRAWING REVIEW AND SUBMITTAL NOTES ALL CONCRETE WORK SHALL CONFORM TO THE AMERICAN CONCRETE INSTITUTE (ACI) SPECIFICATION, ACI #301 & BUILDING CODE REQUIREMENTS, ACI #318, LATEST EXITION, FOR BUILDING STRUCTURES. 1. REFER TO PROJECT SPECIFICATIONS FOR SUBMITTAL REQUIREMENTS. CONSTRUCTION WORKMANSHIP, AND MATERIALS SHALL COMPLY WITH THE 2021 INTERNATIONAL BUILDING CODE (IBC). SHOP DRAWINGS AND SUBMITTALS WILL BE REVIEWED FOR THE LIMITED PURPOSE OF CHECKING FOR CONFORMANCE WITH INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN THE CONTRACT DOCUMENTS. 2. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND SHALL COORDINATE ALL STRUCTURAL PLANS AND DETAILS WITH ARCHITECTURAL, MECHANICAL, ELECTRICAL AND CIVIL DRAWINGS BEFORE STATING WORK, IN CASE OF DISCREPANCY, THE CONTRACTOR SHALL NOTIFY THE ENGINEER OF 2. ALL DETAILING, FABRICATION AND ERECTION OF REINFORCING BARS, UNLESS OTHERWISE NOTED, MUST FOLLOW THE ACT IMMANUAL OF STANDARD PRACTICE FOR DETAILING REINFORCED CONCRETE, ACHISTIS, LITEST EDITION. SUBMITTAL REVIEW WILL NOT BE CONDUCTED FOR THE PURPOSE OF UNLESS SHOWN OTHERWISE IN THE SPECIFICATIONS, CONCRETE SHALL BE CONCRETE WITH 4009 PSI MINIMUM COMPRESSIVE STRENGTH AT 22 DAYS, ALSO REFER TO SPECIFICATIONS FOR ADDITIONAL CONCRETE MIX DESIGN REQUIREMENTS. SUBMITTAL REVIEW WILL NOT BE CONDUCTED FOR THE PURPOSE OF DETERMINING THE ACCURACY AND COMPLETENESS OF OTHER DETALED INFORMATION SUCH AS DIMENSIONS AND QUANTITIES, OR FOR SUBSTANTIATING INSTRUCTIONS FOR INSTALLATION OR PERFORMANCE O EQUIPMENT OR SYSTEMS DESIGNED BY THE CONTRACTOR, ALL OF THIS SAME IN A TIMELY MANNER. 3. COMPLETE SHOP DRAWINGS FOR THE STRUCTURAL WORK SHALL BE SUBMITTED FOR REVIEW PRIOR TO COMMENCEMENT OF CONSTRUCTION IN ACCORDANCE WITH THE SPECIFICATION, REVIEW OF SHOP DRAWINGS BY THE ARCHITECTHENGINEER DOES NOT RELIEVE THE CONTRACTOR OF FULL RESPONSIBILITY FOR CORRECT FARRICATION AND CONSTRUCTION OF THE 4. REINFORCING BARS SHALL BE NEW BILLET STEEL CONFORMING TO ASTM A-615. REMAINS THE RESPONSIBILITY OF THE CONTRACTOR. REVIEW SHALL NOT CONSTITUTE APPROVAL OF SAFETY PRECAUTIONS OR OF ANY CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES OR PROCEDURES. STANDARD PROTECTIVE COVER OF REINFORCING BARS UNLESS OTHERWISE NOTED SHALL BE: THE STRUCTURAL DRAWINGS SHALL NOT BE SCALED FOR DETERMINATION OF QUANTITIES, LENGTHS, OR FIT OF MATERIALS. PRINCIPAL OPENINGS ARE SHOWN ON THE STRUCTURAL DRAWINGS, THE CONTRACTOR SHALL REFER TO ARCHITECTURAL. MECHANICAL. ELECTRICAL SHOP DRAWINGS AND/OR PRODUCT DATA FOR THE FOLLOWING ITEMS ARE
TO BE SUBMITTED TO THE STRUCTURAL ENGINEER FOR REVIEW AND APPROVAL: CONTRACTOR SHALL REFER TO ARCHITECTURAL, MECHANICAL, BLECTRICAL HAVA GAND PLUMBING DRAWNESS FOR SLEEVES, CURBS, INSERTS AND SIMILAR DETAILS NOT SHOWN, SUZE AND LOCATION OF ALL OPENINGS SHALL BE VERIFIED BY THE CONTROLOR. ANY DEVAITON FROM OPENINGS SHOWN ON THE STRUCTURAL DRAWNESS SHALL BE BROUGHT TO THE ARCHITECTIENGINEERS ANTENION PROOF TO CONSTRUCTION. 6 CONCRETE SHUMPS SHALL BE AS FOLLOWS: A REINFORCING STEEL B. STRUCTURAL STEEL C. METAL GRATING A. ALL ACCESSORES SHALL BE IN ACCORDANCE WITH THE ACT INVALID.

A. ALL ACCESSORES SHALL BE IN ACCORDANCE WITH THE ACT INVALID.

STANDARD PRACTICE FOR BETALING REINFORCED DONCRETE, ACLIFIST, LITEST
EDITION, ACCESSORES FOR INTERIOR CONCRETE SHAFFACE SPORSED TO VIEW SHALL
HAVE PLANTE DONCRETE FOR THE ACCESSORISES FOR CONCRETE SHAFFACE SPORSED TO

STEEL OR PLANTE, PROVIDE BIOLISTIC AT SUPPRIVED SHAFFACE
FINANCE STANDESS AT ALL SLASS WITH TWO LAVERS OF REINFORCIDE, FOR
BALLO-DIAGONE REPROCEDING, PROVIDE CHAPSIAMILY ACTURES PROVIDED FOR THE ACCESSORY

DAIL-DIAGONE REPROCEDING, PROVIDE CHAPSIAMILY ACTURES PROVIDED FOR THE DONCRETE BLOOG OF

CALL MILES STANDESS TIES. STANDESS TIES. PLASTIC, OF MICCAST CONCRETE BLOOG OF

COUNTY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY.

THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE ACCESSORY OF THE THE STRUCTURAL DRAWINGS AND SPECIFICATIONS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE METHODS OF CONSTRUCTION UNLESS SO STATEO OR NOTED. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY TO PROTECT THE WORKERS AND ALL OTHER PERSONS DURING CONSTRUCTION. SHOP DRAWINGS ARE TO BE DISTRIBUTED ONLY FROM RETURNED SUBMITIALS BEARING AN INITIALED REVIEW STAMP AND WORK ON THESE ITEMS SHALL NOT PROCEED UNLESS THE STAMP CLEARLY INDICATES THE DRAWINGS ARE "APPROVED" OR "APPROVED AS NOTED." 3. SHOP DRAWINGS AND/OR PRODUCT DATA FOR THE FOLLOWING ITEMS ARE SHOP DRAWINGS ANDOR PRODUCT DATA FOR THE FOLLOWING ITEMS ARE TO BE SUBMITTED TO THE STRUCTURE. BENDRESS FOR REVIEW. THE BENDRESS REVIEW WILL BE LIMITED TO COMPONANCE WITH DESIGN AND THE DESIGN AND THE STRUCTURE. THE STRUCTURE THE STRUCTURE THE STRUCTURE THE STRUCTURE THE STRUCTURE. THE STRUCTURE 7. THE CONTRACTOR SHALL PROVIDE TEMPORARY ERECTION BRACING AND SHORING OF ALL STRUCTURAL WORK AS REQUIRED FOR STABILITY OF THE BLANCH STABILITY OF THE CONTROL OF THE STRUCTURAL BRACING AND AND ADDITION WHICH, IN HIS OPHION, MIGHT ENDANGER THE STABILITY OF THE STRUCTURE OR CAUSE DISTRESS IN THE STRUCTURE. 8. MAINTAIN A MINIMUM OF ONE BAR DIAMETER (BUT NOT LESS THAN NOT) BETWEEN ALL CONTINUOUS REINFORCING BARS ON ALL SLABS. MAINTAIN A MINIMUM OF 1-12' BETWEEN BARS IN COLUMNS, AND A MINIMUM OF 1-12' TIMES THE MAYMUM COARSE AGGREGATE SIZE IN ALL CASES. CONSTRUCTION MATERIALS SHALL NOT BE STORED ON FLOORS OR ROOFS IN EXCESS OF THE DESIGN LIVE LOADS, IMPACT SHALL BE AVOIDED WHEN PLACING MATERIALS ON FLOORS OR ROOFS. BARS SCHEDULED AND DETAILED "CONT" SHALL BE LAPPED ACCORDING TO STANDARD TENSION LAP LENGTHS TABLE UNLESS OTHERWISE NOTED. THE SPLICES SHALL OCCUR AT MIDSPAN FOR TOP BARS AND OVER THE SUPPORTS FOR BOTTOM BARS. CONCRETE MIXES
PRE-ENGINEERED PRECAST CONCRETE COMPONENTS
PRE-MANUFACTURED METAL STAIRS DESIGN CRITERIA 10. ANY PROPOSED PENETRATIONS NOT MEETING ALL OF THE BELOW CRITERIA SHALL NOT BE ALLOWED WITHOUT THE WRITTEN APPROVAL OF THE STRUCTURAL ENGINEER: GRAVITY LOADS:
 STRUCTURE SELF-WEIGHT INCLUDED AS DEAD LOAD FOR ALL LOCATIONS. SIN O PENETRATIONS ARE TO BE LARGER THAN 7 (2.12 SLEVE) IN DIAMETER FOR BEANS LESS THAN 18" WIDE NO PENETRATIONS ARE TO BE LARGER THAN 4" OF ALEPVEIN IN 1997 OF A SHAPE TO SHAPE THAN 19" OF A SHAPE THAN 19" NO WORK ON STRUCTURAL ELEMENTS SUPPORTING OR RELATED TO THESE ITEMS IS TO PROCEED UNLESS THE REVIEW CLEARLY INDICATES REVIEWED. OR: "REVIEWED, SEE COMMENTS" BY THE STRUCTURAL ENGINEER." GRATING
ROOF LIVE LOADS
VOLUTE OPERATING WEIGHT 4. CONCRETE IS A PRE-INGINEERED MATERIAL DESIGNED BY THE SUPPLIER TO MEET THE STREAGTH AND PERFORMANCE CRITIERA SPECIFIED IN THE CONTRACT DOCUMENTS. CONCRETE MIX DESIGNS SHALL BE USED AND SHALL BE SUBMITTED TO THE INCEPACION TESTING LAS BY ALL PREVIOURL ITS DITAL AND ANALYS FOR RELIEVE AND PAPERVALL BY SUBMITTED TO THE INCEPACION TESTING LAS PROPRIAL SHALL BE SUBMITTED TO THE INCEPTION AND PARTICIAL SHALL BE SUBMITTED TO THE INCEPTION AND PARTICIAL SHALL BE SUBMITTED TO THE INCEPTION AND PARTICIAL SHALL BE SUBMITTED. THE STREAM CHECKNICK SHALL BE SUBMITTED. 2. WIND DESIGN DATA (BC AND ASCE 7-10): a) RISK CATEGORY b) BASIC WIND SPEED 3. SEISMIC DESIGN DATA a) DESIGN CRITERIA: RISK CATEGORY 11. SHOP DRAWINGS SHALL BE PREPARED FOR ALL REINFORGING STEEL AND SUBMITTED FOR REVIEW BY ENGINEER, ENGINEERING DRAWINGS SHALL NOT BE REPRODUCED AND USED AS SHOP DRAWINGS. MANY VARIABLES, INCLUDING MIX COMPONENTS AND ENVIRONMENTAL NAY OWNUSES, INCLUDING MIA COMPONENTS AND ENVIRONMENTAL CONDITIONS AFFECT THE QUALITY OF CONCRETE. THE CONTRACTOR IS RESPONSIBLE FOR CONTROLLING VARIABLES AND REQUESTING MIX MODIFICATIONS AND SHALL BE SOLELY RESPONSIBLE FOR THE QUALITY OF CONCRETE DELIVERED AND PLACED ON THE SITE. RISK CATEGORY...

IMPORTANCE FACTOR, Ie...

MAPPED SPECTRAL RESPONSE ACCELERATION

1) SHORT PERIODS, Sa. 0.086

2) PERIODS OF 1SEC, S1. 0.040 12. WELDING OF REINFORCING BARS SHALL NOT BE PERMITTED, UNLESS APPROVED BY PAGINFER 5. GENERAL CONTRACTOR SHALL PRE-CHECK ALL SHOP DRAWINGS BEFORE SUBMISSION TO THE ENGINEER FOR REVIEW. ALL SUBMITTAL MATERIALS MUST BEAR AN INTILACE DREVIEW STAMP OF THE GENERAL CONTRACTOR. SUBMITTALS WITHOUT THE REVIEW STAMP OF THE GENERAL CONTRACTOR WILL BE RETURNED WITHOUT REVIEW AND SHALL NOT BE CAUSE FOR CLAMS OF DURING PLACEMENT OF CONCRETE, USE TREMIE OR OTHER MEANS TO LIMIT FREE FALL OF CONCRETE TO 5-0*. SITE CLASS ...

DESIGN SPECTRAL RESPONSE ACCELERATION

1) SHORT PERIODS, SDS 0.070

2) PERIODS OF 1SEC, SD1 0.084 14. VERTICAL REINFORCING, DOWEL, AND LAPS ARE OFFSET IN DETAILS FOR CLARITY BARS SHOULD BE CONSIDERED TO BE IN THE SAME PLANE AT EXTERNAL FACE. SEBMIC DESIGN CATEGORY A

1) RESPONSE MODIFICATION COEFFICIENT, R


2) SEISMIC RESPONSE COEFFICIENT, Cs

3) DESIGN BASE SHEAR, V = CaW 0 CONCRETE SHALL MEET THE REQUIREMENTS FOR THE FOLLOWING CLASS OF CONCRETE DEFINED BY THE PROJECT SPECIFICATIONS (03300). 6. REFER TO PROJECT SPECIFICATIONS FOR SUBMITTAL REQUIREMENTS. GINERAL CONTRACTOR SHALL SCHEDULE SUBMITTALS SUFFICIENTLY IN ADVANCE OF THE DEAT REQUIRED OF ALLOW REASONABLE TIME FOR DELIVERY, PROJESSING AND REVIEW BY THE DESIGN TEAM, THIS SHALL S 16. CONCRETE PLACED BY PUMPING SHALL MEET THE FOLLOWING REQUIREMENTS: b) RESISTING SYSTEM = BRACED FRAME a) COARSE AGGREGATE (AGG) SHALL BE GRADED FROM A MAXIMUM OF 11/2*. 0) RESISTING SYSTEM = BRACED FRAME C) ANALYSIS PROCEDURE = EQUIVALENT LATERAL FORCE PROCEDURE d) IBC AND ASCE 7-10 USED FOR EARTHQUAKE LOADING e) LATERAL DESIGN CONTROLLED BY WIND b) MAXIMUM ALLOWABLE INCREASE IN CEMENT FACTOR SHALL BE 1/2 IS MANUMAN ALLOWABLE INVERSEE IN CIDENT FACTOR SHALL BE 12


MANUMAN WERE CORNITE RATE ONLY LOOPINGH TO REQUIREDING STATED IN THE PROJECT PRECIPICATION, IF MODE WORKHALTHY IS EQUIRED, AN ADMINISTRA WHE USED.

MANUMAN TO PROJECT PROJECT ONLY IN THE ADDRESS AT STATEMENT OF COMPANY AND THE ADMINISTRATION OF COMPANY 4. GROUND SNOW LOAD: 5 PSE SHORTER REVIEW PERIODS WILL ONLY BE HONORED WITH PRIOR WRITTEN CONSENT FROM THE ENGINEER. THESE ACCELERATED SERVICES, AND APPROPRIATE COMPENSATION, MUST BE NEGOTIATED WITH THE ENGINEER IN ADVANCE. TEN DAY REVIEW PERIODS CAN NOT BE HONORED WHEN LARGE QUANTITIES OF SHOP DRAWINGS ARE SUBMITTED AT ONE TIME. WHEN THIS HAPPENS, THE CONTRACTOR SHALL SUBMIT AN ITEMIZED LIST INDICATING PRIORITIES AND REASONABLE RETURN DATES. 17. NO HORIZONTAL JOINTS WILL BE PERMITTED IN SLABS OR BEAMS UNLESS SPECIFICALLY SHOWN ON DRAWINGS. CONTRACTOR MUST SUBMIT VARIANCE IN CONSTRUCTION JOINT LOCATIONS FOR REVIEW BY ENGINEER. 7. THE USE OF REPRODUCTIONS OF THESE CONTRACT DRAWINGS, INCLUDING THE USE OF ELECTROMIC PILES, BY ANY CONTRACTOR. IN LIEU OF THE METERS OF THE 18 LISE 3/4" CHAMEER ON ALL EXPOSED CONCRETE CORNERS CONSENT FROM THE ENGINEER WHEN USING ELECTRONIC FORMAT FOR SUBMITTALS, THE CONTRACTOR
 SHALL PROVIDE ONE PRINTED HARD COPY FOR ENGINEER REVIEW OR EXECUTE
 AN AGREEMENT FOR REIMBURSING THE ENGINEER FOR PRINTING COSTS FOR PROJECT NO. 2381-28464 CDM **HANKS** CITY OF BRYAN, TEXAS FILE NAME: DRAWN BY F. SOLIS **GENERAL NOTES** Smith SHEET NO. SHEET CHK'D BY:_ SHEET 1 OF 1 STILL CREEK WASTEWATER TREATMENT SZ-1 PPROVED BY:. PLANT IMPROVEMENTS REV. DATE DRWN CHKD REMARKS MARCH 2024 100% SUBMITTAL

24-041 RFB STILL CREEK WASTEWATER TREATMENT PLANT IMPROVEMENTS - Page 849 of 1053



24-041 RFB STILL CREEK WASTEWATER TREATMENT PLANT IMPROVEMENTS - Page 850 of 1053



 \mathbb{B}

 ∇

 ∇

FLANGE AS REQUIRED

SCHED CONN PLATES- REF 4/SZ-3

 $\overline{\mathbb{A}}$

AND ARE NOT


	BEAM-TO-COLUMN AND BEAM-TO-BEAM CONNECTION SCHEDUL	E
BEAM DEPTH	FRAMING PLATE	BOLTS PER LEG
W8 x W10 x	PL 1/4 x 4 x 5 1/2"	2 - 3/4°Ø
W12 x	PL 1/4 x 4 x 8 1/2*	3 - 3/4°Ø
W14 x	PL 3/8 x 4 x 8 1/2*	3 - 3/4"Ø
W16 x	PL 3/8 x 4 x 11 1/2"	4 - 3/4°Ø
W18 x	PL 3/8 x 4 x 1'-2 1/2"	5 - 3/4° Ø

Œ

V

TO GRATING

TO BEAM



 ∇

-1 1/2" Ø PIPE POSTS TYP

© POST & ALUMINUM BRACE BM BEYOND

EXPANSION JOINT OR SPLICE LOCATION

- 1 1/2" Ø PIPE RAILS-TYP

 \forall

TO BEAM

1 1/2" Ø PIPE POSTS TYP

EXTRUDED TOEPLATE

BEAM-TO-COLUMN AND BEAM-TO-BEAM CONNECTION SCHEDULE

GUARDRAIL NOTES:

1. SPACING OF POSTS FOR HORIZONTAL GUARDRAILS SHALL NOT EXCEED 5°-0'. SPACING OF STAIR GUARDRAILS SUPPORTS, POSTS OR BRACKETS, SHALL NOT EXCEED 4°-0'. RAILING SUPPORT SPACING SHALL NOT EXCEED DISTANCE REQUIRED TO RESIST DESIGN LOADS LISTED IN SPECIFICATION.

2. PROVIDE EXPANSION JOINT SPLICES IN RAILINGS AND TOE PLATES OVER EXPANSION JOINTS IN SUPPORT STRUCTURE. MAXIMUM SPACING OF EXPANSION JOINTS SHALL BE 20-0". REFERENCE SPECIFICATION 05520 FOR ADDITIONAL EJ INFO.

3. LOCATE SPLICES AND EXPANSION JOINTS IN RAILS AND TOE BOARDS WITHIN 8" OF POSTS OR OTHER RAILING SUPPORTS.

4. COAT ALL AREAS OF RAILINGS IN CONTACT WITH CONCRETE, GROUT, MASONRY, WOOD OR DISSIMILAR METALS WITH A PROTECTIVE COATING PER SPEC.

5. LOCATIONS OF HOLES THRU BEAMS REQUIRED FOR ANCHORING GUARDRAILS MUST BE COORDINATED WITH RAILING SYSTEM MFR.

6. OMIT GUARDRAIL RETURN AT LOCATIONS WHERE IT OBSTRUCTS WALKWAY PATH AT BOTTOM OF STAIR.

					DESIGNED BY: K. HANKS	١,
					DRAWN BY: F. SOLIS	ľ
					SHEET CHK'D BY: K. HANKS	ı
					CROSS CHK'D BY:	ı
					APPROVED BY:	ı
REV. NO.	DATE	DRWN	CHKD		DATE: MARCH 2024	ı
		l		TAPAT DI AUTHURPOUPUPUTE. Dans SEL al COS		L







CITY OF BRYAN, TEXAS STILL CREEK WASTEWATER TREATMENT PLANT IMPROVEMENTS


TYPICAL STRUCTURAL DETAILS SHEET 1 OF 2


PROJECT NO. 2381-284648 FILE NAME: SZ-3.DWG SHEET NO. SZ-3





24-041 RFB STILL CREEK WASTEWATER TREATMENT PLANT IMPROVEMENTS - Page 852 of 1053











The County of th


DESIGNED BY: D. HERNANDEZ
DRAWN BY: P. VEERA
SHEET CHIC'D BY: C. VARNON
CROSS CHIC'D BY: A. WOKLKE
APPROVED BY: C. VARNON
DATE: APRIL 2024
Tel-


s


CITY OF BRYAN, TEXAS


STILL CREEK WASTEWATER TREATMENT
PLANT IMPROVEMENTS


DIGESTER BUILDING GROUND AND LOWER LEVEL PLANS MODIFICATIONS PROJECT NO. 2381-284648
FILE NAME: MD04DILPL.DWG
SHEET NO.
MD-4
























⟨₿/

	ADJUSTABLE PIPE SUPPORT APPROX. DIMENSIONS IN INCHES						
PIPE SIZE	А	В	С	D MIN	D MAX		
2-1/2	2-1/2	1-1/2	9	8	11-1/2		
3	2-1/2	1-1/2	9	8-1/4	11-3/4		
3-/12	2-1/2	1-1/2	9	8-1/2	12		
4	3	2-1/2	9	10-1/4	14		
6	3	2-1/2	9	11-5/8	15-1/4		
8	3	2-1/2	9	13-5/8	16-1/2		
10	3	2-1/2	9	14-5/8	18-1/4		
12	3	2-1/2	9	15-5/8	19-3/4		
14	4	3	11	18-7/8	20-3/4		
16	4	3	11	19-7/8	22-1/4		
18	6	3-1/2	13-1/2	21-1/4	24		
20	6	3-1/2	13-1/2	23-1/4	25-1/2		
24	6	4	13-1/2	26-1/2	28-1/4		
30	6	4	13-1/2	29-5/8	31-1/2		
32	6	4	13-1/2	30-5/8	32-3/4		
36	6	4	13-1/2	32-5/8	34-3/4		

\D/

\c/



\F/

\E/

ELBOW		DIMENSIONS	IN INCHES	
'A' DIA	'B' DIA	'C' THICK	'D' SQ	'E' DIA
4	2	3/8	6	5/8
6	2-1/2	3/8	7	5/8
8	4	1/2	9	5/8
10	4	1/2	9	5/8
12	6	1/2	11	3/4
14	6	1/2	11	3/4
16	6	1/2	11	3/4
18	8	1/2	13-1/2	3/4
20	8	1/2	13-1/2	3/4
24	8	1/2	13-1/2	3/4
30	10	3/4	16	7/8
36	12	3/4	19	7/8
42	16	3/4	23-1/2	1
48	18	3/4	25	1-1/8

\G/

NOTES:

1. MATERIAL FINISH TO MATCH PIPE.

W

 ALL PIPE AND SUPPORT MATERIALS INCLUDING ALL FASTENERS SHALL BE MANUFACTURED 316SS.

NOIES


XREFs: [CDMS_2234, RE
Lost soved by: PALANIY
pw:\\cdmsmith-oz02-p

\$\frac{2}{2}\tilde{2}\til

 ∇

- UNDER VALVES, METERS OR OTHER SPECIAL APPURTENANCES, A FABRICATED SUPPORT PIECE MAY BE UTILIZED AS ACCEPTABLE TO ENGINEER.
- ALL PIPE AND SUPPORT MATERIALS INCLUDING ALL FASTENERS SHALL BE MANUFACTURED 316SS.









NOTES:

- MATERIALS OF CONSTRUCTION SHALL BE AS SPECIFIED IN THE AREA CLASSIFICATION AND MATERIALS SCHEDULE CLOSURY ON CHEET OF 15
- REFER TO GENERAL NOTES ON SHEET MZ-1 AND SECTION 400507 FOR SPECIAL PIPE SUPPORT REQUIREMENTS.



NOTES:

- SIZES OF FLEXIBLE HOSE AND QUICK DISCONNECT FITTINGS SHALL BE AS SHOWN ON DRAWINGS.
- PROVIDE TYPE 304 SST HOSE CLAMPS OVER FLEXIBLE HOSE TO SECURE TO HOSE BARB INSERT ON QUICK DISCONNECTS.
- 3. ALL QUICK DISCONNECT COUPLINGS SHALL BE HIGH FLOWED OUPLINGS (HFC), DOUBLE SHUT-OFF TYPE AS MANUFACTURED BY COLLER PRODUCTS, FAPILL, MIN. MATERIALS OF CONSTRUCTION SHALL BE COMPATIBLE WITH PROCESS FLUID AND APPLICATION PRESSURE, GUICK DISCONNECT COUPLINGS FOR INSTRUMENTS (JEE. TURBURDERS), CHLORINE ANALYZERS, ETC.) SHALL BE SINGLE SHUT-OFF TYPE.
- FLEXIBLE TUBING SHALL BE SUITABLE FOR APPLICATION PRESSURE AND BE COMPATIBLE WITH PROCESS FLUID.



ELBOW SUPPORT

DETAIL

FLUSHING COCK

DETAIL E



					DESIGNED BY:	D. HERNAN
					DRAWN BY:	K.
					SHEET CHK'D BY:	C. VAR
					CROSS CHK'D BY:	A. WOE
	_				APPROVED BY:	C. VAR
REV. NO.	DATE	DRWN	CHKD	REMARKS	DATE:	APRIL 2
7.01						



CITY OF BRYAN, TEXAS

STILL CREEK WASTEWATER TREATMENT PLANT IMPROVEMENTS

MECHANICAL DETAILS I

PROJECT NO. 2381–2846
FILE NAME: MZ-1.DI
SHEET NO.

MZ-1


 ∇

NOTES:

- WHERE SUBMERGED OR LOCATED ABOVE WATER, PIPE CLAMP, WASHER AND SHIELD SHALL BE TYPE 316 STAINLESS STEEL.
- WHEN USED WITH PVC OR FIBERGLASS PIPE, PROVIDE SST SHIELD AROUND PIPE AT CLAMP WITH LOOSE FIT. WRAP COPPER TUBES WITH 2" WIDE STRIP OF RUBBER FABRIC.
- REFER TO GENERAL NOTES ON SHEET MZ-1 AND SECTION 400507 FOR SPECIAL PIPE SUPPORT REQUIREMENTS.
- MATERIALS OF CONSTRUCTION SHALL BE AS SPECIFIED IN THE AREA CLASSIFICATION AND MATERIALS SCHEDULE SHOWN ON SHEET G-15.

PIPE CLAMP FOR INDIVIDUAL PIPES





PIPE CLAMP FOR INDIVIDUAL PIPES

DETAIL

\c/

PIPE DIA

'Δ'

5-15/16

6-15/16

8-5/16

10-9/16

9-1/8

6-1/4

WHERE SUBMERGED OR LOCATED ABOVE WATER, PIPE CLAMP, WASHER AND SHIELD SHALL BE TYPE 316 SST.

14-3/8 5-5/16 9/16 3/8 X 1-1/2 850

- WHEN USED WITH PVC OR FIBERGLASS PIPE PROVIDE SST SHIELD AROUND PIPE AT CLAMP, WITH LOOSE FIT. WRAP COPPER TUBES WITH 2" STRIP OF RUBBER FABRIC.
- 3. FOR FLANGED PIPING INCREASE 'B' DIMENSION AS REQUIRED.
 4. 'B' DIMENSION SHALL INCREASE AS SHOWN ON DRAWINGS.

\D/

2-1/2

DIMENSIONS IN INCHES

\E/

LOAD RATINI LBS*

300

'D' FLAT BAR SIZE

7/16 3/16 X 1-1/4

2-5/8 7/16 3/16 X 1-1/4 300

2-3/4 7/16 3/16 X 1-1/4 300

3 7/16 3/16 x 1-1/4 300


3-3/16 7/16 1/4 X 1-1/4 500

3-7/16 7/16 1/4 X 1-1/4 500 3-3/4 7/16 1/4 X 1-1/4 500

4 7/16 1/4 X 1-1/4 500

4-1/4 9/16 1/4 X 1-1/2 600 11-3/4 4-3/4 9/16 1/4 X 1-1/2 600 \F/

- REFER TO GENERAL NOTES ON SHEET MZ-1 AND SECTION 400507 FOR SPECIAL PIPE SUPPORT REQUIREMENTS.
- MATERIALS OF CONSTRUCTION SHALL BE AS SPECIFIED IN THE AREA CLASSIFICATION AND MATERIALS SCHEDULE SHOWN ON SHEET G-15.
- WITHIN TEMPORARY CONTAINMENT AREA, ADHESIVE CAPSULE ANCHORS TO BE BULTED INTO CONCRETE BLOCKS THAT REST ON TOP OF THE ANCHORS SHOULD BE INSTALLED TON STEPRIZE THE POLYUFEA CONTAINMENT LINER, DIMENSIONS OF CONCRETE BLOCK WILL VARY BASED ON PIPE DIA.



\G/

W

NOMINAL PIPE SIZE	30"	24"	18/16"	12"	10"	8"	6"
TYPE OF PIPE	SST						
SUPPORT MATERIAL THICKNESS (ALL)	0.375*	0.375"	0.375"	0.375"	0.375"	0.375"	0.375"
SUPPORT MATERIAL	SST						
DMIENSION (X)	1.50"	1.50	1.50"	1.50	1.50"	1.50"	1.50
DIMENSION (Y)	2.25	2.25"	2.25"	2.25"	2.25"	2.25"	2.25"
DIMENSION (W)	30.00*	24.00"	22.50"	18.50"	16.25	14.50"	11.25
DIMENSION (A)	8"	8"	8"	8"	8"	8"	8"
DIMENSION (B)	6"	6"	6"	6"	6"	6"	6"
DIMENSION (H)	3"	3"	3*	3"	3"	3"	3"
ANCHOR BOLT HOLE DIA	1"	1*	1"	1*	1"	1"	1*
ANCHOR BOLT SIZE	0.750*	0.750"	0.750"	0.750"	0.750"	0.750"	0.750"

CONTRACTOR TO VERIFY ELEVATIONS BEFORE PRODUCTION




⟨₿/


NOTES:

- FURNISH AND INSTALL THE ABOVE SIGN ABOVE ALL NEW NON-POTABLE AND PLANT WATER HOSE BIBB AND HYDRANT STATIONS WHETHER SHOWN ON DRAWINGS OR NOT. ATTACH THE SIGN TO THE STRUCTURE, GUARDHALL OR POST WITH STAINLESS STEEL HARDWARE AND MOUNTING BRACKET.
- FURNISH ONE SIGN AND RECEIVE APPROVAL FROM OWNER PRIOR TO ORDERING REMAINDER OF SIGNS.

NON-POTABLE WATER SIGN







				DESIGNED BY:	D. HERNANDI
				DRAWN BY:	K. DI
				SHEET CHK'D BY:	C. VARNO
				CROSS CHK'D BY:	A. WOELI
				APPROVED BY:	C. VARNO
REV. NO.	DATE	DRWN	CHKD	DATE:	APRIL 202



CITY OF BRYAN, TEXAS STILL CREEK WASTEWATER TREATMENT PLANT IMPROVEMENTS

MECHANICAL DETAILS II


PROJECT NO. 2381-2846 SHEET NO. MZ-2

100% SUBMITTAL - NOT FOR CONSTRUCTION


AND

Fs: [CDN t soved \\cdmsn \ze CDM

REVW_CHRIS] Imog INMNDN Time: 2/19, -pw.bentley.com;pw_e _ RIGHTS RESERVED. S: THESE DOCUMENT



₩	I B		V . V	1	E	F	<u>\$</u>	H/
SYMBOLS	DESCRIPTION	SYMBOLS	DESCRIPTION	SYMBOLS	DESCRIPTION	SYMBOLS	DESCRIPTION	
* • • • • • • • • • • • • • • • • • • •	MEDIUM VOLTAGE DRAWOUT TYPE POWER CIRCUIT	SPD	SURGE PROTECTION DEVICE		PILOT LIGHT, COLOR AS NOTED * R- RED G- GREEN	→ ^{LA}		
52−© ¥	BREAKER CS-CONTROL SWITCH	·*	VOLTMETER (WITH SWITCH IF 3-PHASE)		G-GREEN B-BLUE W-WHITE A-AMBER	sc	LIGHTNING ARRESTER/SURGE CAPACITOR	OSMEDAL MOTE
(E.O.) FRAME TRIP	LOW VOLTAGE CIRCUIT BREAKER, 3 POLE UNLESS OTHERWISE NOTED. LSIG IF NOTED		AMMETER (WITH SWITCH IF 3-PHASE)	— O _{PTT}	PILOT LIGHT, PUSH-TO-TEST TYPE, COLOR AS NOTED ABOVE.		GROUND ROD	GENERAL NOTE THIS IS A STANDARD LEG
(E.O.) FRAME TRIP	MCP IF NOTED ERMS IF NOTED		METER * WM-WATTMETER WHM-WATTHOUR METER WHDM-WATTHOUR DEMAND METER		TIME DELAY RELAY RANGE AS NOTED SET POINT AS NOTED		GROUND ROD WELL	SOME SYMBOLS MAY N APPEAR ON THE DRAWIN
,	COMBINATION MOTOR CIRCUIT PROTECTOR AND MAGNETIC MOTOR STARTER, FULL VOLTAGE NON-REVERSING UNLESS OTHERWISE NOTED:	-0-	WHOM- WATTHOUR DEMAND METER WHOR- WATTHOUR DEMAND RECORDER PF-POWER FACTOR METER RT- RUNNING TIME METER	(TD)—	SET POINT AS NOTED TDD-TIME DELAY AFTER DE-ENERGIZATION-OFF DELAY TDE-TIME DELAY AFTER ENERGIZATION-ON DELAY	30A	FUSE, AMPERE RATING AS NOTED	
±* or ₩	# FVR-FULL VOLTAGE REVERSING RVNR-REDUCED VOLTAGE NON-REVERSING 2S1W-TWO SPEED, DNG WINDING 2S2W-TWO SPEED, TWO WINDING		TRANSDUCER AX-CURRENT TRANSDUCER WX-WATT TRANSDUCER		NOTC-NORMALLY OPEN, TIMED CLOSING WHEN ENERGIZED	•JJV• OR HTR	HEATER	
ξ	2SZW-TWO SPEED, TWO WINDING		RELAY, NO. AS INDICATED 25-SYNCHRONISM CHECK RELAY 27-LINDER VOLTAGE RELAY		NCTO-NORMALLY CLOSED, TIMED OPENING WHEN ENERGIZE	·	INDUCTOR	
'/* or □¹	NON-FUSIBLE DISCONNECT SWITCH, 600 VOLT, 3 POLE	-#-	27-UNDER VOLTAGE RELAY 38-BEARIND PROTECTIVE DEVICE 40-LOSS OF EXCITATION RELAY 42-RUNNING CONTACTORPILOT RELAY 46-REVERSE PHASE IPHASE BALANCE/CURRENT RELAY 47-PHASE SEQUENCE VOLTAGE RELAY		NOTO-NORMALLY OPEN, TIMED OPENING WHEN DE-ENERGIZE			
1/	* AMPERE RATING NOTED IF OTHER THAN 3DA		48- REVERSE PHASE/PHASE BALANCE/CURRENT RELAY 47- PHASE SEQUENCE VOLTAGE RELAY 49- MACHINE OR TRANSFORMER THERMAL RELAY 50- INSTANTANEOUS OVERCURRENT RELAY	<u> </u>	NCTC-NORMALLY CLOSED, TIMED CLOSING WHEN DE-ENERG FIELD INSTRUMENT, TAG NO. OR LOOP # AS INDICATED *INDICATES INSTRUMENT TYPE DEFINED ON LOOP SHEETS	ZED (TG)	TACHOMETER GENERATOR	
* OR F	FUSIBLE DISCONNECT SWITCH, 800 VOLT, 3 POLE, AMPERE RATING AND FUSE SIZE AS NOTED: * AMPERE RATING NOTED IF OTHER THAN 30A * FUSE RATING		505-INSTANTANEOUS ORGENERY RELAY 506-INSTANTANEOUS GROUND 51-TIME OVER CURRENT RELAY 51G-TIME OVER CURRENT RELAY, GROUNDING RESISTOR TYPE	8	## - INDICATES LOOP NO.		CONTACT, NORMALLY OPEN (NO)	
부 —:			51N-TIME OVERCURRENT RELAY, RESIDUAL TYPE	r	LIQUID LEVEL (FLOAT) SWITCH	+ +-	CONTACT, NORMALLY CLOSED (NC)	
MIS OR I	MOTOR ISOLATION SWITCH, HORSEPOWER RATED		51V-11ME OVERCOMENT NELTY WITH VOLTAGE RESIDENT 10 NEGATIVE SEQUENCE VOLTAGE RELAY 22-TIME DELLAY RELAY 23-OVER PRESSURE RELAY 35-A DIRECTIONAL OVERCURRENT RELAY 35-AUTOMATIC SELECTIVE CONTROL OR TRANSFER RELAY		NORMALLY OPEN, CLOSES ON RISING LEVEL		OVERLOAD RELAY HEATER	
VFI XXXA	MEDIUM VOLTAGE VACUUM FAULT INTERRUPTER AND		83-AUTOMATIC SELECTIVE CONTROL OR TRANSFER RELAY 86-LOCKING-OUT RELAY 87-DIFFERENTIAL PROTECTIVE RELAY PL-SLIFEIX INDICATES "BLIS"	OR ⊗	NORMALLY CLOSED, OPENS ON RISING LEVEL NORMALLY OPEN, CLOSES ON DROPPING LEVEL	K	KEY INTERLOCK	-
\ xxxa	VACUUM FAULT INTERRUPTER AND LOAD BREAK SWITCH, AMPERE RATING AS NOTED.		88-AUTOMIN IS SELECTIVE CONTROL ON TRANSPER NELAY 88-LOCKING-OUT RELAY 88-DIFFERENTIAL PROTECTIVE RELAY 88-SUFFIX NDICATES "GENERATOR" GE-GROUD FAULT ST-SHUNT TRIP TO SELECTIVE TRANSPORMED TO SELECTIVE TRANSPORMED		NORMALLY CLOSED, OPENS ON DROPPING LEVEL	ТВ	TERMINAL OR TEST BLOCK	-
	DRAWOUT TYPE EQUIPMENT OR DEVICE		X-SUFFIX INDICATES "AUXILIARY" SPECIAL CAPACITOR		PRESSURE OR VACUUM SWITCH	RTD	RESISTANCE TEMPERATURE DETECTOR	_
	MEDIUM VOLTAGE CABLE TERMINATION	$-\leftarrow$	* SC-SURGE CAPACITOR PF-POWER FACTOR CORRECTION CAPACITOR INCLUDING INDUCTIVE LINK AS NEEDED		NORMALLY OPEN, CLOSES ON RISING PRESSURE NORMALLY CLOSED, OPENS ON RISING PRESSURE	VE	VIBRATION DETECTOR	_
⊸ ~	MEDIUM VOLTAGE AIR INTERRUPTER SWITCH		PUSH BUTTON, MOMENTARY CONTACT, SPRING RETURN, NORMALLY CLOSED	OR ⊗	NORMALLY OPEN, CLOSES ON DROPPING PRESSURE		VIRANTON DETECTOR	
	MEDIUM VOLTAGE FUSED AIR INTERRUPTER SWITCH		PUSH BUTTON, MOMENTARY CONTACT, SPRING RETURN, NORMALLY OPEN		NORMALLY CLOSED, OPENS ON DROPPING PRESSURE	DM	DAMPER MOTOR	
≪□ ≫	MEDIUM VOLTAGE FUSED MOTOR CONTROLLER	E-STOP	EMERGENCY STOP PUSH BUTTON WITH RED MUSHROOM HEAD OPERATOR (MAINTAINED CONTACT)		TEMPERATURE SWITCH OR THERMOSTAT	(ETM) OR [DIDDOD]	ELAPSED TIME METER	
△ 30KVA 480V- 120/208Y	TRANSFORMER, RATINGS AND CONNECTIONS AS NOTED. UNLESS OTHERWISE NOTED ON THE SINGLE LINE DIAGRAMS ALL DRY TYPE TRANSFORMERS SERVICING ADMINISTRATIVE AND LABORATORY SPACES SHALL HAVE A	*	STOP PUSH BUTTON WITH RED HEAD OPERATOR (MAINTAINED CONTACT) WITH LOCKABLE OPTION		NORMALLY OPEN, CLOSES ON RISING TEMPERATURE	(400)	MOTOR OPERATED VALVE	
	OULDS THE PROPERTY OF LOW THE SHOULD LIKE LANGUAGE AND ALL HAND FOR PROPERTY CHEEN AND CONTROL THE SHOULD LIKE LANGUAGE AND ALL HAND EAR AND CONTROL THE SHOULD LIKE THE THE TEAMS FORMERS SHALL HAVE A K-FACTOR OF 1.5, ALL OTHER DRY TYPE TRANSFORMERS SHALL HAVE A K-FACTOR OF 1.5, ALL OTHER DRY TYPE TRANSFORMERS SHALL HAVE A K-FACTOR OF 1.5, ALL OTHER DRY TYPE TRANSFORMERS SHALL HAVE A K-FACTOR OF 1.5, ALL OTHER DRY TYPE TRANSFORMERS SHALL HAVE A K-FACTOR OF THE TRANSFORMER SHALL HAVE A K-FACTOR OF THE		*: E-STOP *: STOP	OR ⊗	NORMALLY CLOSED, OPENS ON RISING TEMPERATURE NORMALLY OPEN, CLOSES ON DROPPING TEMPERATURE	•	PUSHBUTTON STATION, REFER TO ELECTRICAL SCHEMATIC FOR NUMBER OF DEVICES.	
*E _{A:5}	CURRENT TRANSFORMER: ** QUANTITY A= PRIMARY AMPERES	STOP START	START-STOP PUSH BUTTON CONTROL STATION (MOMENTARY CONTACT) "L" DENOTES LOCKOUT TYPE	2	NORMALLY CLOSED, OPENS ON DROPPING TEMPERATURE	J	JUNCTION BOX	
* PV-SV	POTENTIAL TRANSFORMER: * QUANTITY PV= PRIMARY VOLTAGE	START STOP			FLOW SWITCH (AIR, WATER, ETC.)		POWER JUNCTION BOX	
	SV= SECONDARY VOLTAGE	STOP START	START-STOP PUSH BUTTON CONTROL STATION, MAINTAINED CONTACT WITH LOCKOUT DEVICE ON STOP		NORMALLY OPEN, CLOSES ON INCREASED FLOW	J	4-20ma SIGNAL JUNCTION BOX	1
\bigcirc	GENERATOR, RATINGS AND CONNECTIONS AS NOTED	OFF ON	OFF/ON SELECTOR SWITCH	OR Ø	NORMALLY OPEN, CLOSES ON DROPPING FLOW NORMALLY CLOSED, OPENS ON INCREASED FLOW		CONTROL JUNCTION BOX	-
100A ATS-1 N S	TRANSFER SWITCH AUTOMATIC TRANSFER SWITCH (EG ATS-1) MANUAL TRANSFER SWITCH (EG MTS-1) "N" INDICATES NORMAL SOURCE		3 POSITION SELECTOR SWITCH, MAINTAINED CONTACT		NORMALLY CLOSED, OPENS ON DROPPING FLOW		PULL BOX	-
}	100A INDICATES STANDBY SOURCE 100A INDICATES CONTINUOUS CURRENT RATING	A B C*	O-OPEN X-CLOSED POSITION CONTACT CONTACT CONTACT O-OPEN TOP MIDDLE BOTTOM CONTACT CONTACT		POSITION (LIMIT) SWITCH NORMALLY OPEN	PB PB	PULL BOX TERMINATION CABINET	_
*	VARIABLE SPEED DRIVE CONTROLLER # D.C. = D.C. DRIVE CONTROLLER SCR= SILICON CONTROLLED RECTIFIER	(XOO)	B 0 0 0	OR ⊗	NORMALLY OPEN - HELD CLOSED	TC		-
	SCR* SILICON CONTROLLED RECTIFIER VFD= VARIABLE FREQUENCY DRIVE AFD= ADJUSTABLE FREQUENCY DRIVE		C 0 0 X ** NAMEPLATE (AUSC) HOA- HAND/OFF/AUTO HOR- HAND/OFF/AEMOTE		NORMALLY CLOSED - HELD OPEN		REMOTE DEVICES	
	VACUUM CONTACTOR	(00x)	HOR-HAND/OFF/REMOTE LOR-LOCAL/OFF/REMOTE RSL-RAISE/STOP/LOWER TOA-TEST/OFF/AUTO		TORQUE SWITCH NORMALLY CLOSED, OPENS ON HIGH TORQUE	5	MOV WITHOUT INTEGRATED DISCONNECT	
5KW OR E	UNIT HEATER - ELECTRIC HEATING COIL AND FAN		NOTE: 2 POSITION MULTI-CONTACT SWITCH FOLLOWS SAME CONVENTION	<u> </u>	CONDUCTORS OR CONDUITS CROSSING PATHS BUT NOT CONNECTED	5	MOV WITH INTEGRATED DISCONNECT	***
5KW OR U	UNIT HEATER - STEAM OR WATER HEATING COIL AND FAN		MOTOR STARTER COIL, NUMBER AS INDICATED			- F	INDICATES LIMITS OF EQUIPMENT OR WIRING ENCLOSURE	GEORGE B. LU GOODO
M)	MOTOR, NUMERAL INDICATES HORSEPOWER		CONTROL RELAY COIL, NUMBER AS INDICATED		CONDUCTORS ELECTRICALLY CONNECTED			OST IS SOME
		DRAWN BY:	CDM GAI Gupa & Associate CONSULTRIO EXAMENT	tes, Inc.	BRYAN STILL CREEK		ELECTRICAL LEGEND & SYMBOLS - I	PROJECT NO. 2381— FILE NAME: SHEET NO.
		CROSS CHK'D BY: G	LUKE 12400 Colt Road, Suite 400 13717 Norther Road Dalles, Texas 75244 10-1971 (2) 1240 Texas 75244	F-2993 WASTE	WATER TREATMENT PLANT			E-1
DATE DRWN CHKD	REMARKS				IMPROVEMENTS			



⟨₿/

 $\overline{\mathsf{A}}$

- THE NOTES CONTAINED ON THIS SHEET ARE PROVIDED FOR THE CONVENIENCE OF THE CONTRACTOR WHEN WORKING IN THE FIELD, AND CONTAIN EXCERPTS FROM THE SPECIFICATION SECTIONS. HOWEVER THE CONTRACT DO RIS HEREBY ADVISED THAT THE CONTRACT DO COMENTS CONSIST OF BOTH THE DRAWINGS AND THE SPECIFICATIONS. AND THAT THE CONTRACT DO RIVES TO RIVEY WITH BOTH THE BOUND DRAWINGS. AND THE BOUND SPECIFICATIONS
- ALL EQUIPMENT WIRING, RACEWAYS, ETC, SHALL BE INSTALLED AND GROUNDED IN ACCORDANCE WITH THE LATEST EDITION OF THE NATIONAL ELECTRICAL CODE, LOCAL CODES, AND INDUSTRY STANDARDS (IE. UL, NEMA, IEEE, ANS), ETC.) THE DRAWING NOTES AND DETAILS SHALL BE COMPLIED WITH IN ADDITION TO THE REQUIREMENTS IN THE SPECIFICATIONS, REFER TO EACH SPECIFICATION SECTION FOR SPECIFIC
- ALL RACEWAY INSTALLATIONS SHALL BE INSTALLED IN A MANNER TO PREVENT CONFLICTS WITH EQUIPMENT AND STRUCTURAL CONDITIONS. ALL EXPOSED RACEWAY SHALL BE INSTALLED AS PER ANSI NECA 1 PARALLEL TO BEAMS, CEILINGS, FLOORS AND WALLS. SEE SPECIFICATION ON RACEWAYS FOR ADDITIONAL REQUIREMENTS.
- CONDUITS SHALL BE TERMINATED IN A NEAT MANNER AND STRICTLY IN ACCORDANCE WITH THE SPECIFICATIONS
- CONDUITS TERMINATED INTO ENCLOSURES SHALL BE PERPENDICULAR TO THE WALLS OF THE ENCLOSURE. THE USE OF SHORT SEALTIGHT ELBOW FITTINGS FOR SUCH TERMINATIONS IS NOT PERMITTED.
- ALL RACEWAY INSTALLATIONS, CROSSING EXPANSION JOINTS OF TRANSITIONS FROM BELOW GRADE TO EXPOSED ABOVE GRADE, SMALL HAVE EXPANSION OR EXPANSIONDEFLECTION TYPE FITTINGS AS SPECIFIED FOR THE APPLICATION, SEE THE DRAWINGS AND THE SPECIFICATION ON RACEWAYS FOR THE EXACT TYPE OF
- NO CONDUIT SMALLER THAN 3/4", NOR WIRE SMALLER THAN NO. 12 AWG, SHALL BE USED UNLESS SPECIFICALLY
- ALL UNDERGROUND SINGLE CONDUITS AND DUCTBANKS OF MULTIPLE CONDUITS SHALL BE RIGID PVC CONDUIT ENCASED IN REINFORCED RED CONCRETE. CONCRETE BYED RED BEFORE PLACEMENT. MINIMUM SIZE IS 21 NON-FILED VERTIFY THE ROUTING OF ALL EXTITION UNDERGROUND CONDUIT AND DUCTBANKS. COYODINATE ROUTING OF NEW CONDUIT AND DUCTBANKS TO AVOID INTERFRENCE WITH EXISTING CONDUIT, DUCTBANKS, AND OTHER UNDERGROUND UTILITIES.
- ALL CHANGES OF DIRECTION GREATER THAN 20 DEGREES IN UNDERGROUND SINGLE, OR DUCTBANES OF MULTIPLE CONDUITS, SHALL BE ACCOMPLISHED SING PVC COATE DRICH ACIDINAL MORE PARTIES BENDS. BENDS OF PVC CONDUIT GREATER THAN 20 DEGREES, OR THE USE OF FLEXIBLE CONDUIT OF ANY TYPE, WILL NOT BE PERMITTED. SEE THE SPECIFICATIONS FOR MORE REQUIREMENTS.
- 10. LIQUID TIGHT FLEXIBLE ALUMINIM CONDUIT SHALL BE USED FOR THE PRIMARY AND SECONDARY OF TRANSFORMERS, GENERATOR IT REMINATIONS AND OTHER EQUIPMENT WHERE WIRENTON IS PRESENT. USE IN OTHER LOCATIONS IS NOT PERMITTED. EXCEPT FOR CONNECTIONS TO INSTRUMENTATION TRANSMITTERS, WHERE MULTILE PERMITTATIONS ARE REQUIRED. LIQUID THIGH TEASURE ALUMINUM, CONDUIT SHALL HAVE A MAXIMUM LENGTH NOT GREATER THAN THAT OF A FACTORY MANUFACTURED LONG RADIUS ELBOW OF THE CONDUIT SIZE BEING USED. THE MEMORY MENDING RADIUS SHALL NOT BE LESS THAN THAT SHOWN IN THE NEC CHAPTER 9, TABLE 2, "OTHER BENDS", BX OR A C TYPE PREFABRICATED CABLES MILL NOT BE PERMITTED.
- THE WIRING DIAGRAMS, BLOCK DIAGRAMS, QUANTITY/SIZES OF WIRES/CONDUITS REPRESENT A SUGGESTED APRAMORMENT BASED UPON SELECTED STANDARD COMPONENTS OF ELECTRICAL FOLUPMENT MODIFICATIONS ACCEPTABLE TO THE ENGINEER MAY BE MADE BY THE CONTRACTOR TO ACCOMMODATE GOUPMENT MODIFICATIONS ACCEPTABLE TO THE ENGINEER MAY BE MADE BY THE CONTRACTOR TO ACCOMMODATE GOUPMENT ACTIVITY APPROVED. ALL MODIFICATIONS SHALL BE SUBMITTED TO THE BUGINEER FOR APPROVIAL. THE BASIC SEQUENCE AND METHOD OF CONTROL MUST BE MANITAMED AS INDICATED ON THE BROWNINGS ANDOR SPECFIELD.
- 12. ALL JUNCTION BOXES, PULL BOXES AND TERMINATION BOXES IN NEMA 12 AREAS SHALL BE ALUMINUM, FOR NEMA 4X AREAS SEE SPECIFICATIONS FOR BOX DETAILS AND SPECIFICATIONS
- 13. SEAL ALL RACEWAYS ENTERING JUNCTION BOXES OR CONTROL PANELS CONTAINING ELECTRICAL OR INSTRUMENTATION FOURMENT WITH WATERTIGHT SEALANT, REFER TO THE SPECIFICATIONS FOR DETAILS.
- 14. ALL EQUIPMENT AND ELECTRICAL EQUIPMENT ENCLOSURE LOCATIONS, OR TERMINAL BOX LOCATIONS, ARE APPROXIMATE. THE EXACT LOCATIONS SHALL BE COORDINATED WITH AND APPROVED BY THE OWNER/ENGINEER, DURING CONSTRUCTION, AT NO ADDITIONAL COST TO THE OWNER.
- 15. ALL EQUIPMENT AND ELECTRICAL EQUIPMENT ENCLOSURES DIMENSIONS ARE APPROXIMATE. ALL EQUIPMENT AND ELECTRICAL EQUIPMENT ENCLOSURES OR TERMINAL BOX DIMENSIONS SHALL BE VERIFIED WITH THE EQUIPMENT SUPPLIER. ALLOW FOR LOCATION CHANGES AND INCLUDE IN THE CONTRACT PRICE. THE EXACT LOCATIONS OF ALL ELECTRICAL EQUIPMENT AND ROUTINS OF ALL CABLES AND CONDUITS SHALL BE COORDINATED WITH AND APPROVED BY THE OWNER/ENGINEER DURING CONSTRUCTION
- 16. CORING OF AN EXISTING STRUCTURE SHALL BE COORDINATED WITH AND APPROVED BY THE OWNER/ENGINEER. CORING THROUGH STRUCTURAL BEAMS IS STRICTLY PROHIBITED WITHOUT PRIOR WRITTEN APPROVAL FROM THE OWNER/ENGINEER.
- 17. THE LOCATION OF ALL ELECTRICAL EQUIPMENT AND ROUTING OF CABLES AND CONDUITS SHALL BE COORDINATED AND APPROVED BY THE OWNER
- 18. THE DUCTBANK ROUTING AS SHOWN ON THE DRAWING IS APPROXIMATE. FIELD VERIFY THE EXACT DUCTBANK ROUTING, CABLE LENGTH AND CONDUIT LENGT
- 19. PROVIDE CONDUIT SEALS FOR CONDUIT PENETRATIONS AS PER NEC AND NFPA820.
- 20. COORDINATE ALL WORK WITH THE OWNER.

21. LOCATE ALL UNDERGROUND UTILITIES BEFORE DIGGING. COORDINATE THE EFFORT WITH THE OWNER

707

- ALL SLOTTED CHANNEL, SLOTTED CHANNEL SUPPORT MATERIAL, WASHERS, SCREWS, NUTS, CONDUIT CLAMPS, ALL THREAD SPRING NUTS AND MISC, MOUNTING HARDWARE SHALL BE 316 STAINLESS STEEL.
- 23. LIGHTING FIXTURES SHALL BE MOUNTED ACCORDING TO THE MOUNTING HEIGHT GIVEN ON THE DRAWINGS. THE MOUNTING HEIGHT SHALL BE MEASURED FROM THE BOTTOM OF THE LIGHTING FIXTURE TO THE FINISHED
- 24. CONDUIT AND WIRE FOR THE HVAC EQUIPMENT AND MISCELLANEOUS DEVICES SHALL BE
- A 3/4" (MIN) RIGID ALUMINUM
- B. NO.14 XHHW CU. WIRE XHHW (MIN.).
- C. IN ACCORDANCE WITH ALL ELECTRICAL AND HVAC SPECIFICATIONS REQUIREMENTS.
- 25. INSTALL ALL CONDUITS AND WIRES SHOWN ON THE INTERFACE DIAGRAM SHALL BE INSTALLED BY THE CONTRACTOR. GROUPING OF CONDUIT AND WIRE MAY BE CHANGED, IF APPROVED BY THE ENGINEER AND OWNER
- 26. ALL CONDULETS SHALL BE FORM 7 AND SHALL HAVE 316 SS CLAMP COVERS WITH 316 SS CLAMPS AND SOREWS SCREW DOWN COVERS ARE UNACCEPTABLE. REFER TO THE SPECIFICATIONS FOR MORE INFORMATION
- ALL BARE COPPER GROUNDING CONDUCTORS SHALL BE TINNED, ALL GROUND RODS SHALL BE 9/4" BY 10" LONG.
 ALL EXPOSED COPPER GROUND CABLES SHALL BE GREEN INSULATED CONDUCTORS, PROVIDE XHHW
 INSULATIOS.
- 28. WHERE NOTES ON THE GRAWNIG INDICATE THAT THE CONTRACTOR SHALL FIELD ARREFY. THE INTENT IS FOR THE CONTRACTOR TO INVESTIGATE TO THE ECTION RECESSING TO PROPUDE THE WORK AND MATERIALS FROM TO BIDDING AND INCLUDE ALL COSTS IN THE BID PRICE. THE CONTRACT PRICE SHALL NOT BE INCREASED WHEN THE CONTRACTOR HAN SOT INVESTIGATED PER THE NOTES DIRECTIONS THAT BE DON'T THE CONTRACTOR HAN SOT INVESTIGATED PER THE NOTES DIRECTIONS THAT BE DON'T THE CONTRACTOR HAN SOT INVESTIGATED PER THE NOTES DIRECTIONS THAT BE DON'T THE CONTRACTOR HAN SOT INVESTIGATED PER ADMINISTRATION OF THE PROPERTY OF

TYPICAL ENCLOSURE TYPES BY AREA TYPE								
	BOXES & ENCLOSURES				≣S			
NON-HAZARDOUS AREAS	1	3R	4X	4X*	12	CONDUIT		
OUTDOOR; GENERAL AREAS		×	х			RIGID ALUMINUM		
OUTDOOR; CHEMICAL AREAS				х		SCHEDULE 80 PVC		
INDOOR; CHEMICAL ROOM				х		SCHEDULE 80 PVC		
INDOOR; CONDITIONED SPACE					х	RIGID ALUMINUM		
INDOOR; NON-CONDITIONED SHOP SPACE					Х	RIGID ALUMINUM		
INDOOR; NON-CONDITIONED PROCESS AREA			х			RIGID ALUMINUM		
INDOOR, ADMIN BUILDING	Х					EMT/RIGID ALUMINUM		
CLASS I, DIVISION 1	REFER TO NEC. NFPA-820, AND CONTRACT CONSTRUCTION SPECIFICATIONS							
CLASS I, DIVISION 2	REFER TO NEC, NFPA-820, AND CONTRACT CONSTRUCTION SPECIFICATIONS							

GENERAL NOTES:

- FOLIPMENT SLICH AS MOTOR CONTROL CENTER, SWITCHGEAR, VEDS, AND OTHER STAND ALLONE MOTOR STARTERS ARE AS
- NEMA 1 ENCLOSURES ARE TO BE NEMA 1 GASKETED
- . NEMA 4X* ENCLOSURES ARE TO BE NON-METALLIC (ie PVC) NEMA 4X
- CONDUIT INSIDE ADMIN BUILDING LOCATION IS TO BE EMT IF CONCEALED IN DRY WALL (AKA SHEET ROCK WALL): OTHERWISE
- USE OF NEMA 3R OR 4X IN OUTDOOR GENERAL AREAS IS A SHOWN ON DRAWINGS.

CONDUIT TYPE	LOCATION
RIGID GALVANIZED CONDUIT	NOT ACCEPTABLE FOR USE ON THIS PROJECT EXCEPT FOR THE UTILITY COMPANY'S CONDUCTORS. ALL UTILITY COMPANY'S DUCTS SHALL BE AS SPECIFIED BY UTILITY COMPANY.
PVC COATED ALUMINUM CONDUIT	ALL EMBEDDED CONDUIT BENDS, UNDERGROUND DUCTBANK OF MORE THAN 20 DEGREES, AND ALL CONDUIT STUB-UPS TO A MINIMUM OF 6" ABOVE FINISHED FLOOR OR GRADE AND IN CHLORINE AND CAUSTIC ROOMS.
LIQUID TIGHT FLEXIBLE ALUMINUM CONDUIT	RACEWAY CONNECTION TO VIBRATING EQUIPMENT ONLY, IN ALL AREAS LIMITED TO 36" UNLESS APPROVED BY OWNER AND ENGINEER.
RIGID NON-METALLIC, SCHEDULE 40 PVC CONDUIT	UNDERGROUND ENCASED IN RED DYE REINFORCED CONCRETE. (AS WHERE SPECIFIED)
RIGID NON-METALLIC, SCHEDULE 80 PVC CONDUIT	FOR USE IN CHLORINE AND CAUSTIC ROOMS, AND UNDERGROUND. ENCASED IN RED DYED REINFORCED CONCRETE. (AS WHERE SPECIFIED)
FLEXIBLE ALUMINUM CONDUIT	FIXTURE WHIP CONNECTION TO LIGHTING FIXTURES IN NEMA 12 AREAS (MAXIMUM 3-FT). BX OR AC TYPE PREFABRICATED CABLES ARE NOT PERMITTED.
ALUMINUM RIGID METAL CONDUIT	ALL ABOVE GRADE AREAS, EXCEPT FOR CONCRETE EMBEDDED AND THOSE AREAS ALREADY DESCRIBED IN THIS TABLE
ELECTRIC METALLIC TUBING (EMT) CONDUIT	FOR USE ONLY ON CONCEALED, ABOVE GROUND, INTERIOR ELECTRICAL WIRING IN AIR-CONDITIONED ADMINISTRATIVE BUILDINGS REMOTE TO THE PROCESS AREA, AND CLEARLY DEFINED AS SUCH ON THE DRAWINGS OR IN THE SPECIFICATIONS.

DEMOLITION NOTES

\F/

- COORDINATE THE DENOLITION OF ELECTRICAL CONDUIT. WIRE, EQUIPMENT AND DEMOES WITH THE GENERAL DENOLITION AND OFFENDE. THE GENERAL DENOLITION AND OFFENDE THE GENERAL NATURE AND SCOOL OF THE DEMOLITION WORK, EVERY ITEM TO BE DEMOLISHED MAY NOT BE SHOWN. FIELD VERIFY, AND INCLUDE ALL DEMOLITION WORK IN THE CONTRACT PRICE.
- 2. PROVIDE TEMPORARY WIRE AND CONDUIT FOR THE EQUIPMENT WHICH MAY BE AFFECTED BY THE DEMOLITION BUT TO REMAIN IN SERVICE.
- 3. RELOCATE AND RECONNECT POWER AND CONTROL RACEWAYS AND CONDUCTORS TO EQUIPMENT AFFECTED
- 4. ALL CONDUCTORS BEING DEMOLISHED SHALL BE DISCONNECTED AND REMOVED FROM THE LOAD TO THE SOURCE, SURFACE MOUNTED CONDUITS AND MOUNTING HARDWARE SHALL BE REMOVED. UNDERGROUND CONDUITS WHICH ARE NOT BEING REMOVED OR OTHERWISE NOT BEING MADE UNUSABLE SHALL BE CAPPED AND TAGGED AS SPARE, WITH INFORMATION CLEARLY INDICATING THE LOCATION OF THE OTHER END.
- 5. ALL SURFACES WHERE DEMOLISHED EQUIPMENT OR CONDUIT IS REMOVED SHALL BE CLEANED, PATCHED AND PAINTED TO MATCH THE SURROUNDING SURFACE.
- 6 CHECK THE FUNCTION OF EACH CONDUCTOR REFORE REMOVING OR DISCONNECTING
- 7. IF A CONDUCTOR WHICH HAS TO STAY IN SERVICE (NOT BEING DEMOLISHED) IS INSTALLED IN A COMMON CONDUIT WITH CONDUCTORS WHICH ARE BEING DEMOLISHED. THE CONTRACTOR SHALL REMOVE ALL CONDUCTORS FROM THE CONDUIT, FROVIDE NEW CONDUCTORS WHICH ARE REPLACEMENTS FOR THE CONDUCTORS THAT ARE TO REMAIN IN SERVICE AND RE-INSTALL. THE NEW CONDUCTORS AFTER THE CONDUCTORS ARE PULLED. MEGGER OR VFL TEST EACH CONDUCTORS, CONNECT DOTH EMOS OF THE NEW CONDUCTORS AND TEST THE SYSTEM FOR PROPER FUNCTION DO NOT RE-PULL USED CONDUCTORS UNLESS
- WHERE EQUIPMENT IS BEING RE-FED FROM A NEW SOURCE, EXISTING CONDUIT MAY BE REUSED ONLY IF THE CONDUIT AND BITTINGS ARE OF THE TYPES SPECIFIED FOR NEW WORK ON THIS CONTRACT, IF NOT, A CONDUIT AND CONDUCTORS SHALL BE REPLACED WITH NEW MATERIAL MEETING THE SPECIFICATIONS, AT NO ADDITIONAL COST TO THE OWNER.
- THE CONTRACTOR SHALL COORDINATE WITH THE OWNER/ENGINEER TO FLAG EXISTING UNDERGROUND
- THE OWNER HAS THE RIGHT OF FIRST REFUSAL TO THE EQUIPMENT BEING REMOVED. THE CONTRACTOR SHALL DELIVER THE EQUIPMENT WHICH THE OWNER WISHES TO KEEP AT A LOCATION DESIGNATED BY THE OWNER OF SEPEPCHICATIONS.
- 11. DO NOT MAKE ANY MODIFICATIONS TO THE EXISTING ELECTRICAL EQUIPMENT UNTIL THE FOLLOWING HAS BEEN DONE:
 - A. THE OWNER/CONTRACTOR SHALL WITNESS AND RECORD THE CONDITION OF THE EXISTING EQUIPMENT, THE CONTRACTOR SHALL NOTE DOWN ANY DEFECTS OR DEFICIENCIES.
- B. THE OWNER SHALL OPERATE THE EQUIPMENT TO DEMONSTRATE THE CURRENT CONDITIONS. THE CONTRACTOR SHALL NOTE DOWN ANY DEFECTS OR DEFICIENCIES.
- C. A WRITTEN AND PHOTOGRAPHIC RECORD OF THE OPERATION AND EXISTING CONDITION SHALL BE KEPT IN A THREE RING BINDER AT THE OWNER/CONTRACTOR TRAILER, IN FORM OF PICTURES AND INFORMATION.
- D. A FORM SHALL BE GENERATED BY THE CONTRACTOR TO RECORD THE OBSERVATIONS. BOTH PARTIES SHALL SIGN ON THE FORM.
- E. REPLACE ALL MATERIAL OR EQUIPMENT DAMAGED DURING THE COURSE OF WORK.
- F. AFTER THE CHANGES ARE MADE, THE EQUIPMENT SHALL BE INSPECTED AND RE-TESTED TO DEMONSTRATE THAT IT FUNCTIONS CORRECTLY.
- G. NO PORTION OF EXISTING CONDUCTORS SHALL BE SPLICED TO NEW CONDUCTORS FOR RE-USE WITHOUT SPECIFIC APPROVAL FROM THE OWNER/ENGINEER ON A CASE-BY-CASE BASIS.

MCC, CONTROL PANELS, PANELBOARDS

THESE NOTES APPLY TO CONTROL PANELS, MCC ETC WHICH HAS TO BE REFURBISHED, MODIFIED, DISCONNECTED & RECONNECTED OR REWORKED.

- THE CONTRACTOR SHALL NOT MAKE ANY MODIFICATION UNTIL THE FOLLOWING HAS BEEN DONE
- A. THE OWNER/CONTRACTOR SHALL WITNESS THE CONDITION OF THE EXISTING EQUIPMENT. THE CONTRACTOR SHALL NOTE DOWN ANY DEFECTS OR DEFICIENCY
- B. THE OWNER SHALL OPERATE THE EQUIPMENT TO DEMONSTRATE THE CURRENT CONDITIONS. THE CONTRACTOR SHALL NOTE DOWN ANY DEFECTS OR DEFICIENCIES.
- C. A RECORD OF THE OPERATION AND EXISTING CONDITION SHALL BE KEPT IN A THREE RING BINDER AT THE OWNER/CONTRACTOR TRAILER. IN FORM OF PICTURES AND INFORMATION.
- D. A FORM SHALL BE GENERATED BY THE CONTRACTOR TO RECORD THE OBSERVATIONS. BOTH PARTIES SHALL SIGN ON THE FORM.
- E. REPLACE ALL MATERIAL OR EQUIPMENT DAMAGED DURING THE COURSE OF WORK.
- F. AFTER THE CHANGES ARE MADE, THE EQUIPMENT SHALL BE INSPECTED AND RE-TESTED TO DEMONSTRATE THAT IT FUNCTIONS CORRECTLY



ROJECT NO. 2381-284648 SHFFT NO

\HZ

E-3

*


100% SUBMITTALL


					DESIGNED BY:	J.FELGE
					DRAWN BY:	J,MEAI
					SHEET CHK'D BY:	G.LUKI
					CROSS CHK'D BY:	G.LUKI
_	_	_	_		APPROVED BY:	G.LUKE
٧.	DATE	DRWN	CHKD	RFMARKS	DATE:	APRII 2024





GAI Gupta & Associat CONSULTING ENGINE


BRYAN STILL CREEK WASTEWATER TREATMENT PLANT **IMPROVEMENTS**















































 $\overline{\mathbb{A}}$ B VD/ \F/

GENERAL NOTES:

FIELD VERIFY EXISTING EQUIPMENT LAYOUT AND LOCATIONS.

- REFER TO LP-C LIGHTHING PANEL SCHEDULE FOR PANEL SCHEDULE.
- 2. UTILIZE SPARE BREAKER IN PANELBOARD.



A MCC-B PHOTOGRAPH A ED-3

PANEL	BOARD:	LP-B			BUS TYPE: TIN PLATTED COPPER		MAINS: XXA	SPD: TYPE 2				
SERVI	CE: 208Y	//120V,	3Ø, 4W		BUS RATING: 100A	US RATING: 100A LOCATION: INSIDE MCC B						
MOUN	TING: SL	JRFACI	E - NEMA	. 12	FEED: TOP		1					
CKT NO.	BRKR SIZE	WIRE SIZE	COND. SIZE	LOAD			LOAD	COND. SIZE	WIRE SIZE	BRKR SIZE	CK' NO	
1	15/1	12	3/4"	SLUDGE TANK LEVEL (2	\rangle	SPARE		-	-	15/1	2	
3	15/1	-		SPARE		SPARE		-		15/1	4	
5	20/1	-	-	RECEPTACLES		RECEPTACLE	:S	-	-	20/1	6	
7	20/1	-		DIGESTER LIGHTS		DIGESTER LIC	SHTS	-	-	15/1	8	
9	20/1	-	-	DIGESTER LIGHTS		CHLORINATO	R BUILDING	-	-	15/1	10	
11	20/1			DIGESTER RECEPTACLES		-		-	-	70/1	12	
13	15/1	-	-	RECEPTACLES		FLOOD LIGHT	'S	-	-	15/1	14	
15	15/1			FLOOD LIGHTS		FLOOD LIGHT	"S	-	-	15/1	16	
17	15/2	-	-	SUMP PUMP		VENT FAN		-	-	15/1	18	
19	-	-				EXHAUST FAI	N	-	-	15/1	20	
21	15/1	-	-	GAS BURN IGNITION		BOILDER CON	NTROL PANEL	-	-	30/1	22	
23	15/1		-	FLOAT TRANSMITTER		DRIP TRAP HI	EATER	-		15/1	24	

- CONDUIT SIZE SHOWN IS THE MINIMUM SIZE REQUIRED FOR INDIVIDUAL CIRCUITS. MULTIPLE CIRCUITS MAY BE COMBINED IN A SINGLE CONDUIT FOR FIELD ROUTING PROVIDED NEC MAXIMUM CONDUIT FILL IS NOT EXCEEDED.
- EACH SINGLE PHASE 120V CIRCUIT SHALL HAVE A SEPARATE NEUTRAL WIRE.

Y:	J.FELGER	
	J.MEAM	W
D BY:	G.LUKE	9.5
D BY:		_
3Y:	G.LUKE	1240 Dalta
	APRIL 2024	Tot: (

GAI Gupta & Associates, Inc. CONSULTING ENGINEERING Texas Registration No. F-2593 13/17 Northun Road Dallas, Texas 73294 Tet: 972-400-7661 Faz: 972-400-7125


WASTEWATER TREATMENT PLANT **IMPROVEMENTS**


ELECTRICAL DIGESTER DETAILS PROJECT NO. 2381-284648 FILE NAME: ED-7.DW ED-7


100% SUBMITTALL

					DESIGNED BY:	J.FELGER
					DRAWN BY:	J,MEAM
_					SHEET CHK'D BY:	G.LUKE
_					CROSS CHK'D BY:	G.LUKE
BD/	_	_	_		APPROVED BY:	G.LUKE
REV. NO.	DATE	DRWN	CHKD	REMARKS	DATE:	APRIL 2024

BRYAN STILL CREEK







2		_				
: I					DESIGNED BY:	J.FELGER
5					DRAWN BY:	J.MEAM
₹					SHEET CHK'D BY:	G.LUKE
					CROSS CHK'D BY:	G.LUKE
					APPROVED BY:	G.LUKE
3	REV. NO.	DATE	DRWN	CHKD	 DATE:	APRIL 2024
: 1						





GAI


BRYAN STILL CREEK WASTEWATER TREATMENT PLANT **IMPROVEMENTS**


ELECTRICAL **GREASE AREA PHOTOS** AND DEMOLITION RISER


EG-2











SCREENING FACILITY DEMOLITION PHOTO 1

PHOTOGRAPH A

\B/

VA/



VD/

\c/



\F/

FIELD VERIFY AND INVESTIGATE ALL CONDUIT AND CONDUCTOR ROUTING.

\H/

- THE METAL RACK SHALL REMAIN UNMOVED AND UNHARMED.
- DEMOLISH CONTROL PANEL AND ALL ASSOCIATE WIRE AND EXPOSED CONDUIT FROM SOURCE TO LOAD. PREPARE CONCEALED CONDUIT FOR REUSE.
- CONVEYOR PRESS CONTROL PANEL SHALL STAY AS IS.
- RELOCATED RECEPTACLE AS REQUIRED FOR NEW PANEL LOCATION SHOWN ON EH-3.

SCREENING FACILITY DEMOLITION PHOTO 2 PHOTOGRAPH B













SCREENING FACILITY DEMOLITION PHOTO 4 PHOTOGRAPH F



SNS					PUMP STATION BUILDING NO.1 INTERNAL PHOTO		
AND DESIGNS					PHOTOGRAPH D		
RIGHTS RESERVED. THESE DOCUMENTS AND					EH-1		
RESERV Docu							
IGHTS	l						
SMITH ALL R DOCUMENTS:						DESIGNED BY:	J.FELGE
풀종	_					DRAWN BY:	J,MEA
₫8	⊢					SHEET CHK'D BY:	G.LUK
ã, b	\vdash					CROSS CHK'D BY:	G.LUK
8114	BD/	_	_	_		APPROVED BY:	G.LUK
88	NO.	DATE	DRWN	CHKD	REMARKS TIMENT PLANT [IMPROVEMENTS - Page 856 87 1055]	DATE:	APRIL 202
24 041 R	BSTILL	REEK W	ASTEWAT	ER TREA	TMENT PLANT IMPROVEMENTS - Page 898 of 1053	•	

LGER	ABM
MEAM	CPM
LUKE	Smith
LUKE	
LUKE	12400 Colt Road, Suite 400 Dallas, TX 75251
2024	Tel: (214) 346-2800 TBPE Firm Registration No. F-304:


GAI
Gupta & Associates, Inc.
CONSULTING ENGINEERING
Texas Registration No. F-2593
13717 Neutron Road
Dillos, Texas 75244
Tel: 972-490-7661
Fax: 972-490-7125
email: vigageta@guiconswiting.com


BRYAN STILL CREEK


WASTEWATER TREATMENT PLANT **IMPROVEMENTS**


ELECTRICAL SCREENING FACILITY DEMOLITION PHOTOS


PROJECT NO. 2381-284648 FILE NAME: EH-2.DV EH-2














	LIGHTING FIXTURE SCHEDULE											
TYPE	DESCRIPTION	MANUFACTURER/CATALOG NO.	INPUT WATTS	LAMP TYPE	MOUNTING							
A	6' LED SUSPENDED FIXTURE WITH DIFFUSERS OVER LEDS, PROVIDE ON BOARD DRIVER FOR 5000 LUMEN OUTPUT (120V).	FIXTURE: LITHONIA CLX-L96-10000-MDD- MVOLT-40K-80CRI	71	LEDS INCLUDED	PENDANT MOUNT FLUSH WITH CABLE TRAY							
AE	SAME AS TYPE "A" EXCEPT INCLUDES EMERGENCY BATTERY PACK (120V).	FIXTURE: LITHONIA CLX-L96-10000-MDD- 120/277-40K-80CRI-BSL722	71	LEDS INCLUDED	PENDANT MOUNT FLUSH WITH CABLE TRAY							
В	WALL MOUNTED LUMINAIRE WITH 10 LEDS AND 530mA DRIVER, PROVIDE OPTIC WITH FORWARD THROW AND PHOTOCELL (120V).	FIXTURE: LITHONIA DSXW1 LED 10C 530 40K T3M 120 PE DBLBXD	19	LEDS INCLUDED	WALL MOUNT AT 9'-0" AFF							
BE	SAME AS TYPE "B" EXCEPT INCLUDE AN EMERGENCY BATTERY PACK (120V) PROVIDE SEPARATE PHOTOCELL FOR TYPE "BE"	FIXTURE: LITHONIA DSXW1 LED 10C 530 40K T3M 120 PE E20WC DBLBXD	19	LEDS INCLUDED	WALL MOUNT AT 9'-0" AFF							
F	STANCHION MOUNT LED HIXTURE WITH AN ADJUSTABLE SUPFITTER 30 DEGREES FROM 0 DEGREE MOUNTED ON A TELESCOPIC POLE. PROVIDE POLE AND ALL NECESSARY ACCESSORES FOR A COMPLETE INSTALLATION, THE LIGHT FIXTURE IS PROFATED,	FIXTURE: LITHONIA DSXF1 LED P1 40K WFR MVOLT IS DBLBXD POLE: COURSE-HINDS V65-H-A-T57-SA	21	LEDS INCLUDED	POLE MOUNT 10'-0" ABOVE THE WALKWAY							
F1	SAME AS TYPE "F" EXCEPT POLE MOUNTED ON BASE PLATE.	FIXTURE: LITHONIA DSXF1 LED P1 40K WFR MVOLT IS PE DBLBXD POLE: COURSE-HINDS V65-H-A-T57-SA	21	LEDS INCLUDED	POLE MOUNT 10'-0" ABOVE THE WALKWAY							
н	LED WALL PACK INCLUDING A BOROCILICATE GLASS WITH 1000MA DRIVER, LED ENGINE AND DRIVER (120V) AND WIRE GUARD, (120V)	FIXTURE: LITHONIA TWH LED 20C 1000 40K T3M MVOLT WG DNAXD	39	LEDS INCLUDED	SURFACE MOUNT AT 8' AFF							
×	LED EXIT LIGHT WITH RED LETTERS, SINGLE FACE AND NICKLE-CADIMUM BATTERY BACK-UP (120V)	FIXTURE: KENALL METDU-MW-R-DT-EL	5	LEDS INCLUDED	WALL MOUNT AT 6" ABOVE DOOR							

					DESIGNED BY:	J.FELGER
_					DRAWN BY:	J,MEAM
⊢					SHEET CHK'D BY:	G.LUKE
⊢					CROSS CHK'D BY:	G.LUKE
201	-	_	_		APPROVED BY:	G.LUKE
REV. NO.	DATE	DRWN	CHKD	REMARKS	DATE:	APRIL 2024




GAI Gupta & Associates, Inc. GOSULTHG ENGINEERING Texas Rogistration No. F-2893 13173 Notion Board Delles, Texas 75294 Tel. 973-646-560 Feb. 12-90-6-766-760 could hoppingsaksoneithing con-

BRYAN STILL CREEK
WASTEWATER TREATMENT PLANT
IMPROVEMENTS


ELECTRICAL STANDARD DETAILS - IV 60900 01STE 05/06/24 PROJECT NO. 2381–284648 FILE NAME: EZ-4.DWG


SHEET NO.





	*	B	<u> </u>		▼ .	E	<u> </u>		<u>©</u>		₩
	PRIMARY FLOW ELEMENTS		VALVES	PUMPS	, BLOWERS AND MISC EQUIPMENT	CONTROL E	INCLOSURE, INSTRUMENTS AND SCADA	CONT	ROL ENCLOSURE, INSTRUMENT	S AND SCADA	
	MAGNETIC FLOW METER		SOLENOID ACTUATED VALVE		MIXER/FLOCCULATOR/AERATOR		DIGITAL/ANALOG INSTRUMENT AAA ISA TAG (REFER TO TABLE) BBB LOOP NUMBER		TU LOGIC FION SYMBOLS AND ABBREVIAT	IONS	
<u> </u>	ULTRASONIC DOPPLER FLOW METER		"X" P AIR CYLINDER O OIL CYLINDER	A			D DIVISION NUMBER (BOTTOM LEFT OR RIGHT)	-	SUMMING	NUATE (INPUT:OUTPUT) I OR ATTENUATE (INPUT:OUTPUT	0
	ULTRASONIC TIME TRANSIT FLOW METER VORTEX FLOW METER		H HYDRAULIC CYLINDER E ELECTRIC MOTOR S SOLENOID VALVE		VERTICAL PUMP-1	P AAA YY	P POWER REQUIREMENT XXX DESCRIPTION (USED ON PANEL INSTRUMENTS)	<u> </u>	AVERAGING SUBTRACTING EXTRACT SQUARE ROOT		
	VENTURI TUBE	Т		╢	USED WHEN DISCHARGE LINE IS IN WETWELL	BBB CCC D	YY CHEMICAL ZZZ LOCATION DIGITAL/ANALOG INSTRUMENT	F(X) + X	DIVIDE MULTIPLY INTEGRATE		
	TURBINE OR PROPELLER TYPE METER	OR NO SYMBOL	MANUAL VALVE MISC PROCESS SYMBOLS				-LOCATED IN THE FIELD -NOT INSIDE OF PANEL	+	BIAS POSITIVE BIAS NEGATIVE NONLINEAR OR UNSPECIFIED F	LINCTION	
— <u>Ш</u>	ROTAMETER	1	ANNULAR TYPE SEAL	1 A			-VISIBLE AT FIELD LOCATION -NORMALLY OPERATOR ACCESSIBLE DIGITALIANALOG INSTRUMENT -LOCATED ON PANEL		HIGH SELECT LOW SELECT HIGH LIMIT	ONCTION	
 - Q -	PITOT TUBE	<u> </u>	CHEMICAL INJECTION POINT		VERTICAL PUMP-2 USED WHEN DISCHARGE	P AAA YY BBB CCC D	-VISIBLE TO OPERATOR -NORMALLY OPERATOR ACCESSIBLE		LOW LIMIT INSTRUMENT	INSTRUMENT	
	WEIR FLOW METER	\forall \fora	WYE STRAINER		LINE IS EXPOSED.	ZZZ	DIGITAL/ANALOG INSTRUMENT	(COMMON HOUSING)	(SEPERATOR HOUSING)	(PART OF MAJOR EQUIPMEN	<u>r)</u>
*	PARSHALL FLUME OR TRAPEZOIDAL FLUME	Ψ	DRAIN	<u> </u>		P AAA YY BBB CCC D	-LOCATED INSIDE PANEL -NOT VISIBLE TO OPERATOR -NORMALLY NOT ACCESSIBLE		00	$ \infty \rangle$	
⊣ I⊢	ORIFICE PLATE		NORMAL OPERATING LEVEL	-₩ <u></u> -	USSTEAL SUMS OF THE	ZZZ D					
Ů	THERMAL MASS FLOWMETER		UV CHAMBER	∐ [[VERTICAL PUMP SHAFT USED WHEN INTAKE OF PUMP IS ENCASED.		DISPLAY (INDICATION/CONTROLLER) AAA ISA TAG (REFER TO TABLE)	GENERAL NOTE	_		
	PRIMARY LEVEL ELEMENTS ULTRASONIC LEVEL TRANSDUCER		FLOW STRAIGHTENER	∥ "		XXX	BBB LOOP NUMBER CCC LOOP NUMBER SUB XXX DESCRIPTION	MAY NOT A	PPLY TO THIS SPECIFIC PROJE		
<u>₹</u>	RADAR LEVEL TRANSDUCER	Δ	LOAD CELL		SUBMERSIBLE MIXER	BBB	DISPLAY (INDICATION/CONTROLLER) -LOCATED IN THE FIELD -NOT INSIDE OF PANEL	DIFFER FRO	OM LEGENDS FOR OTHER SHEE		
_	PRIMARY ELEMENT PRESSURE PROBE LEVEL TRANSMITTER	<i>─</i> / <u>~</u>	SPRAY NOZZLE	∥ ᠘			-NOT INSIDE OF PANEL -VISIBLE AT FIELD LOCATION -NORMALLY OPERATOR ACCESSIBLE	FOR PRACT	L THIS LEGEND SHEET AND THE DON INTERNATIONAL SOCIETY OF TICES FOR INSTRUMENTATION, IONS, ADDITIONS AND ALTERAT	INSTRUMENTATION DIAGRAMS DF AUTOMATION, STANDARDS STANDARD S5.1 SOME IONS HAVE REEN MADE AS	
	BUBBLER LEVEL TUBE ELEMENT		BLIND FLANGE FLANGE	→ →		XXX	DISPLAY (INDICATION/CONTROLLER) -LOCATED ON PANEL	REQUIRED 4 SOME PRO	TO ACCOMMODATE THE PROJE CESS ITEMS. SUCH AS FOURPME	CT REQUIREMENTS.	
`` .	CONDUCTIVE LEVEL PROBE	- - 	FLANGE DIAPHRAGM SEAL	1 2	COMPRESSOR	AAA BBB CCC	-VISIBLE TO OPERATOR -NORMALLY OPERATOR ACCESSIBLE	BYPASS LIN OF THE INS	IES, ETC., WHICH ARE NOT CRIT TRUMENTATION AND CONTROL STRUMENTATION SHEETS.	ICAL FOR AN UNDERSTANDING FUNCTIONS ARE NOT SHOWN	
j	FLOAT SWITCH	-1/2	PRESSURE RELIEF (OUT)	(2)	HEAT EXCHANGER	XXX	DISPLAY (INDICATION/CONTROLLER) -LOCATED INSIDE PANEL	5. SEE ELECT CONTROL / OR NOT PR	RICAL SHEETS AND SPECIFICAT AND INTERLOCK REQUIREMENT OVIDED BY THE INSTRUMENTAT	TIONS FOR ADDITIONAL S FOR EQUIPMENT NOT SHOWN TION SUPPLIER.	
	VALVES VALVE - OTHER IN-LINE TYPE NOT			0		AAA BBB CCC	-NOT VISIBLE TO OPERATOR -NORMALLY NOT ACCESSIBLE	6. IN THE EVE INSTRUMEN	NT OF DISCREPANCY BETWEEN	THE PROCESS &	
<u></u>	OTHERWISE IDENTIFIED	學	VACUUM RELIEF (IN)		FEED PUMP	_		INFORMATI	ON FROM THE LOOP DIAGRAMS	SHALL BE USED.	
_₩	KNIFE GATE VALVE	M	GATES SLUICE/SLIDE GATE	₽Q I	GRINDER/MACERATOR	<u> </u>	INTERLOCKING RELAY	HOA HAND/O	ABBREVIATIONS:		
<u>M</u>	THREE-WAY VALVE BALL VALVE	T	FLOW CONTROL GATE				DIGITAL INPUT	HOR HAND/O	FF/REMOTE DFF/COMPUTER DFF/REMOTE		
	GLOBE VALVE	~	MOTORS		BLOWER	∇	DIGITAL OUTPUT	LOS LOCKOU OSC OPEN/S RSL RAISE/S	JT STOP TOP/CLOSE TOP/LOWER COMPUTER		
D 8 Cl	PINCH VALVE	P T	VARIABLE SPEED MOTOR	-			ANALOG INPUT	UR LOCAL/I	REMOTE LOSE STOP		
M	GATE VALVE	M) PUMPS	CONSTANT SPEED MOTOR BLOWERS AND MISC EQUIPMENT		SILENCER	▼	ANALOG OUTPUT	A/M AUTO/N	IANUAL OMPUTER		
DKI	NEEDLE VALVE		CENTRIFUGAL BLOWER				SURGE SUPPRESSOR				
N	BUTTERFLY VALVE		SERVINI OGNE DESPIEN		PERISTALTIC METERING PUMP		OPTO ISOLATOR				
Z	CHECK VALVE WITH FLOW DIRECTION		CENTRIFUGAL PUMP				SIGNAL CONVERTER/ ISOLATOR */* - (INPUT/OUTPUT) * DEFINED AS FOLLOWS:				
KI	PLUG VALVE		DIAPHRAGM PUMP AND MOTOR	╢ -□-	ROCK TRAP		E - VOLTAGE I - CURRENT P - PNEUMATIC				
- <u>Z</u> -	PRESSURE-REDUCING REGULATOR INTERNAL PRESSURE TAP			╢ <u>~~</u>			PD - PULSE DURATION H - HYDRAULIC O - ELECTROMAGNETIC, SONIC				, De
<u></u>	BACK PRESSURE REGULATOR INTERNAL PRESSURE TAP	-1111	PROGRESSIVE CAVITY PUMP		PULSATION DAMPENER		R - RESISTANCE (ELECTRIC)				
A.	PRESSURE-REDUCING REGULATOR EXTERNAL PRESSURE TAP	Ţ	SUBMERSIBLE PUMP	-							GEORGE B. LUKE 60900
<u> </u>	BACK PRESSURE REGULATOR EXTERNAL PRESSURE TAP										SONAL 04/11/2
			DESIGNED BY: W. NILSSON DRAWN BY: H. OSIO SHEET CHK'D BY: B. DANG	Gunn	A la & Associates, Inc. LTING ENGINEERING	BRYAN STILL CF	REEK		STRUMENTATION END & SYMBOLS		PROJECT NO. 2381-284648 FILE NAME: I-1.DWC SHEET NO.
-			SHEET CHK'D BY: B. DANG CROSS CHK'D BY: J. FELGER APPROVED BY: G. LUKE Dallas. TX 752 Dallas. TX 752	CONSU. Texas I ord Suite 400	ILTING ENGINEERING Registration No. F-2593 Instrum Road WAST	TEWATER TREATI	MENT PLANT NTS	LLOI		•	I-1


	LINE SYMBOLS		EQUIPMENT/LOOP TAGGING	1 —	GENERAL ABBREVIATIONS	1		MEANINGS OF IDENTIFI	ICATION L	ETTERS			
		$\overline{}$	EQUIPMENT TAG USED TO IDENTIFY NON-INSTRUMENT		ANALOG INPUT ALARM PILOT LIGHT	-	THIS TABLE APPLIES ONLY T	O THE FUNCTIONAL IDEN	TIFICATION	OF INSTRUMENTS.			_
	MAJOR PROCESS LINE		EQUIPMENT	AO A	ANALOG OUTPUT		FIRST LE				SUCCEEDING LETTERS		
	MINOR PROCESS LINE	×	LOOP TAG USED TO TIE THE PROCESS FLOW		AIR SUPPLY APPLICATION SERVICE PROVIDER	-	MEASURED OR INITIATING VARIABLE	MODIFIER	RE/	ADOUT OR PASSIVE FUNCTION	OUTPUT FUNCTION	MODIFIER	
	MINOR TROOPS EINE		DIAGRAM TO A LOOP DIAGRAM	BFV I	BUTTERFLY VALVE	I A		+	ALAF		+	+	Ⅎ
	FUTURE PROCESS LINE	_	ANDARD VALVE AND PIPING USAGE	- CCTV /	CLOSED CIRCUIT TELEVISION METHANE	_	BURNER, COMBUSTION						コ
	+	DPIT		CL2 0	CHLORINE	С			l		CONTROL		_
—	EXISTING PROCESS LINE	100	BLOCK/BLEED VALVE ARRANGEMENT		CONDUCTIVITY		OR SPECIFIC GRAVITY	DIFFERENTIAL	1 L				
		X X X		CP (CONTROL PANEL	E			PRIM	MARY ELEMENT			4
	HARDWIRED SIGNAL	<u> </u>		CPU CRC	CENTRAL PROCESSING UNIT CONTROL ROOM CONSOLE	F G	FLOW RATE	RATIO (FRACTION)	1			+	4
	SOFT LINK	PI		CTU (CENTRAL TELEMETRY UNIT		, ,		GLAS	SS VIEWING DEVICE			4
	337 2.111	100	INSTRUMENTS WITH VALVE ONLY		DISTRIBUTED CONTROL UNIT DIGITAL OR DISCRETE INPUT	н	HAND		1 📖			HIGH OR OPEN	_
	HYDRAULIC LINK	Ĭ Ž™			DISSOLVED OXYGEN OR DIGITAL OUTPUT		CURRENT (ELECTRICAL)		INDIC	CATE			
	+				DISTRIBUTED PROCESSING UNIT ETHERNET PATCH PANEL	J	TIME OF TIME	SCAN	ł		+	+	4
- o - o -	PNEUMATIC LINK	PI		ES I	EMERGENCY STOP	K	SCHEDULE		1	T (DI OT)	CONTROL STATION	LOW OR CLOSED	_
,,_	CAPILLARY TUBE OR FILLED SYSTEM	100		ETM	ETHERNET SWITCH ELAPSED TIME METER		MOISTURE OR HUMIDITY	+	LIGH	IT (PILOT)		MIDDLE OR INTERMEDIATE	-
	SIGNAL		INSTRUMENTS WITH DIAPHRAGM SEAL	FC I	FAIL CLOSED		USERS CHOICE		LISE	R'S CHOICE		INTERMEDIATE USER'S CHOICE	4
~~~	ELECTROMAGNET OR SONIC SIGNAL (GUIDED)				FILTER CONTROL STATION	0	USER'S CHOICE		ORIF	ICE (RESTRICTION)	+	USER'S CHOICE	-
				FCV I	FLOW CONTROL VALVE	Р			POIN	IT (TEST NECTION)			٦
	(USED WHEN REFERRING TO A SHEET IN THE DESIGN SET)	PI		FLP I	FAIL LAST POSITION FAIL OPEN			INTEGRATE OR	1			+	7
	DESCRIPTION - WHERE FLOW IS GOING	PI 100 -1	INSTRUMENTS WITH ANNULAR SEAL	FOPP I	FIBER OPTIC PATCH PANEL	R	RADIATION	TOTALIZE	RECO	ORD	+	+	Ⅎ
	SHEET# - WHAT SHEET PROCESS CONTINUES				FEEDER PROTECTION RELAY HYDROGEN SULFIDE	s		SAFETY			switch		7
DESCRIPTION	ON				HUMAN MACHINE INTERFACE	Т	TEMPERATURE				TRANSMIT	†	
X SHEET# Y	X - USED WHEN TWO OR MORE ARROWS ARE		PANEL DETAIL SYMBOLS	10	JUNCTION BOX INPUT/OUTPUT	U	MULTIVARIABLE VIBRATION		MUL	TIFUNCTION	MULTIFUNCTION	MULTIFUNCTION	7
	REFERING TO THE SAME SHEET.	RUN	INDICATING LIGHT -R RED (ACTIVE EQUIPMENT)	IR I	INFARED		VIBRATION WEIGHT OR FORCE	+	WELI	L	VALVE, DAMPER OR LOUVER	UNCLASSIFIED	$\dashv$
	Y - USED WHEN TWO OR MORE ARROWS ARE REFERRING TO THE SAME SHEET.	(B)	-R RED (ACTIVE EQUIPMENT) -G GREEN (EQUIPMENT OFF) -W WHITE (POWER)		LIQUID AMMONIA SULFATE LOCAL CONTROL PANEL	X	UNCLASSIFIED	X AXIS		LASSIFIED	UNCLASSIFIED	UNCLASSIFIED	
	(USED WHEN REFERRING TO A SHEET NOT IN		-B BLUE (CONDITION IE BACKWASH IN PROGRESS)	LCS I	LOCAL CONTROL STATION	Y	EVENT, STATE	Y AXIS	1		RELAY, COMPUTE, CONVERT		
DESCRIPTION	THE DESIGN SET)		-A AMBER (ALARM CONDITION)	LPU J	LOCAL PROCESSING UNIT LOCAL TERMINAL SYSTEM	z	POSITION, DIMENSION	Z AXIS	1		DRIVE, ACTUATE OR UNCLASSIFIED CONTROL ELEMENT		
	DESCRIPTION - WHERE FLOW IS GOING	H/O/A	SWITCH -L/R (LOCAL - REMOTE)	MC I	MOTOR CONTROLLER	-			ш		ELEMENT		
		•	-L/O/A (LOCAL - OFF - AUTO) -L/O/R (LOCAL - OFF - REMOTE)	NAOCL :	SODIUM HYPOCHLORIDE NORMALLY CLOSED								
	CAT-5e ETHERNET CABLE		-H/O/A (HAND - OFF - AUTO)	NH3	AMMONIA	1 🗀	COMMON HMI/INSTRUM				ON HMI/INSTRUMENT ISA TAGGING		
— CAT5e—— CAT5e——	CAT-5e ETHERNET CABLE		-H/O/R (HAND - OFF - REMOTE)		NETWORK INTERFACE MODULE NORMALLY OPEN	ABB	BREVIATION	MEANING		ABBREVIATION	MEANING		
CAT6 CAT6	CAT-6 ETHERNET CABLE	START		MCC I	MOTOR CONTROL CENTER	」		DICATING TRANSMITTER	-		SPEED INDICATION SPEED INDICATING CONTROLLER	——	
****			PUSHBUTTON	MM I	MULTI MODE FIBER OPTIC CABLE SYSTEM MANUFACTURER-PROVIDED PLC	<b>-</b> ⊢		BIDUAL/INDICATION	-		TEMPERATURE INDICATING TRANSA	MITTER	
MB+ MB+	MODBUS PLUS CABLE			MPR I	MOTOR PROTECTION RELAY	」 ├─	7.0	ING TRANSMITTER	$\dashv$		TEMPERATURE ELEMENT	WITTER	
	+	START	PUSHBUTTON		OPERATIONS INTERFACE TERMINAL OVERLOAD	-	FE FLOW ELEMEN	т	$\dashv$		TEMPERATURE INDICATION		
	RS-485 CABLE		1 00100	ows (	OPERATOR WORKSTATION		FI FLOW INDICATI	ION	$\neg$		TEMPERATURE SWITCH HIGH		
	1				PUSH BUTTON PROCESS CONTROL SYSTEM INTEGRATOR	1	HS HAND SWITCH	-	$\neg$		WEIGHT INDICATING TRANSMITTER		
	RS-232 CABLE		HORN	pH I	HYDROGEN ION		JAL POWER ALARM				WEIGHT ELEMENT		
POF POF	POWER OVER ETHERNET CABLE	шыш			PROGRAMMABLE LOGIC CONTROLLER PROCESS MONITORING CONTROL SYSTEM		II CURRENT INDI				WEIGHT INDICATION		
- 100	POWER OVER ETTERNET OFBEE		•	POLY I	POLYMER			TING TRANSMITTER			MISC. EVENT LIGHT (IN REMOTE)		
T1 T1 T1	T1 LINE		BEACON		POWER QUALITY METER POWER SUPPLY	<b>↓</b>	LE LEVEL ELEMEN			2011	OPEN GATE/VALVE		
	1	_		PSU I	POWER SUPPLY UNIT	1 ⊢	LI LEVEL INDICAT		_	200	CLOSE GATE/VALVE		
SM SM SM	SINGLE MODE FIBER OPTIC CABLE	OIT	OPERATOR INTERFACE TERMINAL	PV PRC	PINCH VALVE REMOTE BASE CONTROLLER	-	LSH LEVEL SWITCH				POSITION SWITCH HIGH	——	
	+	ا لــــــــــــــــــــــــــــــــــــ	OF EIGHT ON INTERNACE TELESCOPE	RIO I	REMOTE INPUT OUTPUT	_	LSL LEVEL SWITCH		-	ZSL	POSITION SWITCH LOW VALVE/GATE OPEN		
— MM—— MM—— MM——	MULTIMODE FIBER OPTIC CABLE	<u> </u>	SECURITY SYSTEM SYMBOLS	RTU I	REMOTE TERMINAL UNIT SUPERVISORY CONTROL AND DATA AQUISITION	_	LAL LEVEL ALARM I		-	ZLH	VALVE/GATE CLOSED		
1			FIXED SURVEILLANCE CAMERA	SM :	SINGLE MODE FIBER OPTIC CABLE	1 —		DICATING TRANSMITTER	$\dashv$		POSITION INDICATING TRANSMITTER	:R	
	- SIGNAL CROSSING				SULFUR DIOXIDE SOLENOID	-	PE PRESSURE ELE	EMENT	$\neg$				
` `		□□ PTZ	PAN/TILT/ZOOM SURVEILLANCE CAMERA	SPD :	SURGE PROTECTION DEVICE	1 -	PI PRESSURE IND	JICATION	$\dashv$				
<u> </u>	+			UPS I	UNINTERRUPTIBLE POWER SUPPLY TERMINATION CABINET	1  -	PSH PRESSURE SW	TCH HIGH	$\neg$				
<b>├</b>	PROCESS LINE CROSSING				TURBIDITY	1 🗀	PSL PRESSURE SW	TCH HIGH					
					VIBRATION VARIABLE FREQUENCY DRIVE								
i	1			VFD VLV		1							7
<u> </u>	PROCESS LINE/ HARDWIRE SIGNAL CROSSING					i							File O
													There
													GEO GEO
													1 0c0
													No.
													100
		DESIGNED BY:	W. NILSSON H. OSIO CDM	GAI	BR'	YAN STILL	CREEK			INSTE	RUMENTATION		PROJECT NO
		DRAWN BY:	H.OSIO	Gupta & Associate CONSULTING ENGINE							D & SYMBOLS - II		FILE NAME:
+		SHEET CHK'D BY: CROSS CHK'D BY		CONSULTING ENGINE Texas Registration No. 13717 Notice Read Delles, Texas 75244 Tel: 973-490-7661	.F-2593 \//ΔSTE\Λ/Δ¬	ED TDE	ATMENT PLANT			LEGENL	J & STIVIDOLS - II		Si

























11490 Westheimer Rd., Suite 700 Houston, Texas 77077 tel: 713-423-7300 fax: 281-589-8295

June 27, 2024

Mr. Mark Jurica Treatment and Compliance Manager City of Bryan 205 E. 28th Street Bryan, TX 77803 Still Creek Wastewater Treatment Plant (WWTP) Improvements Project Recommendation of Award Subject:

Dear Mr. Jurica:

CDM Smith has completed the review of the public bids for construction of the Still Creek WWTP Improvements Project. On June 19th, 2024, a single Bid was received and opened by the City of Bryan for the subject project.

- Teal Services LLC. Total Base Bid Amount was \$6,061,300.00
- The Engineer's Opinion of Probable Construction Cost was \$5,711,000

The bidder supplied a bid bond or security in the amount of 5 percent of the Total Base Bid Amount, which was retained by City staff at the bid opening. The bidder acknowledged receipt of Addenda Nos. 1-4. Teal Construction Company provided the following information as required by the Bid Documents:

- Bid Form per Section 00300, Addendum No. 4
- Bid Security per Section 00300
- Statement of Bidders Experience per Section 00400

project at the Burton Creek WWTP. Therefore, CDM Smith recommends that the subject contract be reference project is less than the total value of this contract, there are three major elements to this work on this project that successfully executed work of similar scope on a previous improvements reference projects. Teal Services LLC is planning to use Subcontractors to perform portions of the CDM Smith reviewed the documentation submitted by Teal Services LLC, and finds them to be a qualified bidder to perform the work as outlined in the contract documents. While their largest project and taken individually, each one is of similar size and scope as the work included in the awarded to Teal Services LLC. in the amount of \$6,061,300.00.



Mr. Mark Jurica June 27, 2024 Page 2

Should you have any questions or require additional information, please contact me at any time.

Very truly yours,

Monica Stiggins, P.E. Project Manager CDM Smith Inc. TBPE Firm Registration No. F-3043